

COMPRESSOR DEFINITION

Designation	NJ 7231GP
Nominal Voltage/Frequency	380-420 V 50 Hz / 440-480 V 60 Hz
Engineering Number	948CM11

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-407C		
3 Nominal voltage and frequency	380-420 / 50	[V / Hz]	
4 Application type	Air Conditioning		
4.1 Evaporating temperature range	0°C to 15°C	(32°F to 59°F)	
5 Motor type	3PHASE		
6 Starting torque	HST - Hight starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	21.9	[kgf/cm ²] (311 psig)	/ °C - °F
9.2 Peak	24.8	[kgf/cm ²] (353 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1+	[hp]
2 Displacement	26.11	[cm ³] (1.593 cu.in)
2.1 Bore [mm]	41.770	
2.2 Stroke [mm]	19.066	
3 Lubricant charge	750	[ml] (25.36 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	20.1	[kg] (44.31 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	380-420 V 50 Hz / 440-480 V 60 Hz 3 ~ (Three phase)	
2 Starting device type	3PHASE	
2.1 Starting device		
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	34HM260-49	
6 Start winding resistance	[Ω at 25°C (77°F)] +/- 8%	
7 Run winding resistance	10.20	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	18.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification		

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @380V50Hz			ASHRAEHBP46 Fan		Evaporating temperature (Condensing temperature		7.2°C (44.96°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
11467	2890	3360	1416	3.04	68.44	8.10	2.04	2.37

E - PERFORMANCE - CURVES

TEST CONDITIONS: @380V50Hz			ASHRAE46 Fan		(Condensing temperature 35°C (+95°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
0 (+32)	11478	2892	3363	1017	2.62	57.89	11.28	2.84	3.31
+5 (+41)	14256	3592	4177	1074	2.67	72.43	13.28	3.35	3.89
+10 (+50)	17316	4364	5074	1127	2.73	88.72	15.37	3.87	4.50
+15 (+59)	20658	5206	6053	1176	2.79	106.92	17.56	4.42	5.14

TEST CONDITIONS: @380V50Hz			ASHRAE46 Fan		(Condensing temperature 45°C (+113°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
0 (+32)	9958	2509	2918	1135	2.76	54.21	8.76	2.21	2.57
+5 (+41)	12352	3113	3619	1224	2.85	67.75	10.10	2.54	2.96
+10 (+50)	15052	3793	4410	1300	2.93	83.33	11.59	2.92	3.40
+15 (+59)	18057	4550	5291	1362	2.99	101.08	13.25	3.34	3.88

TEST CONDITIONS: @380V50Hz			ASHRAE46 Fan		(Condensing temperature 55°C (+131°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
0 (+32)	8294	2090	2430	1257	2.88	49.20	6.61	1.67	1.94
+5 (+41)	10351	2608	3033	1384	3.02	61.93	7.47	1.88	2.19
+10 (+50)	12737	3210	3732	1487	3.15	76.97	8.56	2.16	2.51
+15 (+59)	15451	3894	4528	1567	3.25	94.49	9.87	2.49	2.89

F - EXTERNAL CHARACTERISTICS

1 Base plate	American Standard		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	9.6 +0.07/+0.00	[mm]	(0.378" +0.003"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Vertical		
3.2 DISCHARGE	8 +0.07/+0.00	[mm]	(0.315" +0.003"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted J		
3.3 PROCESS	6.42 +0.08/+0.00	[mm]	(0.253" +0.003"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Vertical		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		