

COMPRESSOR DEFINITION

Designation	NT 6222GKV
Nominal Voltage/Frequency	115 V 60 Hz
Engineering Number	922KG08

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-404A		
3 Nominal voltage and frequency	115 / 60	[V / Hz]	
4 Application type	Medium Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-20°C to 10°C	(-4°F to 50°F)	
5 Motor type	CSCR		
6 Starting torque	HST - Hight starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	25.2	[kgf/cm ²] (358 psig)	/ °C - °F
9.2 Peak	28.3	[kgf/cm ²] (402 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1	[hp]
2 Displacement	17.39	[cm ³] (1.061 cu.in)
2.1 Bore [mm]	34.120	
2.2 Stroke [mm]	19.030	
3 Lubricant charge	450	[ml] (15.22 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	17	[kg] (37.48 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	115 V 60 Hz 1~ (Single phase)	
2 Starting device type	Voltage Relay	
2.1 Starting device	RVA9AD3C-121	
3 Start capacitor	243-292(250)	[µF(VAC minimum)]
4 Run capacitor	35(400)	[µF(VAC minimum)]
5 Motor protection	T0888/C9	
6 Start winding resistance	2.60	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	0.40	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	-	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	UL	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @115V60Hz			ARIMBP Fan		Evaporating temperature (Condensing temperature		-6.7°C (19.94°F) 48.9°C (120.02°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
5350	1348	1568	993	9.47	57.65	5.39	1.36	1.58

E - PERFORMANCE - CURVES

TEST CONDITIONS: @115V60Hz		ARI4 Fan			(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	4281	1079	1254	698	7.01	36.12	6.12	1.54	1.79
-15	(+ 5)	5389	1358	1579	768	7.58	46.07	7.02	1.77	2.06
-10	(+14)	6657	1678	1951	834	8.13	57.61	7.99	2.01	2.34
-5	(+23)	8084	2037	2369	895	8.65	70.98	9.04	2.28	2.65
0	(+32)	9670	2437	2834	952	9.15	86.39	10.17	2.56	2.98
+5	(+41)	11416	2877	3345	1004	9.62	104.03	11.37	2.87	3.33
+10	(+50)	13320	3357	3903	1052	10.07	124.14	12.65	3.19	3.71

TEST CONDITIONS: @115V60Hz		ARI4 Fan			(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	3377	851	990	731	7.32	33.05	4.64	1.17	1.36
-15	(+ 5)	4347	1095	1274	819	8.04	42.93	5.31	1.34	1.55
-10	(+14)	5456	1375	1599	903	8.74	54.60	6.03	1.52	1.77
-5	(+23)	6704	1689	1964	982	9.43	68.26	6.81	1.72	2.00
0	(+32)	8090	2039	2371	1057	10.10	84.12	7.64	1.93	2.24
+5	(+41)	9615	2423	2818	1127	10.76	102.40	8.53	2.15	2.50
+10	(+50)	11279	2842	3305	1193	11.40	123.31	9.47	2.39	2.78

TEST CONDITIONS: @115V60Hz		ARI4 Fan			(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	2704	681	792	778	7.66	31.79	3.47	0.87	1.02
-15	(+ 5)	3471	875	1017	879	8.49	41.29	3.95	1.00	1.16
-10	(+14)	4357	1098	1277	976	9.31	52.75	4.47	1.13	1.31
-5	(+23)	5361	1351	1571	1069	10.12	66.37	5.02	1.27	1.47
0	(+32)	6484	1634	1900	1157	10.92	82.36	5.61	1.41	1.64
+5	(+41)	7725	1947	2264	1240	11.72	100.95	6.23	1.57	1.83
+10	(+50)	9085	2290	2662	1319	12.51	122.33	6.88	1.73	2.02

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal
2 Tray holder	No
3 Connectors	
3.1 SUCTION	12.7 +0.25/-0.25 [mm] (0.500" +0.010"/-0.010")
3.1.1 Material	Steel
3.1.2 Shape	ROTOLOCK(Ex. thr. 1"-14UNS-2A)
3.2 DISCHARGE	6.42 +0.08/+0.00 [mm] (0.253" +0.003"/+0.000")
3.2.1 Material	Copper
3.2.2 Shape	Vertical
3.3 PROCESS	6.42 +0.08/+0.00 [mm] (0.253" +0.003"/+0.000")
3.3.1 Material	Copper
3.3.2 Shape	Vertical
3.4 Oil cooler (Copper)	No [mm]
3.5 Connector sealing	Rubber Plugs