

### COMPRESSOR DEFINITION

Designation	EG Y80HLP
Nominal Voltage/Frequency	115-127 V 60 Hz
Engineering Number	513700158

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	115-127 / 60	[ V / Hz ]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	85 to 110 V	98 to 140 V
8.2 LBP (43°C Ambient temperature)	Static	85 to 110 V	98 to 140 V
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	16.2	[kgf/cm <sup>2</sup> ] (230 psig)	/ °C - °F
9.2 Peak (gauge)	20.6	[kgf/cm <sup>2</sup> ] (293 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation	1/4	[hp]
2 Displacement	6.76	[cm <sup>3</sup> ] (0.413 cu.in)
2.1 Bore [mm]	22.500	
2.2 Stroke [mm]	17.000	
3 Lubricant charge	280	[ml] (9.47 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO10	
4 Weight (with oil charge)	11.37	[kg] (25.07 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm <sup>2</sup> ] (2.84 to 4.27 psig)

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	115-127 V 60 Hz 1 ~ (Single phase)	
2 Starting device type	Combo	
2.1 Starting device	5SP04X445K/5SP14X445K	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	12(180)	[µF(VAC minimum)]
5 Motor protection	5SP04X445KFX	
6 Start winding resistance	5.60	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	3.50	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	-	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	UL	

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @115V60Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
815	205	239	143	1.30	4.63	5.70	1.44	1.67

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 45°C (+113°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	436	110	128	97	0.90	2.46	4.52	1.14	1.32
-30 (-22)	609	154	179	115	1.08	3.45	5.28	1.33	1.55
-25 (-13)	823	207	241	134	1.25	4.67	6.11	1.54	1.79
-20 (- 4)	1082	273	317	154	1.42	6.16	7.00	1.76	2.05
-15 (+ 5)	1394	351	409	175	1.59	7.96	7.96	2.01	2.33
-10 (+14)	1766	445	518	196	1.77	10.12	9.00	2.27	2.64

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 55°C (+131°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	400	101	117	96	0.90	2.27	4.19	1.05	1.23
-30 (-22)	556	140	163	115	1.09	3.15	4.83	1.22	1.41
-25 (-13)	751	189	220	137	1.27	4.26	5.50	1.39	1.61
-20 (- 4)	993	250	291	160	1.47	5.65	6.21	1.56	1.82
-15 (+ 5)	1287	324	377	185	1.68	7.35	6.95	1.75	2.04
-10 (+14)	1642	414	481	212	1.91	9.41	7.75	1.95	2.27

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 65°C (+149°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	334	84	98	93	0.87	1.89	3.59	0.90	1.05
-30 (-22)	478	120	140	113	1.06	2.71	4.22	1.06	1.24
-25 (-13)	661	167	194	136	1.26	3.75	4.85	1.22	1.42
-20 (- 4)	891	225	261	163	1.48	5.07	5.49	1.38	1.61
-15 (+ 5)	1175	296	344	192	1.73	6.70	6.13	1.54	1.80
-10 (+14)	1518	383	445	223	2.01	8.70	6.79	1.71	1.99

### F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal EG/F/AMEM version 2		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.1.1 Material	Copper		
3.1.2 Shape	Straight		
3.2 DISCHARGE	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.3.1 Material	Copper		
3.3.2 Shape	Straight		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		