

COMPRESSOR DEFINITION

Designation	EG Z80HLP
Nominal Voltage/Frequency	115-127 V 60 Hz
Engineering Number	513700196

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	115-127 / 60	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	85 to 110 V	98 to 140 V
8.2 LBP (43°C Ambient temperature)	Static	85 to 110 V	98 to 140 V
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	16.2	[kgf/cm ²] (230 psig)	/ °C - °F
9.2 Peak (gauge)	20.6	[kgf/cm ²] (293 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/4	[hp]
2 Displacement	6.76	[cm ³] (0.413 cu.in)
2.1 Bore [mm]	22.500	
2.2 Stroke [mm]	17.000	
3 Lubricant charge	280	[ml] (9.47 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO7	
4 Weight (with oil charge)	11.54	[kg] (25.44 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	115-127 V 60 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	7M4R7MD3/8EA14C3/8EA1B3/8EA21C3/8EA3B3/8EA4B3/8M4I	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	12(180)	[µF(VAC minimum)]
5 Motor protection	4TM445KFBYY-53	
6 Start winding resistance	5.60	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	3.50	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	13.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	1.70	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	UL	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @115V60Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
850	214	249	143	1.28	4.83	5.96	1.50	1.75

E - PERFORMANCE - CURVES

TEST CONDITIONS: @115V60Hz		ASHRAE32 Static				(Condensing temperature 35°C (+95°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	511	129	150	109	0.81	2.89	4.68	1.18	1.37
-30	(-22)	685	173	201	120	0.94	3.88	5.72	1.44	1.68
-25	(-13)	889	224	261	131	1.06	5.05	6.82	1.72	2.00
-20	(- 4)	1134	286	332	142	1.19	6.45	7.99	2.01	2.34
-15	(+ 5)	1429	360	419	154	1.32	8.16	9.25	2.33	2.71
-10	(+14)	1784	449	523	167	1.47	10.22	10.63	2.68	3.12

TEST CONDITIONS: @115V60Hz		ASHRAE32 Static				(Condensing temperature 45°C (+113°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	455	115	133	97	0.90	2.57	4.68	1.18	1.37
-30	(-22)	642	162	188	115	1.05	3.64	5.59	1.41	1.64
-25	(-13)	856	216	251	132	1.19	4.86	6.51	1.64	1.91
-20	(- 4)	1105	278	324	148	1.34	6.29	7.44	1.87	2.18
-15	(+ 5)	1399	353	410	165	1.49	7.99	8.42	2.12	2.47
-10	(+14)	1750	441	513	184	1.66	10.03	9.46	2.38	2.77

TEST CONDITIONS: @115V60Hz		ASHRAE32 Static				(Condensing temperature 55°C (+131°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	357	90	105	88	0.86	2.02	4.09	1.03	1.20
-30	(-22)	556	140	163	112	1.04	3.15	4.96	1.25	1.45
-25	(-13)	778	196	228	135	1.22	4.41	5.78	1.46	1.69
-20	(- 4)	1030	260	302	158	1.41	5.86	6.57	1.65	1.92
-15	(+ 5)	1324	334	388	181	1.61	7.56	7.34	1.85	2.15
-10	(+14)	1669	421	489	205	1.82	9.56	8.14	2.05	2.38

E - PERFORMANCE - CURVES

TEST CONDITIONS: @115V60Hz		ASHRAE32 Static			(Condensing temperature 65°C (+149°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	243	61	71	74	0.73	1.37	3.24	0.82	0.95
-30	(-22)	454	114	133	106	0.98	2.57	4.15	1.05	1.22
-25	(-13)	682	172	200	136	1.22	3.87	4.96	1.25	1.45
-20	(- 4)	937	236	275	165	1.47	5.33	5.68	1.43	1.67
-15	(+ 5)	1229	310	360	195	1.74	7.01	6.35	1.60	1.86
-10	(+14)	1568	395	459	226	2.02	8.98	6.97	1.76	2.04

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal EG/F/AMEM version 2		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.1.1 Material	Copper		
3.1.2 Shape	Straight		
3.2 DISCHARGE	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.3.1 Material	Copper		
3.3.2 Shape	Straight		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		