

COMPRESSOR DEFINITION

Designation	EG Z100HLP
Nominal Voltage/Frequency	115-127 V 60 Hz
Engineering Number	513700238

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	115-127 / 60	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	85 to 110 V	98 to 140 V
8.2 LBP (43°C Ambient temperature)	Static	85 to 110 V	98 to 140 V
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	16.2	[kgf/cm ²] (230 psig)	/ °C - °F
9.2 Peak (gauge)	20.6	[kgf/cm ²] (293 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/3	[hp]
2 Displacement	7.95	[cm ³] (0.485 cu.in)
2.1 Bore [mm]	22.500	
2.2 Stroke [mm]	20.000	
3 Lubricant charge	280	[ml] (9.47 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO10	
4 Weight (with oil charge)	11.45	[kg] (25.24 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	115-127 V 60 Hz 1 ~ (Single phase)	
2 Starting device type	TSD	
2.1 Starting device	TSD- 115V	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	12(180)	[µF(VAC minimum)]
5 Motor protection	4TM445NFBYY-53	
6 Start winding resistance	5.90	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	2.75	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	17.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	2.70	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	UL	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @115V60Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
1033	260	303	173	1.71	5.87	5.96	1.50	1.75

E - PERFORMANCE - CURVES

TEST CONDITIONS: @115V60Hz		ASHRAE32 Static				(Condensing temperature 35°C (+95°F))			
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	616	155	181	117	1.16	3.49	5.24	1.32	1.54
-30 (-22)	809	204	237	136	1.33	4.59	5.97	1.51	1.75
-25 (-13)	1046	264	306	155	1.51	5.94	6.78	1.71	1.99
-20 (- 4)	1337	337	392	174	1.69	7.61	7.69	1.94	2.25
-15 (+ 5)	1693	427	496	194	1.89	9.67	8.72	2.20	2.56
-10 (+14)	2124	535	623	214	2.10	12.17	9.90	2.50	2.90

TEST CONDITIONS: @115V60Hz		ASHRAE32 Static				(Condensing temperature 45°C (+113°F))			
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	553	139	162	116	1.27	3.13	4.79	1.21	1.40
-30 (-22)	757	191	222	137	1.43	4.29	5.52	1.39	1.62
-25 (-13)	1000	252	293	160	1.61	5.68	6.28	1.58	1.84
-20 (- 4)	1292	326	379	182	1.80	7.35	7.08	1.78	2.07
-15 (+ 5)	1643	414	481	206	2.01	9.38	7.95	2.00	2.33
-10 (+14)	2064	520	605	230	2.22	11.83	8.91	2.25	2.61

TEST CONDITIONS: @115V60Hz		ASHRAE32 Static				(Condensing temperature 55°C (+131°F))			
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	466	117	137	110	1.25	2.64	4.23	1.07	1.24
-30 (-22)	683	172	200	137	1.44	3.87	4.99	1.26	1.46
-25 (-13)	934	235	274	164	1.65	5.30	5.72	1.44	1.68
-20 (- 4)	1228	309	360	192	1.88	6.99	6.44	1.62	1.89
-15 (+ 5)	1575	397	462	220	2.13	8.99	7.18	1.81	2.10
-10 (+14)	1988	501	582	250	2.38	11.39	7.96	2.01	2.33

E - PERFORMANCE - CURVES

TEST CONDITIONS: @115V60Hz		ASHRAE32 Static			(Condensing temperature 65°C (+149°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	333	84	98	98	1.14	1.89	3.41	0.86	1.00
-30	(-22)	565	142	166	131	1.38	3.20	4.24	1.07	1.24
-25	(-13)	824	208	242	164	1.66	4.68	4.97	1.25	1.46
-20	(- 4)	1121	283	329	199	1.95	6.38	5.65	1.42	1.65
-15	(+ 5)	1467	370	430	235	2.26	8.37	6.28	1.58	1.84
-10	(+14)	1872	472	549	272	2.59	10.72	6.90	1.74	2.02

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal EG/F/AMEM version 2		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.1.1 Material	Copper		
3.1.2 Shape	Straight		
3.2 DISCHARGE	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.3.1 Material	Copper		
3.3.2 Shape	Straight		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		