

### COMPRESSOR DEFINITION

Designation	EM U30HSC
Nominal Voltage/Frequency	115 V 60 Hz
Engineering Number	513308009

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	115 / 60	[ V / Hz ]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	85 to 110 V	103 to 135 V
8.2 LBP (43°C Ambient temperature)	Static	85 to 110 V	103 to 135 V
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	14.2	[kgf/cm <sup>2</sup> ] (202 psig)	/ °C - °F
9.2 Peak	15.9	[kgf/cm <sup>2</sup> ] (226 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation	1/10	[hp]
2 Displacement	3.00	[cm <sup>3</sup> ] (0.183 cu.in)
2.1 Bore [mm]	19.000	
2.2 Stroke [mm]	10.600	
3 Lubricant charge	160	[ml] (5.41 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO10	
4 Weight (with oil charge)	7.16	[kg] (15.78 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm <sup>2</sup> ] (2.84 to 4.27 psig)

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	115 V 60 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	8EA14C3/8EA1B3/8EA21C3/8EA3B3/8EA4B3/QPS2-A4R7MD3	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	12(180)	[µF(VAC minimum)]
5 Motor protection	4TM197NFBYY-53	
6 Start winding resistance	7.00	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	8.40	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	5.50	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	1.00	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	CE - UKCA - UL	

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @115V60Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
328	83	96	70	0.65	1.86	4.67	1.18	1.37

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 45°C (+113°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	174	44	51	53	0.49	0.99	3.29	0.83	0.96
-30 (-22)	251	63	74	60	0.54	1.42	4.17	1.05	1.22
-25 (-13)	347	87	102	69	0.60	1.97	5.06	1.28	1.48
-20 (- 4)	462	116	135	77	0.67	2.63	5.98	1.51	1.75
-15 (+ 5)	596	150	175	86	0.74	3.40	6.96	1.75	2.04
-10 (+14)	749	189	219	94	0.81	4.29	8.01	2.02	2.35

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 55°C (+131°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	137	34	40	51	0.47	0.77	2.66	0.67	0.78
-30 (-22)	211	53	62	60	0.54	1.20	3.55	0.89	1.04
-25 (-13)	305	77	89	69	0.61	1.73	4.41	1.11	1.29
-20 (- 4)	418	105	122	79	0.69	2.38	5.26	1.32	1.54
-15 (+ 5)	550	138	161	90	0.78	3.14	6.12	1.54	1.79
-10 (+14)	701	177	205	100	0.87	4.02	7.01	1.77	2.05

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 65°C (+149°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	91	23	27	48	0.46	0.52	1.92	0.48	0.56
-30 (-22)	163	41	48	57	0.53	0.92	2.85	0.72	0.83
-25 (-13)	253	64	74	68	0.62	1.44	3.70	0.93	1.08
-20 (- 4)	363	91	106	80	0.71	2.06	4.50	1.13	1.32
-15 (+ 5)	492	124	144	93	0.82	2.81	5.26	1.33	1.54
-10 (+14)	640	161	188	106	0.92	3.67	6.02	1.52	1.76

### F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal EG/F/AMEM version 2		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.1.1 Material	Copper		
3.1.2 Shape	Straight		
3.2 DISCHARGE	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted		
3.3 PROCESS	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.3.1 Material	Copper		
3.3.2 Shape	Straight		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		