

### COMPRESSOR DEFINITION

Designation	<b>F GS100HAS</b>
Nominal Voltage/Frequency	<b>100 V 50-60 Hz</b>
Engineering Number	<b>513200872</b>

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	100 / 50-60	[ V / Hz ]	
4 Application type	Low-Medium (Plus) Back Pressure		
4.1 Evaporating temperature range	-35°C to 5°C	(-31°F to 41°F)	
5 Motor type	RSCR-CSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static/Fan	85 to 110 V	85 to 110 V
8.2 LBP (43°C Ambient temperature)	Static/Fan	85 to 110 V	85 to 110 V
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	14.2	[kgf/cm <sup>2</sup> ] (202 psig)	/ °C - °F
9.2 Peak	15.9	[kgf/cm <sup>2</sup> ] (226 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation	1/3	[hp]
2 Displacement	9.04	[cm <sup>3</sup> ] (0.552 cu.in)
2.1 Bore [mm]	24.000	
2.2 Stroke [mm]	20.000	
3 Lubricant charge	280	[ml] (9.47 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	11.52	[kg] (25.40 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm <sup>2</sup> ] (2.84 to 4.27 psig)

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	100 V 50-60 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	7M4R7MB3/7M4R7MD3/8EA14B11/8EA14C3/8EA14D7/QPS2-/	
3 Start capacitor	378-454(130)	[µF(VAC minimum)]
4 Run capacitor	12(155)	[µF(VAC minimum)]
5 Motor protection	5TM801KFBZZ-53	
6 Start winding resistance	4.47	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	1.12	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50/60 Hz)	30.90/28.30	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50/60 Hz)	5.10/4.36	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50/60 Hz)	5.96/5.23	[A] - Measured according to UL 984
11 Approval boards certification		

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: <b>@100V50Hz</b>			<b>FUJI HEAT32</b> <b>Static</b>		Evaporating temperature (Condensing temperature	<b>-10°C (14°F)</b> <b>75°C (167°F)</b>		
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
1559	393	457	287	3.98		5.43	1.37	1.59

TEST CONDITIONS: <b>@100V60Hz</b>			<b>FUJI HEAT32</b> <b>Static</b>		Evaporating temperature (Condensing temperature	<b>-10°C (14°F)</b> <b>75°C (167°F)</b>		
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
1907	481	559	329	3.88		5.80	1.46	1.70

### E - PERFORMANCE - CURVES

### F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal EG/F/AMEM version 2		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.2 +0.12/-0.08	[mm]	(0.323" +0.005"/-0.003")
3.1.1 Material	Copper		
3.1.2 Shape	Straight		
3.2 DISCHARGE	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.3.1 Material	Copper		
3.3.2 Shape	Straight		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		