

### COMPRESSOR DEFINITION

|                           |                 |
|---------------------------|-----------------|
| Designation               | EG Y60HLP       |
| Nominal Voltage/Frequency | 115-127 V 60 Hz |
| Engineering Number        | 513700150       |

### A - APPLICATION / LIMIT WORKING CONDITIONS

|  |                                   |                                   |             |
|--|-----------------------------------|-----------------------------------|-------------|
| 1 Type                                     | Hermetic reciprocating compressor |                                   |             |
| 2 Refrigerant                              | R-134a                            |                                   |             |
| 3 Nominal voltage and frequency            | 115-127 / 60                      | [ V / Hz ]                        |             |
| 4 Application type                         | Low Back Pressure                 |                                   |             |
| 4.1 Evaporating temperature range          | -35°C to -10°C                    | (-31°F to 14°F)                   |             |
| 5 Motor type                               | RSCR                              |                                   |             |
| 6 Starting torque                          | LST - Low Starting Torque         |                                   |             |
| 7 Expansion device                         | Capillary tube                    |                                   |             |
| 8 Compressor cooling                       |                                   | Operating voltage range           |             |
|  |                                   | 50 Hz                             | 60 Hz       |
| 8.1 LBP (32°C Ambient temperature)         | Static                            | 85 to 110 V                       | 98 to 140 V |
| 8.2 LBP (43°C Ambient temperature)         | Static                            | 85 to 110 V                       | 98 to 140 V |
| 8.3 HBP (32°C Ambient temperature)         | -                                 | -                                 | -           |
| 8.4 HBP (43°C Ambient temperature)         | -                                 | -                                 | -           |
| 9 Maximum condensing pressures/temperature |                                   |                                   |             |
| 9.1 Operating (gauge)                      | 16.2                              | [kgf/cm <sup>2</sup> ] (230 psig) | / °C - °F   |
| 9.2 Peak (gauge)                           | 20.6                              | [kgf/cm <sup>2</sup> ] (293 psig) | / °C - °F   |
| 10 Maximum winding temperature             | 130                               | [ °C ]                            |             |

### B - MECHANICAL DATA

|                               |               |  |
|-------------------------------|---------------|--|
| 1 Commercial designation      | 1/5           | [hp]                                       |
| 2 Displacement                | 5.56          | [cm <sup>3</sup> ] (0.339 cu.in)           |
| 2.1 Bore [mm]                 | 22.500        |  |
| 2.2 Stroke [mm]               | 14.000        |  |
| 3 Lubricant charge            | 280           | [ml] (9.47 fl.oz.)                         |
| 3.1 Lubricants approved       |               |  |
| 3.2 Lubricants type/viscosity | ESTER / ISO10 |  |
| 4 Weight (with oil charge)    | 10.75         | [kg] (23.70 lb.)                           |
| 5 Nitrogen charge             | 0.2 to 0.3    | [kgf/cm <sup>2</sup> ] (2.84 to 4.27 psig) |

### C - ELETRICAL DATA

|  |                                    |                                    |
|--|------------------------------------|------------------------------------|
| 1 Nominal Voltage/Frequency/Number of Phases | 115-127 V 60 Hz 1 ~ (Single phase) |                                    |
| 2 Starting device type                       | Combo                              |                                    |
| 2.1 Starting device                          | 5SP04X319N/5SP14X319N              |                                    |
| 3 Start capacitor                            | -                                  | [µF(VAC minimum)]                  |
| 4 Run capacitor                              | 15(180)                            | [µF(VAC minimum)]                  |
| 5 Motor protection                           | 5SP04X319NFX                       |                                    |
| 6 Start winding resistance                   | 5.70                               | [Ω at 25°C (77°F)] +/- 8%          |
| 7 Run winding resistance                     | 5.10                               | [Ω at 25°C (77°F)] +/- 8%          |
| 8 LRA - Locked rotor amperage (60 Hz)        | -                                  | [A] - Measured according to UL 984 |
| 9 FLA - Full load amperage L/MBP (60 Hz)     | -                                  | [A] - Measured according to UL 984 |
| 10 FLA - Full Load Amperage HBP (60 Hz)      | -                                  | [A] - Measured according to UL 984 |
| 11 Approval boards certification             | UL                                 |                                    |

### D - PERFORMANCE - CHECK POINT DATA

|                               |          |     |                                |                                  |  |                           |  |       |
|-------------------------------|----------|-----|--------------------------------|----------------------------------|--|---------------------------|--|-------|
| TEST CONDITIONS:<br>@115V60Hz |          |     | ASHRAELBP32<br>Static          |                                  | Evaporating temperature<br>(Condensing temperature |                           | -23.3°C (-9.94°F)<br>54.4°C (129.92°F) |       |
| Cooling capacity<br>+/- 5%    |          |     | Power<br>consumption<br>+/- 5% | Current<br>consumption<br>+/- 5% | Gas flow<br>rate<br>+/- 5%                         | EFFICIENCY RATE<br>+/- 7% |  |       |
| [Btu/h]                       | [kcal/h] | [W] | [W]                            | [A]                              | [kg/h]   | [Btu/Wh]                  | [kcal/Wh]                              | [W/W] |
| 620                           | 156      | 182 | 112                            | 1.01                             | 3.52   | 5.54                      | 1.40                                   | 1.62  |

### E - PERFORMANCE - CURVES

|                               |                            |          |                    |                                |  |                            |                           |           |       |
|-------------------------------|----------------------------|----------|--------------------|--------------------------------|--|----------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS:<br>@115V60Hz |                            |          | ASHRAE32<br>Static |                                | (Condensing temperature 45°C (+113°F)) |                            |                           |           |       |
| Evaporating<br>temperature    | Cooling capacity<br>+/- 5% |          |                    | Power<br>consumption<br>+/- 5% | Current<br>consumption<br>+/- 5%       | Gas flow<br>rate<br>+/- 5% | EFFICIENCY RATE<br>+/- 7% |           |       |
| °C (°F)                       | [Btu/h]                    | [kcal/h] | [W]                | [W]                            | [A]                                    | [kg/h]                     | [Btu/Wh]                  | [kcal/Wh] | [W/W] |
| -35 (-31)                     | 325                        | 82       | 95                 | 78                             | 0.73                                   | 1.84                       | 4.16                      | 1.05      | 1.22  |
| -30 (-22)                     | 470                        | 118      | 138                | 92                             | 0.84                                   | 2.67                       | 5.09                      | 1.28      | 1.49  |
| -25 (-13)                     | 639                        | 161      | 187                | 106                            | 0.95                                   | 3.63                       | 6.01                      | 1.51      | 1.76  |
| -20 (- 4)                     | 841                        | 212      | 247                | 121                            | 1.08                                   | 4.79                       | 6.96                      | 1.75      | 2.04  |
| -15 (+ 5)                     | 1089                       | 274      | 319                | 136                            | 1.21                                   | 6.22                       | 7.97                      | 2.01      | 2.33  |
| -10 (+14)                     | 1392                       | 351      | 408                | 152                            | 1.35                                   | 7.97                       | 9.09                      | 2.29      | 2.66  |

|                               |                            |          |                    |                                |  |                            |                           |           |       |
|-------------------------------|----------------------------|----------|--------------------|--------------------------------|--|----------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS:<br>@115V60Hz |                            |          | ASHRAE32<br>Static |                                | (Condensing temperature 55°C (+131°F)) |                            |                           |           |       |
| Evaporating<br>temperature    | Cooling capacity<br>+/- 5% |          |                    | Power<br>consumption<br>+/- 5% | Current<br>consumption<br>+/- 5%       | Gas flow<br>rate<br>+/- 5% | EFFICIENCY RATE<br>+/- 7% |           |       |
| °C (°F)                       | [Btu/h]                    | [kcal/h] | [W]                | [W]                            | [A]                                    | [kg/h]                     | [Btu/Wh]                  | [kcal/Wh] | [W/W] |
| -35 (-31)                     | 270                        | 68       | 79                 | 75                             | 0.74                                   | 1.52                       | 3.63                      | 0.91      | 1.06  |
| -30 (-22)                     | 416                        | 105      | 122                | 92                             | 0.86                                   | 2.36                       | 4.55                      | 1.15      | 1.33  |
| -25 (-13)                     | 581                        | 146      | 170                | 108                            | 0.99                                   | 3.30                       | 5.41                      | 1.36      | 1.58  |
| -20 (- 4)                     | 775                        | 195      | 227                | 125                            | 1.13                                   | 4.41                       | 6.23                      | 1.57      | 1.83  |
| -15 (+ 5)                     | 1010                       | 255      | 296                | 143                            | 1.29                                   | 5.77                       | 7.07                      | 1.78      | 2.07  |
| -10 (+14)                     | 1296                       | 327      | 380                | 162                            | 1.46                                   | 7.43                       | 7.96                      | 2.01      | 2.33  |

|                               |                            |          |                    |                                |  |                            |                           |           |       |
|-------------------------------|----------------------------|----------|--------------------|--------------------------------|--|----------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS:<br>@115V60Hz |                            |          | ASHRAE32<br>Static |                                | (Condensing temperature 65°C (+149°F)) |                            |                           |           |       |
| Evaporating<br>temperature    | Cooling capacity<br>+/- 5% |          |                    | Power<br>consumption<br>+/- 5% | Current<br>consumption<br>+/- 5%       | Gas flow<br>rate<br>+/- 5% | EFFICIENCY RATE<br>+/- 7% |           |       |
| °C (°F)                       | [Btu/h]                    | [kcal/h] | [W]                | [W]                            | [A]                                    | [kg/h]                     | [Btu/Wh]                  | [kcal/Wh] | [W/W] |
| -35 (-31)                     | 190                        | 48       | 56                 | 66                             | 0.67                                   | 1.07                       | 2.82                      | 0.71      | 0.83  |
| -30 (-22)                     | 338                        | 85       | 99                 | 87                             | 0.81                                   | 1.92                       | 3.80                      | 0.96      | 1.11  |
| -25 (-13)                     | 501                        | 126      | 147                | 107                            | 0.96                                   | 2.84                       | 4.66                      | 1.17      | 1.37  |
| -20 (- 4)                     | 689                        | 174      | 202                | 127                            | 1.13                                   | 3.92                       | 5.43                      | 1.37      | 1.59  |
| -15 (+ 5)                     | 913                        | 230      | 268                | 149                            | 1.32                                   | 5.21                       | 6.16                      | 1.55      | 1.81  |
| -10 (+14)                     | 1184                       | 298      | 347                | 172                            | 1.52                                   | 6.78                       | 6.89                      | 1.74      | 2.02  |

### F - EXTERNAL CHARACTERISTICS

|                         |                               |      |                          |
|-------------------------|-------------------------------|------|--------------------------|
| 1 Base plate            | Universal EG/F/AMEM version 2 |      |                          |
| 2 Tray holder           | No                            |      |                          |
| 3 Connectors            |                               |      |                          |
| 3.1 SUCTION             | 6.5 +0.12/-0.08               | [mm] | (0.256" +0.005"/-0.003") |
| 3.1.1 Material          | Copper                        |      |                          |
| 3.1.2 Shape             | Straight                      |      |                          |
| 3.2 DISCHARGE           | 6.5 +0.12/-0.08               | [mm] | (0.256" +0.005"/-0.003") |
| 3.2.1 Material          | Copper                        |      |                          |
| 3.2.2 Shape             | Straight                      |      |                          |
| 3.3 PROCESS             | 6.5 +0.12/-0.08               | [mm] | (0.256" +0.005"/-0.003") |
| 3.3.1 Material          | Copper                        |      |                          |
| 3.3.2 Shape             | Straight                      |      |                          |
| 3.4 Oil cooler (Copper) | No                            | [mm] |                          |
| 3.5 Connector sealing   | Rubber Plugs                  |      |                          |