

COMPRESSOR DEFINITION

Designation	EG Y80HLP
Nominal Voltage/Frequency	115-127 V 60 Hz
Engineering Number	513700212

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	115-127 / 60	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	85 to 110 V	98 to 140 V
8.2 LBP (43°C Ambient temperature)	Static	85 to 110 V	98 to 140 V
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	16.2	[kgf/cm ²] (230 psig)	/ °C - °F
9.2 Peak (gauge)	20.6	[kgf/cm ²] (293 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/4	[hp]
2 Displacement	6.76	[cm ³] (0.413 cu.in)
2.1 Bore [mm]	22.500	
2.2 Stroke [mm]	17.000	
3 Lubricant charge	280	[ml] (9.47 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO7	
4 Weight (with oil charge)	11.37	[kg] (25.07 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	115-127 V 60 Hz 1 ~ (Single phase)	
2 Starting device type	TSD	
2.1 Starting device	TSD- 115V	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	15(180)	[µF(VAC minimum)]
5 Motor protection	4TM445KFBYY-53	
6 Start winding resistance	5.60	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	3.50	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	13.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	1.70	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	UL	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @115V60Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)		
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
815	205	239	140	1.27	4.63	5.83	1.47	1.71	

E - PERFORMANCE - CURVES

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 45°C (+113°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	436	110	128	95	0.87	2.46	4.61	1.16	1.35
-30 (-22)	609	154	179	113	1.05	3.45	5.39	1.36	1.58
-25 (-13)	823	207	241	132	1.22	4.67	6.24	1.57	1.83
-20 (- 4)	1082	273	317	151	1.38	6.16	7.15	1.80	2.10
-15 (+ 5)	1394	351	409	171	1.55	7.96	8.14	2.05	2.39
-10 (+14)	1766	445	518	192	1.72	10.12	9.21	2.32	2.70

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 55°C (+131°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	400	101	117	94	0.87	2.27	4.27	1.08	1.25
-30 (-22)	556	140	163	113	1.06	3.15	4.93	1.24	1.44
-25 (-13)	751	189	220	134	1.24	4.26	5.62	1.42	1.65
-20 (- 4)	993	250	291	157	1.43	5.65	6.34	1.60	1.86
-15 (+ 5)	1287	324	377	181	1.63	7.35	7.11	1.79	2.08
-10 (+14)	1642	414	481	207	1.86	9.41	7.93	2.00	2.32

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 65°C (+149°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	334	84	98	91	0.85	1.89	3.66	0.92	1.07
-30 (-22)	478	120	140	111	1.04	2.71	4.31	1.09	1.26
-25 (-13)	661	167	194	134	1.23	3.75	4.95	1.25	1.45
-20 (- 4)	891	225	261	159	1.44	5.07	5.60	1.41	1.64
-15 (+ 5)	1175	296	344	188	1.68	6.70	6.27	1.58	1.84
-10 (+14)	1518	383	445	218	1.95	8.70	6.95	1.75	2.04

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal EG/F/AMEM version 2		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.2 +0.12/-0.08	[mm]	(0.323" +0.005"/-0.003")
3.1.1 Material	Copper		
3.1.2 Shape	Straight		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.3.1 Material	Copper		
3.3.2 Shape	Straight		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		