

### COMPRESSOR DEFINITION

Designation	EG X80HLC
Nominal Voltage/Frequency	115-127 V 60 Hz
Engineering Number	513703015

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	115-127 / 60	[ V / Hz ]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	-	98 to 140 V
8.2 LBP (43°C Ambient temperature)	Static	-	98 to 140 V
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	14.2	[kgf/cm <sup>2</sup> ] (202 psig)	/ °C - °F
9.2 Peak	15.9	[kgf/cm <sup>2</sup> ] (226 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation	1/4	[hp]
2 Displacement	6.36	[cm <sup>3</sup> ] (0.388 cu.in)
2.1 Bore [mm]	22.500	
2.2 Stroke [mm]	16.000	
3 Lubricant charge	280	[ml] (9.47 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO10	
4 Weight (with oil charge)	11.01	[kg] (24.27 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm <sup>2</sup> ] (2.84 to 4.27 psig)

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	115-127 V 60 Hz 1 ~ (Single phase)	
2 Starting device type	TSD	
2.1 Starting device	TSD- 115V/TSD2-115V	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	15(180)	[µF(VAC minimum)]
5 Motor protection	4TM445KFBYY-53	
6 Start winding resistance	5.60	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	3.50	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	13.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	1.70	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	CE - NOM - UKCA - UL	

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @115V60Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
820	207	240	131	1.18	4.66	6.24	1.57	1.83

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 45°C (+113°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	401	101	117	87	0.78	2.27	4.63	1.17	1.36
-30 (-22)	602	152	176	106	0.95	3.41	5.65	1.42	1.66
-25 (-13)	823	207	241	125	1.11	4.67	6.59	1.66	1.93
-20 (- 4)	1074	271	315	144	1.27	6.11	7.51	1.89	2.20
-15 (+ 5)	1366	344	400	162	1.43	7.80	8.48	2.14	2.48
-10 (+14)	1710	431	501	179	1.58	9.80	9.57	2.41	2.80

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 55°C (+131°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	324	82	95	77	0.70	1.83	4.18	1.05	1.23
-30 (-22)	517	130	151	100	0.90	2.93	5.11	1.29	1.50
-25 (-13)	734	185	215	123	1.11	4.17	5.93	1.49	1.74
-20 (- 4)	988	249	289	147	1.32	5.62	6.70	1.69	1.96
-15 (+ 5)	1287	324	377	171	1.53	7.35	7.50	1.89	2.20
-10 (+14)	1644	414	482	196	1.75	9.42	8.39	2.11	2.46

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 65°C (+149°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	248	63	73	71	0.65	1.41	3.52	0.89	1.03
-30 (-22)	426	107	125	95	0.86	2.41	4.44	1.12	1.30
-25 (-13)	633	159	185	121	1.09	3.59	5.23	1.32	1.53
-20 (- 4)	881	222	258	149	1.32	5.01	5.94	1.50	1.74
-15 (+ 5)	1181	298	346	177	1.57	6.74	6.65	1.68	1.95
-10 (+14)	1542	389	452	207	1.83	8.84	7.43	1.87	2.18

### F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.1.1 Material	Copper		
3.1.2 Shape	Straight		
3.2 DISCHARGE	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.3.1 Material	Copper		
3.3.2 Shape	Straight		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		