

### COMPRESSOR DEFINITION

Designation	EM U45HSC
Nominal Voltage/Frequency	115-127 V 60 Hz
Engineering Number	513308010

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	115-127 / 60	[ V / Hz ]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	85 to 110 V	98 to 140 V
8.2 LBP (43°C Ambient temperature)	Static	85 to 110 V	98 to 140 V
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	14.2	[kgf/cm <sup>2</sup> ] (202 psig)	/ °C - °F
9.2 Peak	15.9	[kgf/cm <sup>2</sup> ] (226 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation	1/6	[hp]
2 Displacement	3.77	[cm <sup>3</sup> ] (0.230 cu.in)
2.1 Bore [mm]	19.000	
2.2 Stroke [mm]	13.300	
3 Lubricant charge	160	[ml] (5.41 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO10	
4 Weight (with oil charge)	7.76	[kg] (17.11 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm <sup>2</sup> ] (2.84 to 4.27 psig)

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	115-127 V 60 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	QPS2-A4R7MD3 094	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	15(160)	[µF(VAC minimum)]
5 Motor protection	4TM283NFBYY-53	
6 Start winding resistance	5.60	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	6.70	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	-	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	CE - NOM - UKCA - UL	

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @115V60Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
450	113	132	91	0.81	2.56	4.96	1.25	1.45

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 45°C (+113°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	243	61	71	66	0.57	1.38	3.70	0.93	1.08
-30 (-22)	338	85	99	75	0.66	1.92	4.50	1.13	1.32
-25 (-13)	452	114	133	86	0.75	2.57	5.28	1.33	1.55
-20 (- 4)	590	149	173	97	0.85	3.36	6.08	1.53	1.78
-15 (+ 5)	754	190	221	109	0.94	4.30	6.93	1.75	2.03
-10 (+14)	946	238	277	120	1.04	5.42	7.88	1.98	2.31

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 55°C (+131°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	197	50	58	64	0.57	1.11	3.06	0.77	0.90
-30 (-22)	294	74	86	75	0.67	1.67	3.90	0.98	1.14
-25 (-13)	409	103	120	88	0.77	2.32	4.67	1.18	1.37
-20 (- 4)	546	137	160	101	0.88	3.10	5.41	1.36	1.58
-15 (+ 5)	705	178	207	115	0.99	4.03	6.15	1.55	1.80
-10 (+14)	892	225	261	129	1.11	5.11	6.93	1.75	2.03

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 65°C (+149°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	147	37	43	59	0.53	0.83	2.50	0.63	0.73
-30 (-22)	246	62	72	72	0.64	1.40	3.37	0.85	0.99
-25 (-13)	361	91	106	87	0.76	2.05	4.13	1.04	1.21
-20 (- 4)	495	125	145	103	0.90	2.81	4.81	1.21	1.41
-15 (+ 5)	650	164	190	120	1.04	3.71	5.44	1.37	1.59
-10 (+14)	830	209	243	137	1.19	4.75	6.07	1.53	1.78

### F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal EG/F/AMEM version 2		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.1.1 Material	Copper		
3.1.2 Shape	Straight		
3.2 DISCHARGE	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted		
3.3 PROCESS	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.3.1 Material	Copper		
3.3.2 Shape	Straight		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		