

COMPRESSOR DEFINITION

Designation	NT 6217Z
Nominal Voltage/Frequency	208-230 V 60 Hz
Engineering Number	212BD06

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	208-230 / 60	[V / Hz]	
4 Application type	High Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-15°C to 10°C	(5°F to 50°F)	
5 Motor type	CSCR		
6 Starting torque	HST - Hight starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	14.2	[kgf/cm ²] (202 psig)	/ °C - °F
9.2 Peak	15.9	[kgf/cm ²] (226 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	3/4	[hp]
2 Displacement	20.44	[cm ³] (1.247 cu.in)
2.1 Bore [mm]	36.990	
2.2 Stroke [mm]	19.030	
3 Lubricant charge	450	[ml] (15.22 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	16.7	[kg] (36.82 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	208-230 V 60 Hz 1~ (Single phase)	
2 Starting device type	Voltage Relay	
2.1 Starting device	RVA2AI3C-124	
3 Start capacitor	64-77(330)	[μF(VAC minimum)]
4 Run capacitor	15(400)	[μF(VAC minimum)]
5 Motor protection	T0905/G9	
6 Start winding resistance	6.03	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	1.84	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	31.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	UL	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @230V60Hz			ARIHBP Fan		Evaporating temperature (Condensing temperature		7.2°C (44.96°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
6839	1723	2004	905	3.98	53.67	7.56	1.91	2.22

E - PERFORMANCE - CURVES

TEST CONDITIONS: @230V60Hz		ARI18 Fan			(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+5)	3537	891	1036	534	2.45	22.12	6.62	1.67	1.94
-10	(+14)	4475	1128	1311	586	2.66	28.14	7.64	1.93	2.24
-5	(+23)	5585	1407	1637	637	2.87	35.30	8.77	2.21	2.57
0	(+32)	6872	1732	2014	689	3.08	43.70	9.97	2.51	2.92
+5	(+41)	8339	2101	2443	741	3.30	53.45	11.25	2.84	3.30
+10	(+50)	9990	2517	2927	794	3.52	64.64	12.58	3.17	3.69

TEST CONDITIONS: @230V60Hz		ARI18 Fan			(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+5)	2956	745	866	563	2.57	20.28	5.25	1.32	1.54
-10	(+14)	3800	958	1114	626	2.82	26.23	6.07	1.53	1.78
-5	(+23)	4795	1208	1405	688	3.08	33.28	6.97	1.76	2.04
0	(+32)	5945	1498	1742	748	3.33	41.55	7.94	2.00	2.33
+5	(+41)	7253	1828	2125	809	3.58	51.13	8.97	2.26	2.63
+10	(+50)	8723	2198	2556	869	3.84	62.12	10.04	2.53	2.94

TEST CONDITIONS: @230V60Hz		ARI18 Fan			(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+5)	2475	624	725	588	2.66	18.89	4.21	1.06	1.23
-10	(+14)	3217	811	943	664	2.97	24.70	4.84	1.22	1.42
-5	(+23)	4088	1030	1198	737	3.27	31.60	5.54	1.40	1.62
0	(+32)	5091	1283	1492	808	3.57	39.67	6.30	1.59	1.85
+5	(+41)	6231	1570	1826	879	3.87	49.02	7.10	1.79	2.08
+10	(+50)	7512	1893	2201	948	4.17	59.76	7.92	2.00	2.32

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	9.6 +0.07/+0.00	[mm]	(0.378" +0.003"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	6.42 +0.08/+0.00	[mm]	(0.253" +0.003"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.42 +0.08/+0.00	[mm]	(0.253" +0.003"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Vertical		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		