

COMPRESSOR DEFINITION

Designation	EG U70HLC
Nominal Voltage/Frequency	100 V 50-60 Hz
Engineering Number	513700033

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	100 / 50-60	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	85 to 110 V	85 to 110 V
8.2 LBP (43°C Ambient temperature)	Static	85 to 110 V	85 to 110 V
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	16.2	[kgf/cm ²] (230 psig)	/ °C - °F
9.2 Peak (gauge)	20.6	[kgf/cm ²] (293 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/4	[hp]
2 Displacement	6.36	[cm ³] (0.388 cu.in)
2.1 Bore [mm]	22.500	
2.2 Stroke [mm]	16.000	
3 Lubricant charge	350	[ml] (11.84 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	11.23	[kg] (24.76 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	100 V 50-60 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	490B814R7/7M4R7MB3/8M4R7MB3	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	20(180)	[µF(VAC minimum)]
5 Motor protection	4TM427NFBYY-53	
6 Start winding resistance	3.50	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	3.80	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50/60 Hz)	-	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50/60 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50/60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification		

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @100V50Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
600	151	176	109	1.16	3.41	5.50	1.39	1.61

TEST CONDITIONS: @100V60Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
700	176	205	127	1.32	3.98	5.52	1.39	1.62

E - PERFORMANCE - CURVES

TEST CONDITIONS: @100V50Hz			ASHRAE32 Static		(Condensing temperature 45°C (+113°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	307	77	90	74	0.86	1.74	4.13	1.04	1.21
-30 (-22)	448	113	131	87	0.98	2.54	5.15	1.30	1.51
-25 (-13)	615	155	180	100	1.10	3.49	6.12	1.54	1.79
-20 (- 4)	814	205	239	115	1.24	4.63	7.05	1.78	2.07
-15 (+ 5)	1050	265	308	131	1.39	5.99	7.98	2.01	2.34
-10 (+14)	1327	334	389	149	1.54	7.60	8.92	2.25	2.61

TEST CONDITIONS: @100V50Hz			ASHRAE32 Static		(Condensing temperature 55°C (+131°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	239	60	70	72	0.82	1.35	3.36	0.85	0.98
-30 (-22)	375	94	110	87	0.97	2.12	4.34	1.09	1.27
-25 (-13)	537	135	157	103	1.12	3.05	5.24	1.32	1.54
-20 (- 4)	732	184	214	120	1.29	4.16	6.11	1.54	1.79
-15 (+ 5)	963	243	282	139	1.48	5.50	6.95	1.75	2.04
-10 (+14)	1237	312	362	158	1.68	7.08	7.79	1.96	2.28

E - PERFORMANCE - CURVES

TEST CONDITIONS: @100V50Hz		ASHRAE32 Static			(Condensing temperature 65°C (+149°F))					
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
	°C	(°F)	[Btu/h]				[kcal/h]	[W]	[W]	[A]
-35	(-31)	170	43	50	64	0.76	0.96	2.65	0.67	0.78
-30	(-22)	301	76	88	82	0.93	1.70	3.60	0.91	1.05
-25	(-13)	459	116	134	103	1.11	2.60	4.46	1.12	1.31
-20	(- 4)	649	164	190	124	1.32	3.69	5.25	1.32	1.54
-15	(+ 5)	877	221	257	146	1.54	5.01	6.02	1.52	1.76
-10	(+14)	1147	289	336	170	1.77	6.57	6.77	1.71	1.98

TEST CONDITIONS: @100V60Hz		ASHRAE32 Static			(Condensing temperature 45°C (+113°F))					
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
	°C	(°F)	[Btu/h]				[kcal/h]	[W]	[W]	[A]
-35	(-31)	366	92	107	0.00	2.07	0.00	0.00	0.00	0.00
-30	(-22)	530	133	155	0.00	3.00	0.00	0.00	0.00	0.00
-25	(-13)	722	182	212	0.00	4.10	0.00	0.00	0.00	0.00
-20	(- 4)	954	240	280	0.00	5.43	0.00	0.00	0.00	0.00
-15	(+ 5)	1238	312	363	0.00	7.07	0.00	0.00	0.00	0.00
-10	(+14)	1585	399	464	0.00	9.08	0.00	0.00	0.00	0.00

TEST CONDITIONS: @100V60Hz		ASHRAE32 Static			(Condensing temperature 55°C (+131°F))					
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
	°C	(°F)	[Btu/h]				[kcal/h]	[W]	[W]	[A]
-35	(-31)	286	72	84	0.00	1.62	0.00	0.00	0.00	0.00
-30	(-22)	446	112	131	0.00	2.53	0.00	0.00	0.00	0.00
-25	(-13)	628	158	184	0.00	3.56	0.00	0.00	0.00	0.00
-20	(- 4)	844	213	247	0.00	4.80	0.00	0.00	0.00	0.00
-15	(+ 5)	1105	279	324	0.00	6.31	0.00	0.00	0.00	0.00
-10	(+14)	1424	359	417	0.00	8.16	0.00	0.00	0.00	0.00

TEST CONDITIONS: @100V60Hz		ASHRAE32 Static			(Condensing temperature 65°C (+149°F))					
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
	°C	(°F)	[Btu/h]				[kcal/h]	[W]	[W]	[A]
-35	(-31)	185	47	54	0.00	1.05	0.00	0.00	0.00	0.00
-30	(-22)	349	88	102	0.00	1.98	0.00	0.00	0.00	0.00
-25	(-13)	529	133	155	0.00	3.01	0.00	0.00	0.00	0.00
-20	(- 4)	738	186	216	0.00	4.20	0.00	0.00	0.00	0.00
-15	(+ 5)	987	249	289	0.00	5.63	0.00	0.00	0.00	0.00
-10	(+14)	1287	324	377	0.00	7.37	0.00	0.00	0.00	0.00

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal EG/F/AMEM version 2		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.1.1 Material	Copper		
3.1.2 Shape	Straight		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.3.1 Material	Copper		
3.3.2 Shape	Straight		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		