

COMPRESSOR DEFINITION

Designation	EG Y60HLP
Nominal Voltage/Frequency	115-127 V 60 Hz
Engineering Number	513700235

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	115-127 / 60	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	-	98 to 140 V
8.2 LBP (43°C Ambient temperature)	Static	-	98 to 140 V
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	16.2	[kgf/cm ²] (230 psig)	/ °C - °F
9.2 Peak (gauge)	20.6	[kgf/cm ²] (293 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/5	[hp]
2 Displacement	5.56	[cm ³] (0.339 cu.in)
2.1 Bore [mm]	22.500	
2.2 Stroke [mm]	14.000	
3 Lubricant charge	280	[ml] (9.47 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO7	
4 Weight (with oil charge)	10.75	[kg] (23.70 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	115-127 V 60 Hz 1 ~ (Single phase)	
2 Starting device type	TSD	
2.1 Starting device	TSD- 115V	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	20(180)	[µF(VAC minimum)]
5 Motor protection	4TM319NFBYY-53	
6 Start winding resistance	5.70	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	5.10	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	9.30	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	1.50	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	UL	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @115V60Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
620	156	182	112	1.18	3.52	5.54	1.40	1.62

E - PERFORMANCE - CURVES

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 45°C (+113°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	325	82	95	80	0.97	1.84	4.04	1.02	1.19
-30 (-22)	470	118	138	94	1.03	2.67	5.01	1.26	1.47
-25 (-13)	639	161	187	107	1.11	3.63	5.98	1.51	1.75
-20 (- 4)	841	212	247	121	1.20	4.79	6.97	1.76	2.04
-15 (+ 5)	1089	274	319	135	1.31	6.22	8.04	2.03	2.36
-10 (+14)	1392	351	408	150	1.42	7.97	9.23	2.33	2.70

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 55°C (+131°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	270	68	79	78	0.98	1.52	3.52	0.89	1.03
-30 (-22)	416	105	122	93	1.05	2.36	4.48	1.13	1.31
-25 (-13)	581	146	170	109	1.14	3.30	5.38	1.36	1.58
-20 (- 4)	775	195	227	125	1.25	4.41	6.26	1.58	1.83
-15 (+ 5)	1010	255	296	141	1.38	5.77	7.15	1.80	2.10
-10 (+14)	1296	327	380	159	1.52	7.43	8.11	2.04	2.38

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 65°C (+149°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	190	48	56	69	0.94	1.07	2.71	0.68	0.79
-30 (-22)	338	85	99	88	1.02	1.92	3.73	0.94	1.09
-25 (-13)	501	126	147	107	1.12	2.84	4.63	1.17	1.36
-20 (- 4)	689	174	202	127	1.25	3.92	5.46	1.38	1.60
-15 (+ 5)	913	230	268	147	1.40	5.21	6.25	1.57	1.83
-10 (+14)	1184	298	347	169	1.56	6.78	7.04	1.77	2.06

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal EG/F/AMEM version 2		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted		
3.3 PROCESS	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		