

COMPRESSOR DEFINITION

| | |
|---------------------------|-----------------|
| Designation | EG Y80HLP |
| Nominal Voltage/Frequency | 115-127 V 60 Hz |
| Engineering Number | 513700198 |

A - APPLICATION / LIMIT WORKING CONDITIONS

| | | | |
|--|-----------------------------------|-----------------------------------|-------------|
| 1 Type | Hermetic reciprocating compressor | | |
| 2 Refrigerant | R-134a | | |
| 3 Nominal voltage and frequency | 115-127 / 60 | [V / Hz] | |
| 4 Application type | Low Back Pressure | | |
| 4.1 Evaporating temperature range | -35°C to -10°C | (-31°F to 14°F) | |
| 5 Motor type | RSCR | | |
| 6 Starting torque | LST - Low Starting Torque | | |
| 7 Expansion device | Capillary tube | | |
| 8 Compressor cooling | | Operating voltage range | |
| | | 50 Hz | 60 Hz |
| 8.1 LBP (32°C Ambient temperature) | Static | 85 to 110 V | 98 to 140 V |
| 8.2 LBP (43°C Ambient temperature) | Static | 85 to 110 V | 98 to 140 V |
| 8.3 HBP (32°C Ambient temperature) | - | - | - |
| 8.4 HBP (43°C Ambient temperature) | - | - | - |
| 9 Maximum condensing pressures/temperature | | | |
| 9.1 Operating (gauge) | 16.2 | [kgf/cm ²] (230 psig) | / °C - °F |
| 9.2 Peak (gauge) | 20.6 | [kgf/cm ²] (293 psig) | / °C - °F |
| 10 Maximum winding temperature | 130 | [°C] | |

B - MECHANICAL DATA

| | | |
|-------------------------------|--------------|--|
| 1 Commercial designation | 1/4 | [hp] |
| 2 Displacement | 6.76 | [cm ³] (0.413 cu.in) |
| 2.1 Bore [mm] | 22.500 | |
| 2.2 Stroke [mm] | 17.000 | |
| 3 Lubricant charge | 280 | [ml] (9.47 fl.oz.) |
| 3.1 Lubricants approved | | |
| 3.2 Lubricants type/viscosity | ESTER / ISO7 | |
| 4 Weight (with oil charge) | 11.37 | [kg] (25.07 lb.) |
| 5 Nitrogen charge | 0.2 to 0.3 | [kgf/cm ²] (2.84 to 4.27 psig) |

C - ELETRICAL DATA

| | | |
|--|------------------------------------|------------------------------------|
| 1 Nominal Voltage/Frequency/Number of Phases | 115-127 V 60 Hz 1 ~ (Single phase) | |
| 2 Starting device type | TSD | |
| 2.1 Starting device | TSD- 115V | |
| 3 Start capacitor | - | [µF(VAC minimum)] |
| 4 Run capacitor | 20(180) | [µF(VAC minimum)] |
| 5 Motor protection | 4TM445KFBYY-53 | |
| 6 Start winding resistance | 5.60 | [Ω at 25°C (77°F)] +/- 8% |
| 7 Run winding resistance | 3.50 | [Ω at 25°C (77°F)] +/- 8% |
| 8 LRA - Locked rotor amperage (60 Hz) | 13.00 | [A] - Measured according to UL 984 |
| 9 FLA - Full load amperage L/MBP (60 Hz) | 1.70 | [A] - Measured according to UL 984 |
| 10 FLA - Full Load Amperage HBP (60 Hz) | - | [A] - Measured according to UL 984 |
| 11 Approval boards certification | UL | |

D - PERFORMANCE - CHECK POINT DATA

| | | | | | | | | | |
|-------------------------------|----------|-----|--------------------------------|----------------------------------|--|---------------------------|--|-------|--|
| TEST CONDITIONS: @115V60Hz | | | ASHRAELBP32 Static | | Evaporating temperature (Condensing temperature | | -23.3°C (-9.94°F) 54.4°C (129.92°F) | | |
| Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | | |
| [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] | |
| 815 | 205 | 239 | 143 | 1.34 | 4.63 | 5.70 | 1.44 | 1.67 | |

E - PERFORMANCE - CURVES

| | | | | | | | | | | |
|-------------------------------|----------------------------|----------|--------------------|--------------------------------|--|----------------------------|---------------------------|-----------|-------|--|
| TEST CONDITIONS: @115V60Hz | | | ASHRAE32 Static | | (Condensing temperature 45°C (+113°F)) | | | | | |
| Evaporating temperature | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | | |
| °C (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] | |
| -35 (-31) | 436 | 110 | 128 | 98 | 1.01 | 2.46 | 4.44 | 1.12 | 1.30 | |
| -30 (-22) | 609 | 154 | 179 | 116 | 1.15 | 3.45 | 5.24 | 1.32 | 1.54 | |
| -25 (-13) | 823 | 207 | 241 | 134 | 1.29 | 4.67 | 6.12 | 1.54 | 1.79 | |
| -20 (- 4) | 1082 | 273 | 317 | 153 | 1.43 | 6.16 | 7.07 | 1.78 | 2.07 | |
| -15 (+ 5) | 1394 | 351 | 409 | 172 | 1.57 | 7.96 | 8.10 | 2.04 | 2.37 | |
| -10 (+14) | 1766 | 445 | 518 | 192 | 1.73 | 10.12 | 9.21 | 2.32 | 2.70 | |

| | | | | | | | | | | |
|-------------------------------|----------------------------|----------|--------------------|--------------------------------|--|----------------------------|---------------------------|-----------|-------|--|
| TEST CONDITIONS: @115V60Hz | | | ASHRAE32 Static | | (Condensing temperature 55°C (+131°F)) | | | | | |
| Evaporating temperature | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | | |
| °C (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] | |
| -35 (-31) | 400 | 101 | 117 | 98 | 1.02 | 2.27 | 4.11 | 1.04 | 1.20 | |
| -30 (-22) | 556 | 140 | 163 | 116 | 1.16 | 3.15 | 4.79 | 1.21 | 1.40 | |
| -25 (-13) | 751 | 189 | 220 | 136 | 1.31 | 4.26 | 5.51 | 1.39 | 1.62 | |
| -20 (- 4) | 993 | 250 | 291 | 158 | 1.47 | 5.65 | 6.28 | 1.58 | 1.84 | |
| -15 (+ 5) | 1287 | 324 | 377 | 181 | 1.64 | 7.35 | 7.09 | 1.79 | 2.08 | |
| -10 (+14) | 1642 | 414 | 481 | 206 | 1.85 | 9.41 | 7.96 | 2.01 | 2.33 | |

| | | | | | | | | | | |
|-------------------------------|----------------------------|----------|--------------------|--------------------------------|--|----------------------------|---------------------------|-----------|-------|--|
| TEST CONDITIONS: @115V60Hz | | | ASHRAE32 Static | | (Condensing temperature 65°C (+149°F)) | | | | | |
| Evaporating temperature | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | | |
| °C (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] | |
| -35 (-31) | 334 | 84 | 98 | 95 | 0.99 | 1.89 | 3.51 | 0.88 | 1.03 | |
| -30 (-22) | 478 | 120 | 140 | 114 | 1.13 | 2.71 | 4.18 | 1.05 | 1.23 | |
| -25 (-13) | 661 | 167 | 194 | 136 | 1.29 | 3.75 | 4.86 | 1.23 | 1.43 | |
| -20 (- 4) | 891 | 225 | 261 | 161 | 1.47 | 5.07 | 5.55 | 1.40 | 1.63 | |
| -15 (+ 5) | 1175 | 296 | 344 | 188 | 1.69 | 6.70 | 6.26 | 1.58 | 1.83 | |
| -10 (+14) | 1518 | 383 | 445 | 217 | 1.94 | 8.70 | 6.99 | 1.76 | 2.05 | |

F - EXTERNAL CHARACTERISTICS

| | | | |
|-------------------------|-------------------------------|------|--------------------------|
| 1 Base plate | Universal EG/F/AMEM version 2 | | |
| 2 Tray holder | No | | |
| 3 Connectors | | | |
| 3.1 SUCTION | 6.5 +0.12/-0.08 | [mm] | (0.256" +0.005"/-0.003") |
| 3.1.1 Material | Copper | | |
| 3.1.2 Shape | Straight | | |
| 3.2 DISCHARGE | 6.5 +0.12/-0.08 | [mm] | (0.256" +0.005"/-0.003") |
| 3.2.1 Material | Copper | | |
| 3.2.2 Shape | Straight | | |
| 3.3 PROCESS | 6.5 +0.12/-0.08 | [mm] | (0.256" +0.005"/-0.003") |
| 3.3.1 Material | Copper | | |
| 3.3.2 Shape | Straight | | |
| 3.4 Oil cooler (Copper) | No | [mm] | |
| 3.5 Connector sealing | Rubber Plugs | | |