

COMPRESSOR DEFINITION

| | |
|---------------------------|------------------------|
| Designation | F GS70HA |
| Nominal Voltage/Frequency | 115-127 V 60 Hz |
| Engineering Number | 513200496 |

A - APPLICATION / LIMIT WORKING CONDITIONS

| | | | |
|--|-----------------------------------|-----------------------------------|--------------|
| 1 Type | Hermetic reciprocating compressor | | |
| 2 Refrigerant | R-134a | | |
| 3 Nominal voltage and frequency | 115-127 / 60 | [V / Hz] | |
| 4 Application type | Low Back Pressure | | |
| 4.1 Evaporating temperature range | -35°C to -10°C | (-31°F to 14°F) | |
| 5 Motor type | RSCR | | |
| 6 Starting torque | LST - Low Starting Torque | | |
| 7 Expansion device | Capillary tube | | |
| 8 Compressor cooling | Operating voltage range | | |
| | | 50 Hz | 60 Hz |
| 8.1 LBP (32°C Ambient temperature) | Static | - | 103 to 140 V |
| 8.2 LBP (43°C Ambient temperature) | Static | - | 103 to 140 V |
| 8.3 HBP (32°C Ambient temperature) | - | - | - |
| 8.4 HBP (43°C Ambient temperature) | - | - | - |
| 9 Maximum condensing pressures/temperature | | | |
| 9.1 Operating (gauge) | 16.2 | [kgf/cm ²] (230 psig) | / °C - °F |
| 9.2 Peak (gauge) | 20.6 | [kgf/cm ²] (293 psig) | / °C - °F |
| 10 Maximum winding temperature | 130 | [°C] | |

B - MECHANICAL DATA

| | | |
|-------------------------------|---------------|--|
| 1 Commercial designation | 1/5+ | [hp] |
| 2 Displacement | 6.36 | [cm ³] (0.388 cu.in) |
| 2.1 Bore [mm] | 22.500 | |
| 2.2 Stroke [mm] | 16.000 | |
| 3 Lubricant charge | 350 | [ml] (11.84 fl.oz.) |
| 3.1 Lubricants approved | | |
| 3.2 Lubricants type/viscosity | ESTER / ISO22 | |
| 4 Weight (with oil charge) | 11.49 | [kg] (25.33 lb.) |
| 5 Nitrogen charge | 0.2 to 0.3 | [kgf/cm ²] (2.84 to 4.27 psig) |

C - ELETRICAL DATA

| | | |
|--|------------------------------------|------------------------------------|
| 1 Nominal Voltage/Frequency/Number of Phases | 115-127 V 60 Hz 1 ~ (Single phase) | |
| 2 Starting device type | Combo | |
| 2.1 Starting device | 5SP14X427N | |
| 3 Start capacitor | - | [µF(VAC minimum)] |
| 4 Run capacitor | 20(180) | [µF(VAC minimum)] |
| 5 Motor protection | 5SP14X427NFX | |
| 6 Start winding resistance | 2.68 | [Ω at 25°C (77°F)] +/- 8% |
| 7 Run winding resistance | 3.69 | [Ω at 25°C (77°F)] +/- 8% |
| 8 LRA - Locked rotor amperage (60 Hz) | 12.00 | [A] - Measured according to UL 984 |
| 9 FLA - Full load amperage L/MBP (60 Hz) | 1.91 | [A] - Measured according to UL 984 |
| 10 FLA - Full Load Amperage HBP (60 Hz) | - | [A] - Measured according to UL 984 |
| 11 Approval boards certification | UL | |

D - PERFORMANCE - CHECK POINT DATA

| | | | | | | | | |
|-------------------------------|----------|-----|--------------------------------|----------------------------------|--|---------------------------|--|-------|
| TEST CONDITIONS: @115V60Hz | | | ASHRAELBP32 Static | | Evaporating temperature (Condensing temperature | | -23.3°C (-9.94°F) 54.4°C (129.92°F) | |
| Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| 710 | 179 | 208 | 140 | 1.24 | 4.03 | 5.07 | 1.28 | 1.49 |

E - PERFORMANCE - CURVES

| | | | | | | | | | |
|-------------------------------|----------------------------|----------|--------------------|--------------------------------|--|----------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS: @115V60Hz | | | ASHRAE32 Static | | (Condensing temperature 45°C (+113°F)) | | | | |
| Evaporating temperature | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 (-31) | 348 | 88 | 102 | 100 | 0.91 | 1.97 | 3.49 | 0.88 | 1.02 |
| -30 (-22) | 527 | 133 | 154 | 117 | 1.03 | 2.99 | 4.49 | 1.13 | 1.32 |
| -25 (-13) | 732 | 184 | 214 | 135 | 1.18 | 4.16 | 5.39 | 1.36 | 1.58 |
| -20 (- 4) | 971 | 245 | 284 | 155 | 1.35 | 5.52 | 6.27 | 1.58 | 1.84 |
| -15 (+ 5) | 1250 | 315 | 366 | 174 | 1.52 | 7.13 | 7.19 | 1.81 | 2.11 |
| -10 (+14) | 1576 | 397 | 462 | 192 | 1.71 | 9.03 | 8.20 | 2.07 | 2.40 |

| | | | | | | | | | |
|-------------------------------|----------------------------|----------|--------------------|--------------------------------|--|----------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS: @115V60Hz | | | ASHRAE32 Static | | (Condensing temperature 55°C (+131°F)) | | | | |
| Evaporating temperature | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 (-31) | 273 | 69 | 80 | 95 | 0.88 | 1.54 | 2.87 | 0.72 | 0.84 |
| -30 (-22) | 439 | 111 | 129 | 114 | 1.01 | 2.49 | 3.87 | 0.98 | 1.13 |
| -25 (-13) | 635 | 160 | 186 | 135 | 1.17 | 3.60 | 4.72 | 1.19 | 1.38 |
| -20 (- 4) | 866 | 218 | 254 | 158 | 1.36 | 4.93 | 5.49 | 1.38 | 1.61 |
| -15 (+ 5) | 1139 | 287 | 334 | 182 | 1.57 | 6.50 | 6.23 | 1.57 | 1.83 |
| -10 (+14) | 1463 | 369 | 429 | 208 | 1.80 | 8.38 | 7.02 | 1.77 | 2.06 |

| | | | | | | | | | |
|-------------------------------|----------------------------|----------|--------------------|--------------------------------|--|----------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS: @115V60Hz | | | ASHRAE32 Static | | (Condensing temperature 65°C (+149°F)) | | | | |
| Evaporating temperature | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 (-31) | 187 | 47 | 55 | 91 | 0.84 | 1.06 | 2.03 | 0.51 | 0.59 |
| -30 (-22) | 345 | 87 | 101 | 108 | 0.97 | 1.96 | 3.18 | 0.80 | 0.93 |
| -25 (-13) | 535 | 135 | 157 | 130 | 1.15 | 3.04 | 4.12 | 1.04 | 1.21 |
| -20 (- 4) | 764 | 192 | 224 | 156 | 1.36 | 4.34 | 4.91 | 1.24 | 1.44 |
| -15 (+ 5) | 1037 | 261 | 304 | 185 | 1.60 | 5.92 | 5.63 | 1.42 | 1.65 |
| -10 (+14) | 1363 | 344 | 399 | 215 | 1.87 | 7.81 | 6.32 | 1.59 | 1.85 |

F - EXTERNAL CHARACTERISTICS

| | | | |
|-------------------------|------------------|------|--------------------------|
| 1 Base plate | Universal EG/F | | |
| 2 Tray holder | No | | |
| 3 Connectors | | | |
| 3.1 SUCTION | 6.5 +0.12/-0.08 | [mm] | (0.256" +0.005"/-0.003") |
| 3.1.1 Material | Copper | | |
| 3.1.2 Shape | Straight | | |
| 3.2 DISCHARGE | 4.94 +0.08/-0.08 | [mm] | (0.194" +0.003"/-0.003") |
| 3.2.1 Material | Copper | | |
| 3.2.2 Shape | Straight | | |
| 3.3 PROCESS | 6.5 +0.12/-0.08 | [mm] | (0.256" +0.005"/-0.003") |
| 3.3.1 Material | Copper | | |
| 3.3.2 Shape | Straight | | |
| 3.4 Oil cooler (Copper) | No | [mm] | |
| 3.5 Connector sealing | Rubber Plugs | | |