

COMPRESSOR DEFINITION

Designation	NT U6232GKV
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	925AA60

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-404A		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Medium Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-20°C to 10°C	(-4°F to 50°F)	
5 Motor type	CSCR		
6 Starting torque	HST - High starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	25.2	[kgf/cm ²] (358 psig)	/ °C - °F
9.2 Peak	28.3	[kgf/cm ²] (402 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1+	[hp]
2 Displacement	20.44	[cm ³] (1.247 cu.in)
2.1 Bore [mm]	36.990	
2.2 Stroke [mm]	19.030	
3 Lubricant charge	650	[ml] (21.98 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	18.4	[kg] (40.56 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	Voltage Relay	
2.1 Starting device	3ARR3B10AS3	
3 Start capacitor	88-108(330)	[µF(VAC minimum)]
4 Run capacitor	25(400)	[µF(VAC minimum)]
5 Motor protection	15HM1963-247	
6 Start winding resistance	3.75	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	1.54	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	-	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			EN12900MBP Fan		Evaporating temperature (Condensing temperature		-10°C (14°F) 45°C (113°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
6005	1513	1760	894	4.69	52.86	6.72	1.69	1.97

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			EN12900 Fan		(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	4745	1196	1390	706	3.90	35.99	6.71	1.69	1.97
-15	(+ 5)	5848	1474	1714	753	4.08	44.87	7.75	1.95	2.27
-10	(+14)	7147	1801	2094	791	4.23	55.26	9.04	2.28	2.65
-5	(+23)	8690	2190	2546	820	4.35	67.80	10.61	2.67	3.11
0	(+32)	10526	2653	3084	841	4.43	83.14	12.55	3.16	3.68
+5	(+41)	12702	3201	3722	854	4.49	101.93	14.89	3.75	4.36
+10	(+50)	15266	3847	4473	860	4.51	124.82	17.71	4.46	5.19

TEST CONDITIONS: @220V50Hz			EN12900 Fan		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	3916	987	1148	759	4.11	33.78	5.20	1.31	1.52
-15	(+ 5)	4890	1232	1433	825	4.37	42.65	5.93	1.49	1.74
-10	(+14)	5986	1509	1754	882	4.60	52.71	6.76	1.70	1.98
-5	(+23)	7254	1828	2126	931	4.80	64.61	7.75	1.95	2.27
0	(+32)	8740	2203	2561	972	4.97	79.00	8.95	2.26	2.62
+5	(+41)	10493	2644	3075	1005	5.12	96.53	10.43	2.63	3.06
+10	(+50)	12561	3165	3681	1032	5.24	117.85	12.24	3.08	3.59

TEST CONDITIONS: @220V50Hz			EN12900 Fan		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	2995	755	878	794	4.26	30.55	3.74	0.94	1.10
-15	(+ 5)	3870	975	1134	882	4.61	39.67	4.40	1.11	1.29
-10	(+14)	4794	1208	1405	962	4.93	49.68	5.02	1.26	1.47
-5	(+23)	5816	1466	1704	1033	5.23	61.21	5.66	1.43	1.66
0	(+32)	6983	1760	2046	1096	5.50	74.91	6.37	1.61	1.87
+5	(+41)	8343	2103	2445	1152	5.75	91.44	7.22	1.82	2.12
+10	(+50)	9945	2506	2914	1201	5.98	111.44	8.27	2.08	2.42

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	12.77 +0.08/+0.00	[mm]	(0.503" +0.003"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted		
3.2 DISCHARGE	9.6 +0.07/+0.00	[mm]	(0.378" +0.003"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Vertical		
3.3 PROCESS	6.42 +0.08/+0.00	[mm]	(0.253" +0.003"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Vertical		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		