

COMPRESSOR DEFINITION

Designation	EG X100CLC
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	513703069

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	198 to 255 V	-
8.2 LBP (43°C Ambient temperature)	Static	198 to 255 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	6.9	[kgf/cm ²] (98 psig)	/ °C - °F
9.2 Peak	7.8	[kgf/cm ²] (111 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/3	[hp]
2 Displacement	13.54	[cm ³] (0.826 cu.in)
2.1 Bore [mm]	28.000	
2.2 Stroke [mm]	22.000	
3 Lubricant charge	280	[ml] (9.47 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO5	
4 Weight (with oil charge)	11.24	[kg] (24.78 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	TSD	
2.1 Starting device	TSD-220V/TSD2-220V	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	4(350)/5(350)	[µF(VAC minimum)]
5 Motor protection	4TM283KFBYY-53	
6 Start winding resistance	21.20	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	19.60	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	4.90	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	CCC - CE - UKCA - VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			CECOMAFLBP-NOFAN Static		Evaporating temperature (Condensing temperature	-25°C (-13°F) 55°C (131°F)		
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
577	145	169	117	0.54	2.20	4.95	1.25	1.45

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			CECOMAF-NOFAN Static		(Condensing temperature 45°C (+113°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	395	100	116	82	0.40	1.37	4.80	1.21	1.41
-30 (-22)	520	131	152	97	0.46	1.82	5.39	1.36	1.58
-25 (-13)	654	165	192	110	0.52	2.28	6.03	1.52	1.77
-20 (- 4)	813	205	238	121	0.57	2.83	6.72	1.69	1.97
-15 (+ 5)	1014	255	297	134	0.63	3.53	7.49	1.89	2.19
-10 (+14)	1271	320	373	150	0.71	4.44	8.34	2.10	2.44

TEST CONDITIONS: @220V50Hz			CECOMAF-NOFAN Static		(Condensing temperature 55°C (+131°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	309	78	91	79	0.39	1.17	3.87	0.97	1.13
-30 (-22)	445	112	130	100	0.47	1.70	4.44	1.12	1.30
-25 (-13)	577	145	169	117	0.54	2.21	4.99	1.26	1.46
-20 (- 4)	722	182	211	131	0.61	2.76	5.54	1.40	1.62
-15 (+ 5)	895	225	262	146	0.68	3.43	6.12	1.54	1.79
-10 (+14)	1112	280	326	165	0.77	4.27	6.72	1.69	1.97

TEST CONDITIONS: @220V50Hz			CECOMAF-NOFAN Static		(Condensing temperature 65°C (+149°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	197	50	58	69	0.36	0.83	2.86	0.72	0.84
-30 (-22)	350	88	103	97	0.47	1.47	3.47	0.87	1.02
-25 (-13)	487	123	143	119	0.56	2.05	4.01	1.01	1.17
-20 (- 4)	624	157	183	139	0.65	2.64	4.50	1.13	1.32
-15 (+ 5)	776	195	227	158	0.73	3.30	4.94	1.25	1.45
-10 (+14)	959	242	281	180	0.83	4.09	5.37	1.35	1.57

F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted		
3.3 PROCESS	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		