

COMPRESSOR DEFINITION

Designation	EM R40CLP
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	513300149

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	187 to 255 V	-
8.2 LBP (43°C Ambient temperature)	Static	187 to 255 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	6.9	[kgf/cm ²] (98 psig)	/ °C - °F
9.2 Peak	7.8	[kgf/cm ²] (111 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/6	[hp]
2 Displacement	7.23	[cm ³] (0.441 cu.in)
2.1 Bore [mm]	24.000	
2.2 Stroke [mm]	16.000	
3 Lubricant charge	150	[ml] (5.07 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO5	
4 Weight (with oil charge)	7.4	[kg] (16.31 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	8EA17B3	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	4(350)	[µF(VAC minimum)]
5 Motor protection	4TM134NFBYY-53	
6 Start winding resistance	[Ω at 25°C (77°F)] +/- 8%	
7 Run winding resistance	[Ω at 25°C (77°F)] +/- 8%	
8 LRA - Locked rotor amperage (50 Hz)	-	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	CCC - VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
436	110	128	76	0.36	1.37	5.72	1.44	1.68

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 45°C (+113°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	229	58	67	53	0.31	0.72	4.29	1.08	1.26
-30 (-22)	315	79	92	62	0.34	0.99	5.12	1.29	1.50
-25 (-13)	419	106	123	70	0.38	1.32	5.98	1.51	1.75
-20 (- 4)	545	137	160	79	0.42	1.71	6.90	1.74	2.02
-15 (+ 5)	694	175	203	88	0.47	2.18	7.86	1.98	2.30
-10 (+14)	868	219	254	98	0.51	2.74	8.88	2.24	2.60

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 55°C (+131°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	202	51	59	53	0.31	0.63	3.85	0.97	1.13
-30 (-22)	290	73	85	63	0.34	0.91	4.63	1.17	1.36
-25 (-13)	394	99	116	73	0.39	1.24	5.40	1.36	1.58
-20 (- 4)	518	131	152	84	0.44	1.63	6.18	1.56	1.81
-15 (+ 5)	664	167	194	95	0.49	2.09	6.96	1.75	2.04
-10 (+14)	833	210	244	107	0.55	2.63	7.75	1.95	2.27

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 65°C (+149°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	178	45	52	55	0.32	0.56	3.23	0.81	0.95
-30 (-22)	263	66	77	65	0.35	0.82	4.00	1.01	1.17
-25 (-13)	362	91	106	76	0.40	1.14	4.72	1.19	1.38
-20 (- 4)	480	121	141	89	0.46	1.51	5.41	1.36	1.59
-15 (+ 5)	617	155	181	102	0.52	1.94	6.06	1.53	1.78
-10 (+14)	776	195	227	116	0.59	2.45	6.68	1.68	1.96

F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard EUEM		
2 Tray holder	Yes		
3 Connectors			
3.1 SUCTION	6.2 +0.05/+0.05	[mm]	(0.244" +0.002"/+0.002")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 40° up + 45° to Back		
3.2 DISCHARGE	4.9 +0.10/-0.05	[mm]	(0.193" +0.004"/-0.002")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted 0° up + 24° to Back		
3.3 PROCESS	6.2 +0.05/+0.05	[mm]	(0.244" +0.002"/+0.002")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 40° up + 45° to Back		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		