

COMPRESSOR DEFINITION

Designation	NB T1116Y
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	815EA47

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSIR-RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	198 to 254 V	-
8.2 LBP (43°C Ambient temperature)	Static	198 to 254 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	7.7	[kgf/cm ²] (109 psig)	/ °C - °F
9.2 Peak (gauge)	9.8	[kgf/cm ²] (139 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation		[hp]
2 Displacement	12.11	[cm ³] (0.739 cu.in)
2.1 Bore [mm]	27.775	
2.2 Stroke [mm]	20.000	
3 Lubricant charge	280	[ml] (9.47 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO5	
4 Weight (with oil charge)	10.73	[kg] (23.66 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	V230	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	4(450)	[µF(VAC minimum)]
5 Motor protection	T0521/07	
6 Start winding resistance	20.90	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	17.80	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	-	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			CECOMAFLBP Static		Evaporating temperature (Condensing temperature		-25°C (-13°F) 55°C (131°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
522	132	153	120	0.59	1.99	4.35	1.10	1.27

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		CECOMAF Static				(Condensing temperature 35°C (+95°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	405	102	119	84	0.42	1.30	4.81	1.21	1.41
-30	(-22)	525	132	154	97	0.47	1.68	5.45	1.37	1.60
-25	(-13)	682	172	200	109	0.53	2.19	6.27	1.58	1.84
-20	(- 4)	878	221	257	121	0.60	2.82	7.27	1.83	2.13
-15	(+ 5)	1113	281	326	132	0.67	3.58	8.42	2.12	2.47
-10	(+14)	1389	350	407	143	0.73	4.48	9.70	2.45	2.84

TEST CONDITIONS: @220V50Hz		CECOMAF Static				(Condensing temperature 45°C (+113°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	358	90	105	87	0.41	1.24	4.14	1.04	1.21
-30	(-22)	464	117	136	101	0.49	1.62	4.60	1.16	1.35
-25	(-13)	603	152	177	115	0.56	2.10	5.21	1.31	1.53
-20	(- 4)	775	195	227	130	0.65	2.70	5.93	1.49	1.74
-15	(+ 5)	983	248	288	145	0.72	3.43	6.76	1.70	1.98
-10	(+14)	1226	309	359	160	0.80	4.29	7.66	1.93	2.25

TEST CONDITIONS: @220V50Hz		CECOMAF Static				(Condensing temperature 55°C (+131°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	303	76	89	89	0.44	1.15	3.44	0.87	1.01
-30	(-22)	397	100	116	105	0.52	1.51	3.81	0.96	1.12
-25	(-13)	519	131	152	121	0.61	1.98	4.28	1.08	1.25
-20	(- 4)	671	169	197	139	0.70	2.56	4.81	1.21	1.41
-15	(+ 5)	853	215	250	157	0.77	3.26	5.40	1.36	1.58
-10	(+14)	1066	269	312	177	0.84	4.09	6.02	1.52	1.76

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		CECOMAF Static			(Condensing temperature 65°C (+149°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	238	60	70	89	0.45	1.00	2.66	0.67	0.78
-30	(-22)	322	81	94	106	0.54	1.36	3.03	0.76	0.89
-25	(-13)	430	108	126	125	0.63	1.82	3.44	0.87	1.01
-20	(- 4)	562	142	165	146	0.71	2.38	3.87	0.98	1.13
-15	(+ 5)	721	182	211	168	0.78	3.06	4.31	1.09	1.26
-10	(+14)	906	228	265	192	0.83	3.86	4.73	1.19	1.39

F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted parallel to Base Plate		
3.3 PROCESS	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		