

COMPRESSOR DEFINITION

Designation	NT U6222ZV
Nominal Voltage/Frequency	115 V 60 Hz
Engineering Number	215AG60

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	115 / 60	[V / Hz]	
4 Application type	High Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-15°C to 10°C	(5°F to 50°F)	
5 Motor type	CSCR		
6 Starting torque	HST - Hight starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	14.2	[kgf/cm ²] (202 psig)	/ °C - °F
9.2 Peak	15.9	[kgf/cm ²] (226 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1-	[hp]
2 Displacement	23.74	[cm ³] (1.449 cu.in)
2.1 Bore [mm]	38.100	
2.2 Stroke [mm]	20.830	
3 Lubricant charge	650	[ml] (21.98 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	18.3	[kg] (40.34 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	115 V 60 Hz 1~ (Single phase)	
2 Starting device type	Voltage Relay	
2.1 Starting device	3ARR3B2L3	
3 Start capacitor	340-408(250)	[µF(VAC minimum)]
4 Run capacitor	40(440)	[µF(VAC minimum)]
5 Motor protection	15HM1958	
6 Start winding resistance	1.06	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	0.42	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	-	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	UL	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @115V60Hz			ARIHBP Fan		Evaporating temperature (Condensing temperature		7.2°C (44.96°F) 54.4°C (129.92°F)		
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
9964	2511	2920	1047	10.20	78.19	9.52	2.40	2.79	

E - PERFORMANCE - CURVES

TEST CONDITIONS: @115V60Hz		ARI18 Fan			(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+5)	4950	1247	1450	604	7.05	30.95	8.19	2.06	2.40
-10	(+14)	6323	1593	1853	668	7.41	39.77	9.46	2.38	2.77
-5	(+23)	7916	1995	2320	723	7.75	50.04	10.94	2.76	3.21
0	(+32)	9753	2458	2858	769	8.11	62.02	12.71	3.20	3.72
+5	(+41)	11859	2988	3475	803	8.54	76.00	14.80	3.73	4.34
+10	(+50)	14259	3593	4178	824	9.09	92.26	17.27	4.35	5.06

TEST CONDITIONS: @115V60Hz		ARI18 Fan			(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+5)	4193	1057	1229	629	7.25	28.77	6.70	1.69	1.96
-10	(+14)	5448	1373	1596	712	7.67	37.60	7.65	1.93	2.24
-5	(+23)	6895	1738	2020	788	8.07	47.86	8.72	2.20	2.56
0	(+32)	8559	2157	2508	856	8.50	59.82	9.97	2.51	2.92
+5	(+41)	10465	2637	3067	915	9.00	73.78	11.43	2.88	3.35
+10	(+50)	12638	3185	3703	963	9.63	90.00	13.16	3.32	3.86

TEST CONDITIONS: @115V60Hz		ARI18 Fan			(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+5)	3475	876	1018	646	7.26	26.54	5.35	1.35	1.57
-10	(+14)	4591	1157	1345	747	7.85	35.25	6.17	1.55	1.81
-5	(+23)	5872	1480	1721	843	8.41	45.38	6.99	1.76	2.05
0	(+32)	7342	1850	2151	933	9.00	57.21	7.87	1.98	2.31
+5	(+41)	9026	2275	2645	1016	9.67	71.02	8.87	2.24	2.60
+10	(+50)	10950	2759	3209	1090	10.47	87.10	10.04	2.53	2.94

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	12.77 +0.08/+0.00	[mm]	(0.503" +0.003"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted		
3.2 DISCHARGE	9.6 +0.07/+0.00	[mm]	(0.378" +0.003"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Vertical		
3.3 PROCESS	6.42 +0.08/+0.00	[mm]	(0.253" +0.003"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Vertical		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		