

### COMPRESSOR DEFINITION

|                           |             |
|---------------------------|-------------|
| Designation               | NT U6222ZV  |
| Nominal Voltage/Frequency | 115 V 60 Hz |
| Engineering Number        | 215AG60     |

### A - APPLICATION / LIMIT WORKING CONDITIONS

|                                    |   |                                   |           |
|------------------------------------|---|-----------------------------------|-----------|
| 1 Type                             | Hermetic reciprocating compressor           |                                   |           |
| 2 Refrigerant                      | R-134a                                      |                                   |           |
| 3 Nominal voltage and frequency    | 115 / 60                                    | [ V / Hz ]                        |           |
| 4 Application type                 | High Back Pressure (Commercial Compressors) |                                   |           |
| 4.1 Evaporating temperature range  | -15°C to 10°C                               | (5°F to 50°F)                     |           |
| 5 Motor type                       | CSCR  |                                   |           |
| 6 Starting torque                  | HST - Hight starting torque                 |                                   |           |
| 7 Expansion device                 | Capillary tube or Expansion valve           |                                   |           |
| 8 Compressor cooling               | Operating voltage range                     |                                   |           |
|                                    |   | 50 Hz                             | 60 Hz     |
| 8.1 LBP (32°C Ambient temperature) | -   | -                                 | -         |
| 8.2 LBP (43°C Ambient temperature) | -   | -                                 | -         |
| 8.3 HBP (32°C Ambient temperature) | -   | -                                 | -         |
| 8.4 HBP (43°C Ambient temperature) | -   | -                                 | -         |
| 9 Maximum condensing temperature   |   |                                   |           |
| 9.1 Operating                      | 14.2  | [kgf/cm <sup>2</sup> ] (202 psig) | / °C - °F |
| 9.2 Peak                           | 15.9  | [kgf/cm <sup>2</sup> ] (226 psig) | / °C - °F |
| 10 Maximum winding temperature     | 130   | [ °C ]                            |           |

### B - MECHANICAL DATA

|                               |               |  |
|-------------------------------|---------------|--|
| 1 Commercial designation      | 1-            | [hp]                                       |
| 2 Displacement                | 23.74         | [cm <sup>3</sup> ] (1.449 cu.in)           |
| 2.1 Bore [mm]                 | 38.100        |  |
| 2.2 Stroke [mm]               | 20.830        |  |
| 3 Lubricant charge            | 650           | [ml] (21.98 fl.oz.)                        |
| 3.1 Lubricants approved       |               |  |
| 3.2 Lubricants type/viscosity | ESTER / ISO22 |  |
| 4 Weight (with oil charge)    | 18.3          | [kg] (40.34 lb.)                           |
| 5 Nitrogen charge             | 0.2 to 0.3    | [kgf/cm <sup>2</sup> ] (2.84 to 4.27 psig) |

### C - ELETRICAL DATA

|  |                               |                                    |
|--|-------------------------------|------------------------------------|
| 1 Nominal Voltage/Frequency/Number of Phases | 115 V 60 Hz 1~ (Single phase) |                                    |
| 2 Starting device type                       | Voltage Relay                 |                                    |
| 2.1 Starting device                          | 3ARR3B2L3                     |                                    |
| 3 Start capacitor                            | 340-408(250)                  | [µF(VAC minimum)]                  |
| 4 Run capacitor                              | 40(440)                       | [µF(VAC minimum)]                  |
| 5 Motor protection                           | 15HM1958                      |                                    |
| 6 Start winding resistance                   | 1.06                          | [Ω at 25°C (77°F)] +/- 8%          |
| 7 Run winding resistance                     | 0.42                          | [Ω at 25°C (77°F)] +/- 8%          |
| 8 LRA - Locked rotor amperage (60 Hz)        | -                             | [A] - Measured according to UL 984 |
| 9 FLA - Full load amperage L/MBP (60 Hz)     | -                             | [A] - Measured according to UL 984 |
| 10 FLA - Full Load Amperage HBP (60 Hz)      | -                             | [A] - Measured according to UL 984 |
| 11 Approval boards certification             | UL                            |                                    |

### D - PERFORMANCE - CHECK POINT DATA

|                               |          |      |                                |                                  |  |                           |                                      |       |
|-------------------------------|----------|------|--------------------------------|----------------------------------|--|---------------------------|--------------------------------------|-------|
| TEST CONDITIONS:<br>@115V60Hz |          |      | ASHRAEHBP46<br>Fan             |                                  | Evaporating temperature<br>(Condensing temperature |                           | 7.2°C (44.96°F)<br>54.4°C (129.92°F) |       |
| Cooling capacity<br>+/- 5%    |          |      | Power<br>consumption<br>+/- 5% | Current<br>consumption<br>+/- 5% | Gas flow<br>rate<br>+/- 5%                         | EFFICIENCY RATE<br>+/- 7% |                                      |       |
| [Btu/h]                       | [kcal/h] | [W]  | [W]                            | [A]                              | [kg/h]   | [Btu/Wh]                  | [kcal/Wh]                            | [W/W] |
| 10501                         | 2646     | 3077 | 1039                           | 10.10                            | 68.09  | 10.11                     | 2.55                                 | 2.96  |

### E - PERFORMANCE - CURVES

### F - EXTERNAL CHARACTERISTICS

|                         |                   |      |                          |
|-------------------------|-------------------|------|--------------------------|
| 1 Base plate            | Universal         |      |                          |
| 2 Tray holder           | No                |      |                          |
| 3 Connectors            |                   |      |                          |
| 3.1 SUCTION             | 12.77 +0.08/+0.00 | [mm] | (0.503" +0.003"/+0.000") |
| 3.1.1 Material          | Copper            |      |                          |
| 3.1.2 Shape             | Slanted           |      |                          |
| 3.2 DISCHARGE           | 9.6 +0.07/+0.00   | [mm] | (0.378" +0.003"/+0.000") |
| 3.2.1 Material          | Copper            |      |                          |
| 3.2.2 Shape             | Vertical          |      |                          |
| 3.3 PROCESS             | 6.42 +0.08/+0.00  | [mm] | (0.253" +0.003"/+0.000") |
| 3.3.1 Material          | Copper            |      |                          |
| 3.3.2 Shape             | Vertical          |      |                          |
| 3.4 Oil cooler (Copper) | No                | [mm] |                          |
| 3.5 Connector sealing   | Rubber Plugs      |      |                          |