

COMPRESSOR DEFINITION

Designation	EG Y100HLC
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	513700116

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static/Fan	198 to 255 V	-
8.2 LBP (43°C Ambient temperature)	Static/Fan	198 to 255 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	16.2	[kgf/cm ²] (230 psig)	/ °C - °F
9.2 Peak (gauge)	20.6	[kgf/cm ²] (293 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/3	[hp]
2 Displacement	8.59	[cm ³] (0.524 cu.in)
2.1 Bore [mm]	24.000	
2.2 Stroke [mm]	19.000	
3 Lubricant charge	280	[ml] (9.47 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO10	
4 Weight (with oil charge)	11.33	[kg] (24.98 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	Combo	
2.1 Starting device	3ARR5XS7L/3ARR5XT7L	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	5(350)	[µF(VAC minimum)]
5 Motor protection	3ARR5XS7L	
6 Start winding resistance	21.40	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	15.50	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	6.20	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	0.95	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification		

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)		
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
875	221	256	155	0.73	4.97	5.63	1.42	1.65	

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Fan		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)		
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
890	224	261	156	0.73	5.06	5.70	1.44	1.67	

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		ASHRAE32 Static				(Condensing temperature 45°C (+113°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	446	112	131	100	0.46	2.52	4.48	1.13	1.31
-30	(-22)	643	162	188	120	0.56	3.64	5.32	1.34	1.56
-25	(-13)	861	217	252	141	0.65	4.89	6.10	1.54	1.79
-20	(- 4)	1116	281	327	163	0.75	6.35	6.88	1.73	2.01
-15	(+ 5)	1427	359	418	185	0.85	8.14	7.70	1.94	2.26
-10	(+14)	1808	456	530	209	0.96	10.36	8.63	2.17	2.53

TEST CONDITIONS: @220V50Hz		ASHRAE32 Static				(Condensing temperature 55°C (+131°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	399	101	117	99	0.46	2.26	4.04	1.02	1.18
-30	(-22)	586	148	172	122	0.56	3.32	4.78	1.20	1.40
-25	(-13)	792	200	232	146	0.67	4.50	5.43	1.37	1.59
-20	(- 4)	1035	261	303	171	0.79	5.89	6.05	1.52	1.77
-15	(+ 5)	1331	335	390	199	0.91	7.60	6.69	1.68	1.96
-10	(+14)	1698	428	498	229	1.05	9.73	7.39	1.86	2.17

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		ASHRAE32 Static			(Condensing temperature 65°C (+149°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	330	83	97	93	0.43	1.87	3.54	0.89	1.04
-30	(-22)	507	128	149	119	0.55	2.87	4.22	1.06	1.24
-25	(-13)	702	177	206	147	0.68	3.98	4.79	1.21	1.40
-20	(- 4)	932	235	273	177	0.82	5.31	5.29	1.33	1.55
-15	(+ 5)	1215	306	356	211	0.97	6.94	5.78	1.46	1.69
-10	(+14)	1568	395	459	248	1.14	8.98	6.31	1.59	1.85

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal EG/F/AMEM version 2		
2 Tray holder	Yes		
3 Connectors			
3.1 SUCTION	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.1.1 Material	Copper		
3.1.2 Shape	Straight		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.3.1 Material	Copper		
3.3.2 Shape	Straight		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		