

COMPRESSOR DEFINITION

Designation	EG YS90HLP
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	513701224

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	160 to 260 V	-
8.2 LBP (43°C Ambient temperature)	Static	160 to 260 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	16.2	[kgf/cm ²] (230 psig)	/ °C - °F
9.2 Peak (gauge)	20.6	[kgf/cm ²] (293 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/4+	[hp]
2 Displacement	7.15	[cm ³] (0.436 cu.in)
2.1 Bore [mm]	22.500	
2.2 Stroke [mm]	18.000	
3 Lubricant charge	230	[ml] (7.78 fl.oz)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO10	
4 Weight (with oil charge)	10.92	[kg] (24.07 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	5SP17XXXXXX	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	5(350)	[µF(VAC minimum)]
5 Motor protection	5SP17X319LFX	
6 Start winding resistance	20.94	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	12.03	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	8.20	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	1.18	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	1.53	[A] - Measured according to UL 984
11 Approval boards certification		

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
770	194	226	130	0.70	4.38	5.93	1.49	1.74

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 45°C (+113°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	405	102	119	86	0.47	2.29	4.69	1.18	1.38
-30 (-22)	572	144	167	102	0.55	3.24	5.57	1.40	1.63
-25 (-13)	758	191	222	120	0.64	4.30	6.34	1.60	1.86
-20 (- 4)	977	246	286	138	0.74	5.56	7.11	1.79	2.08
-15 (+ 5)	1245	314	365	156	0.84	7.10	7.97	2.01	2.33
-10 (+14)	1574	397	461	174	0.93	9.02	9.01	2.27	2.64

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 55°C (+131°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	334	84	98	82	0.46	1.89	4.08	1.03	1.20
-30 (-22)	507	128	149	102	0.55	2.88	4.95	1.25	1.45
-25 (-13)	696	176	204	123	0.66	3.95	5.66	1.43	1.66
-20 (- 4)	915	231	268	145	0.77	5.21	6.32	1.59	1.85
-15 (+ 5)	1178	297	345	168	0.89	6.73	7.01	1.77	2.05
-10 (+14)	1500	378	439	191	1.01	8.59	7.83	1.97	2.29

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 65°C (+149°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	256	64	75	73	0.41	1.45	3.49	0.88	1.02
-30 (-22)	432	109	127	97	0.52	2.45	4.38	1.10	1.28
-25 (-13)	620	156	182	122	0.65	3.52	5.06	1.28	1.48
-20 (- 4)	834	210	244	149	0.79	4.74	5.63	1.42	1.65
-15 (+ 5)	1088	274	319	176	0.94	6.21	6.18	1.56	1.81
-10 (+14)	1397	352	409	205	1.09	8.00	6.81	1.72	2.00

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal EG/F/AMEM version 2		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.1.1 Material	Copper		
3.1.2 Shape	Straight		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.3.1 Material	Copper		
3.3.2 Shape	Straight		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		