

COMPRESSOR DEFINITION

Designation	EM 2C70CLT
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	513304507

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	198 to 255 V	-
8.2 LBP (43°C Ambient temperature)	Static	198 to 255 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	7.7	[kgf/cm ²] (109 psig)	/ °C - °F
9.2 Peak (gauge)	9.8	[kgf/cm ²] (139 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation		[hp]
2 Displacement	11.14	[cm ³] (0.680 cu.in)
2.1 Bore [mm]	26.000	
2.2 Stroke [mm]	21.000	
3 Lubricant charge	150	[ml] (5.07 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	MINERAL / ISO5	
4 Weight (with oil charge)	8.36	[kg] (18.43 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	V230	
3 Start capacitor	-	[μF(VAC minimum)]
4 Run capacitor	5(300)	[μF(VAC minimum)]
5 Motor protection	T0225/07	
6 Start winding resistance	14.50	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	19.05	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	4.80	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	0.75	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAE LBP-NOFAN Static		Evaporating temperature (Condensing temperature	-23.3°C (-9.94°F) 54.4°C (129.92°F)		
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
645	163	189	105	0.48		6.16	1.55	1.81

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			ASHRAE32-NOFAN Static		(Condensing temperature 35°C (+95°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	378	95	111	70	0.34	1.18	5.39	1.36	1.58
-30 (-22)	500	126	146	81	0.38	1.57	6.16	1.55	1.81
-25 (-13)	654	165	192	93	0.42	2.05	7.08	1.78	2.07
-20 (- 4)	841	212	246	104	0.47	2.64	8.09	2.04	2.37
-15 (+ 5)	1062	268	311	116	0.52	3.34	9.15	2.31	2.68
-10 (+14)	1318	332	386	129	0.58	4.16	10.22	2.57	2.99

TEST CONDITIONS: @220V50Hz			ASHRAE32-NOFAN Static		(Condensing temperature 45°C (+113°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	358	90	105	71	0.34	1.12	5.02	1.26	1.47
-30 (-22)	474	119	139	84	0.39	1.49	5.66	1.43	1.66
-25 (-13)	622	157	182	97	0.44	1.95	6.43	1.62	1.88
-20 (- 4)	804	202	235	110	0.50	2.53	7.29	1.84	2.14
-15 (+ 5)	1019	257	298	124	0.57	3.21	8.19	2.06	2.40
-10 (+14)	1268	320	372	140	0.64	4.00	9.08	2.29	2.66

TEST CONDITIONS: @220V50Hz			ASHRAE32-NOFAN Static		(Condensing temperature 55°C (+131°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	332	84	97	71	0.34	1.04	4.68	1.18	1.37
-30 (-22)	443	112	130	85	0.40	1.39	5.21	1.31	1.53
-25 (-13)	586	148	172	100	0.46	1.84	5.87	1.48	1.72
-20 (- 4)	763	192	223	115	0.53	2.40	6.60	1.66	1.93
-15 (+ 5)	973	245	285	132	0.60	3.06	7.36	1.85	2.16
-10 (+14)	1218	307	357	150	0.68	3.84	8.10	2.04	2.37

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		ASHRAE32-NOFAN Static			(Condensing temperature 65°C (+149°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	298	75	87	68	0.34	0.93	4.37	1.10	1.28
-30	(-22)	406	102	119	84	0.40	1.27	4.83	1.22	1.41
-25	(-13)	546	138	160	101	0.47	1.71	5.39	1.36	1.58
-20	(- 4)	719	181	211	119	0.55	2.26	6.02	1.52	1.76
-15	(+ 5)	926	233	271	139	0.63	2.92	6.67	1.68	1.95
-10	(+14)	1167	294	342	160	0.72	3.68	7.29	1.84	2.14

F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard EUEM		
2 Tray holder	Yes		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42° up + 45° to Back		
3.2 DISCHARGE	5.1 +0.10/+0.00	[mm]	(0.201" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted 42° up + 24° to Back		
3.3 PROCESS	6 +0.08/-0.08	[mm]	(0.236" +0.003"/-0.003")
3.3.1 Material	Copper(OD)		
3.3.2 Shape	Slanted 43° up + 45° to Back		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		