

COMPRESSOR DEFINITION

Designation	EM YE70HEP
Nominal Voltage/Frequency	220 V 50 Hz
Engineering Number	513306569

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	220 / 50	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	198 to 242 V	-
8.2 LBP (43°C Ambient temperature)	Static	198 to 242 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	14.2	[kgf/cm ²] (202 psig)	/ °C - °F
9.2 Peak	15.9	[kgf/cm ²] (226 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/5	[hp]
2 Displacement	5.96	[cm ³] (0.364 cu.in)
2.1 Bore [mm]	22.500	
2.2 Stroke [mm]	15.000	
3 Lubricant charge	180	[ml] (6.09 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO10	
4 Weight (with oil charge)	7.49	[kg] (16.51 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	7M220MD3/8EA17C3/8EA17E63/8M220MD3/QPS2-A22MD3/QI	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	5(300)	[µF(VAC minimum)]
5 Motor protection	4TM232KFBYY-53	
6 Start winding resistance	18.88	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	19.62	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	5.80	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	1.40	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	1.58	[A] - Measured according to UL 984
11 Approval boards certification	IRAM	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
567	143	166	118	0.65	3.22	4.83	1.22	1.42

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 45°C (+113°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	293	74	86	79	0.52	1.66	3.68	0.93	1.08
-30 (-22)	413	104	121	94	0.57	2.34	4.42	1.11	1.30
-25 (-13)	566	143	166	109	0.62	3.21	5.22	1.32	1.53
-20 (- 4)	753	190	221	124	0.67	4.28	6.08	1.53	1.78
-15 (+ 5)	974	245	285	140	0.73	5.56	6.98	1.76	2.05
-10 (+14)	1231	310	361	156	0.79	7.05	7.92	2.00	2.32

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 55°C (+131°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	230	58	67	79	0.52	1.30	2.96	0.75	0.87
-30 (-22)	351	89	103	94	0.57	1.99	3.74	0.94	1.10
-25 (-13)	508	128	149	110	0.62	2.89	4.56	1.15	1.34
-20 (- 4)	701	177	205	128	0.69	3.99	5.41	1.36	1.58
-15 (+ 5)	931	235	273	147	0.76	5.32	6.28	1.58	1.84
-10 (+14)	1199	302	351	168	0.84	6.87	7.16	1.80	2.10

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 65°C (+149°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	207	52	61	76	0.51	1.17	2.70	0.68	0.79
-30 (-22)	303	76	89	90	0.55	1.72	3.39	0.85	0.99
-25 (-13)	437	110	128	108	0.61	2.48	4.08	1.03	1.20
-20 (- 4)	609	153	178	128	0.68	3.47	4.78	1.21	1.40
-15 (+ 5)	821	207	241	150	0.77	4.69	5.48	1.38	1.61
-10 (+14)	1074	271	315	174	0.87	6.15	6.16	1.55	1.81

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal EUEM		
2 Tray holder	Yes		
3 Connectors			
3.1 SUCTION	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42° up + 45° to Back		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.35 +0.08/-0.08	[mm]	(0.250" +0.003"/-0.003")
3.3.1 Material	Copper(OD)		
3.3.2 Shape	Slanted 43° up + 45° to Back		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		