

COMPRESSOR DEFINITION

Designation	EG Y80HLPW
Nominal Voltage/Frequency	115-127 V 60 Hz
Engineering Number	513700133

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	115-127 / 60	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSIR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	-	103 to 140 V
8.2 LBP (43°C Ambient temperature)	Static	-	103 to 140 V
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	16.2	[kgf/cm ²] (230 psig)	/ °C - °F
9.2 Peak (gauge)	20.6	[kgf/cm ²] (293 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/4	[hp]
2 Displacement	6.76	[cm ³] (0.413 cu.in)
2.1 Bore [mm]	22.500	
2.2 Stroke [mm]	17.000	
3 Lubricant charge	280	[ml] (9.47 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO10	
4 Weight (with oil charge)	11.43	[kg] (25.20 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	115-127 V 60 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	7M4R7MC1/8EA14C1/8EA1B1/8EA21C1/8EA3B1/8EA4B1/8M4I	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	4TM445KFBYY-53	
6 Start winding resistance	5.60	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	3.50	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	13.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	2.10	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	UL	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @115V60Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)		
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
815	205	239	152	1.77	4.63	5.35	1.35	1.57	

E - PERFORMANCE - CURVES

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 45°C (+113°F))					
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
-35 (-31)	436	110	128	99	1.45	2.46	4.40	1.11	1.29	
-30 (-22)	609	154	179	121	1.58	3.45	5.02	1.26	1.47	
-25 (-13)	823	207	241	143	1.72	4.67	5.73	1.44	1.68	
-20 (- 4)	1082	273	317	166	1.88	6.16	6.53	1.65	1.91	
-15 (+ 5)	1394	351	409	188	2.05	7.96	7.42	1.87	2.17	
-10 (+14)	1766	445	518	211	2.24	10.12	8.38	2.11	2.46	

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 55°C (+131°F))					
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
-35 (-31)	400	101	117	102	1.46	2.27	3.94	0.99	1.16	
-30 (-22)	556	140	163	124	1.59	3.15	4.49	1.13	1.32	
-25 (-13)	751	189	220	148	1.75	4.26	5.09	1.28	1.49	
-20 (- 4)	993	250	291	173	1.93	5.65	5.74	1.45	1.68	
-15 (+ 5)	1287	324	377	200	2.15	7.35	6.43	1.62	1.89	
-10 (+14)	1642	414	481	229	2.39	9.41	7.17	1.81	2.10	

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 65°C (+149°F))					
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
-35 (-31)	334	84	98	95	1.43	1.89	3.49	0.88	1.02	
-30 (-22)	478	120	140	119	1.57	2.71	4.00	1.01	1.17	
-25 (-13)	661	167	194	146	1.75	3.75	4.53	1.14	1.33	
-20 (- 4)	891	225	261	176	1.96	5.07	5.08	1.28	1.49	
-15 (+ 5)	1175	296	344	209	2.22	6.70	5.64	1.42	1.65	
-10 (+14)	1518	383	445	245	2.52	8.70	6.20	1.56	1.82	

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal EG/F/AMEM version 2		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.1.1 Material	Copper		
3.1.2 Shape	Straight		
3.2 DISCHARGE	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.3.1 Material	Copper		
3.3.2 Shape	Straight		
3.4 Oil cooler (Copper)	6.5 +0.09/-0.09	[mm]	(0.256" +0.004"/-0.004")
3.5 Connector sealing	Rubber Plugs		