

### COMPRESSOR DEFINITION

Designation	EG S90CLP
Nominal Voltage/Frequency	220-240 V 50-60 Hz
Engineering Number	513700258

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	220-240 / 50-60	[ V / Hz ]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSIR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	187 to 255 V	187 to 242 V
8.2 LBP (43°C Ambient temperature)	Static	187 to 255 V	187 to 242 V
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	7.7	[kgf/cm <sup>2</sup> ] (109 psig)	/ °C - °F
9.2 Peak (gauge)	9.8	[kgf/cm <sup>2</sup> ] (139 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation	1/4+	[hp]
2 Displacement	12.21	[cm <sup>3</sup> ] (0.745 cu.in)
2.1 Bore [mm]	26.000	
2.2 Stroke [mm]	23.000	
3 Lubricant charge	280	[ml] (9.47 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	MINERAL / ISO7	
4 Weight (with oil charge)	11.11	[kg] (24.49 lb.)
5 Nitrogen charge	-	[kgf/cm <sup>2</sup> ]

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50-60 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	7M220MC1/8EA17C1/8EA5B1/8M220MC1/MS34X 220V	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	MSC34F49J3	
6 Start winding resistance	20.20	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	9.35	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50/60 Hz)	11.40/10.50	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50/60 Hz)	1.93/1.73	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50/60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification		

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			<b>CECOMAFLBP</b> Static		Evaporating temperature (Condensing temperature		-25°C (-13°F) 55°C (131°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
566	143	166	142	1.26	2.16	4.00	1.01	1.17

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			<b>CECOMAF</b> Static		(Condensing temperature 45°C (+113°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	382	96	112	104	1.18	1.33	3.65	0.92	1.07
-30 (-22)	491	124	144	119	1.21	1.71	4.15	1.05	1.22
-25 (-13)	639	161	187	135	1.24	2.22	4.77	1.20	1.40
-20 (- 4)	829	209	243	151	1.28	2.89	5.49	1.38	1.61
-15 (+ 5)	1062	268	311	168	1.32	3.71	6.33	1.59	1.85
-10 (+14)	1341	338	393	185	1.36	4.70	7.27	1.83	2.13

TEST CONDITIONS: @220V50Hz			<b>CECOMAF</b> Static		(Condensing temperature 55°C (+131°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	332	84	97	108	1.19	1.26	3.08	0.78	0.90
-30 (-22)	433	109	127	124	1.22	1.65	3.51	0.88	1.03
-25 (-13)	566	143	166	141	1.26	2.16	4.00	1.01	1.17
-20 (- 4)	733	185	215	160	1.30	2.80	4.56	1.15	1.34
-15 (+ 5)	936	236	274	180	1.35	3.59	5.19	1.31	1.52
-10 (+14)	1178	297	345	200	1.41	4.52	5.87	1.48	1.72

TEST CONDITIONS: @220V50Hz			<b>CECOMAF</b> Static		(Condensing temperature 65°C (+149°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	283	71	83	111	1.19	1.20	2.55	0.64	0.75
-30 (-22)	372	94	109	128	1.23	1.57	2.91	0.73	0.85
-25 (-13)	486	123	143	148	1.28	2.05	3.29	0.83	0.96
-20 (- 4)	627	158	184	170	1.33	2.66	3.69	0.93	1.08
-15 (+ 5)	797	201	234	194	1.39	3.39	4.11	1.03	1.20
-10 (+14)	999	252	293	220	1.47	4.26	4.54	1.15	1.33

### F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal EG/F/AMEM version 2		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted		
3.3 PROCESS	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		