

### COMPRESSOR DEFINITION

Designation	EG US70HLP
Nominal Voltage/Frequency	115-127 V 60 Hz
Engineering Number	513701197

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	115-127 / 60	[ V / Hz ]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSIR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	-	98 to 140 V
8.2 LBP (43°C Ambient temperature)	Static	-	98 to 140 V
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	16.2	[kgf/cm <sup>2</sup> ] (230 psig)	/ °C - °F
9.2 Peak (gauge)	20.6	[kgf/cm <sup>2</sup> ] (293 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation	1/5+	[hp]
2 Displacement	5.56	[cm <sup>3</sup> ] (0.339 cu.in)
2.1 Bore [mm]	22.500	
2.2 Stroke [mm]	14.000	
3 Lubricant charge	280	[ml] (9.47 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO7	
4 Weight (with oil charge)	10.33	[kg] (22.77 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm <sup>2</sup> ] (2.84 to 4.27 psig)

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	115-127 V 60 Hz 1 ~ (Single phase)	
2 Starting device type	Combo	
2.1 Starting device	3ARR5XM4BY	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	3ARR5XM4B	
6 Start winding resistance	9.14	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	4.17	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	-	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	UL	

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @115V60Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
684	172	200	125	1.57	3.89	5.45	1.37	1.60

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 45°C (+113°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	335	85	98	80	1.01	1.90	4.20	1.06	1.23
-30 (-22)	497	125	146	98	1.23	2.82	5.02	1.27	1.47
-25 (-13)	700	176	205	118	1.48	3.97	5.90	1.49	1.73
-20 (- 4)	938	236	275	138	1.73	5.34	6.82	1.72	2.00
-15 (+ 5)	1207	304	354	156	1.97	6.89	7.79	1.96	2.28
-10 (+14)	1501	378	440	172	2.19	8.60	8.79	2.21	2.58

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 55°C (+131°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	286	72	84	71	0.92	1.62	4.05	1.02	1.19
-30 (-22)	426	107	125	92	1.17	2.42	4.66	1.17	1.37
-25 (-13)	616	155	180	115	1.46	3.50	5.32	1.34	1.56
-20 (- 4)	848	214	249	140	1.77	4.83	6.03	1.52	1.77
-15 (+ 5)	1119	282	328	165	2.09	6.39	6.78	1.71	1.99
-10 (+14)	1422	358	417	188	2.40	8.15	7.56	1.91	2.22

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 65°C (+149°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	224	56	66	64	0.83	1.27	3.52	0.89	1.03
-30 (-22)	340	86	100	86	1.09	1.93	4.05	1.02	1.19
-25 (-13)	512	129	150	111	1.41	2.91	4.62	1.16	1.35
-20 (- 4)	735	185	215	140	1.77	4.18	5.24	1.32	1.53
-15 (+ 5)	1004	253	294	169	2.16	5.73	5.90	1.49	1.73
-10 (+14)	1313	331	385	199	2.55	7.52	6.59	1.66	1.93

### F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal EG/F/AMEM version 2		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.2 +0.12/-0.08	[mm]	(0.323" +0.005"/-0.003")
3.1.1 Material	Copper		
3.1.2 Shape	Straight		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.3.1 Material	Copper		
3.3.2 Shape	Straight		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		