

COMPRESSOR DEFINITION

| | |
|---------------------------|--------------------|
| Designation | EG US70HLP |
| Nominal Voltage/Frequency | 220-240 V 50-60 Hz |
| Engineering Number | 513701318 |

A - APPLICATION / LIMIT WORKING CONDITIONS

| | | | |
|------------------------------------|-----------------------------------|-----------------------------------|--------------|
| 1 Type | Hermetic reciprocating compressor | | |
| 2 Refrigerant | R-134a | | |
| 3 Nominal voltage and frequency | 220-240 / 50-60 | [V / Hz] | |
| 4 Application type | Low Back Pressure | | |
| 4.1 Evaporating temperature range | -35°C to -10°C | (-31°F to 14°F) | |
| 5 Motor type | RSIR | | |
| 6 Starting torque | LST - Low Starting Torque | | |
| 7 Expansion device | Capillary tube | | |
| 8 Compressor cooling | Operating voltage range | | |
| | | 50 Hz | 60 Hz |
| 8.1 LBP (32°C Ambient temperature) | Static | 198 to 255 V | 198 to 255 V |
| 8.2 LBP (43°C Ambient temperature) | Static | 198 to 255 V | 198 to 255 V |
| 8.3 HBP (32°C Ambient temperature) | - | - | - |
| 8.4 HBP (43°C Ambient temperature) | - | - | - |
| 9 Maximum condensing temperature | | | |
| 9.1 Operating | 14.2 | [kgf/cm ²] (202 psig) | / °C - °F |
| 9.2 Peak | 15.9 | [kgf/cm ²] (226 psig) | / °C - °F |
| 10 Maximum winding temperature | 130 | [°C] | |

B - MECHANICAL DATA

| | | |
|-------------------------------|---------------|--------------------------------------------|
| 1 Commercial designation | 1/5+ | [hp] |
| 2 Displacement | 5.56 | [cm ³] (0.339 cu.in) |
| 2.1 Bore [mm] | 22.500 | |
| 2.2 Stroke [mm] | 14.000 | |
| 3 Lubricant charge | 230 | [ml] (7.78 fl.oz) |
| 3.1 Lubricants approved | | |
| 3.2 Lubricants type/viscosity | ESTER / ISO10 | |
| 4 Weight (with oil charge) | 10.43 | [kg] (22.99 lb.) |
| 5 Nitrogen charge | 0.2 to 0.3 | [kgf/cm ²] (2.84 to 4.27 psig) |

C - ELETRICAL DATA

| | | |
|----------------------------------------------|---------------------------------------|------------------------------------|
| 1 Nominal Voltage/Frequency/Number of Phases | 220-240 V 50-60 Hz 1 ~ (Single phase) | |
| 2 Starting device type | Combo | |
| 2.1 Starting device | MSC34X 220V | |
| 3 Start capacitor | - | [µF(VAC minimum)] |
| 4 Run capacitor | - | [µF(VAC minimum)] |
| 5 Motor protection | MSC34A49H3 | |
| 6 Start winding resistance | 25.60 | [Ω at 25°C (77°F)] +/- 8% |
| 7 Run winding resistance | 13.90 | [Ω at 25°C (77°F)] +/- 8% |
| 8 LRA - Locked rotor amperage (50/60 Hz) | 7.80/7.20 | [A] - Measured according to UL 984 |
| 9 FLA - Full load amperage L/MBP (50/60 Hz) | 1.40/1.25 | [A] - Measured according to UL 984 |
| 10 FLA - Full Load Amperage HBP (50/60 Hz) | 1.60/1.45 | [A] - Measured according to UL 984 |
| 11 Approval boards certification | CE - TUV - UKCA | |

D - PERFORMANCE - CHECK POINT DATA

| | | | | | | | | |
|-------------------------------|----------|-----|--------------------------------|----------------------------------|----------------------------------------------------|---------------------------|----------------------------------------|-------|
| TEST CONDITIONS: @220V50Hz | | | ASHRAELBP32 Static | | Evaporating temperature (Condensing temperature | | -23.3°C (-9.94°F) 54.4°C (129.92°F) | |
| Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| 560 | 141 | 164 | 105 | 0.87 | 3.18 | 5.35 | 1.35 | 1.57 |

| | | | | | | | | |
|-------------------------------|----------|-----|--------------------------------|----------------------------------|----------------------------------------------------|---------------------------|----------------------------------------|-------|
| TEST CONDITIONS: @220V60Hz | | | ASHRAELBP32 Static | | Evaporating temperature (Condensing temperature | | -23.3°C (-9.94°F) 54.4°C (129.92°F) | |
| Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| 695 | 175 | 204 | 124 | 0.81 | 3.95 | 5.60 | 1.41 | 1.64 |

E - PERFORMANCE - CURVES

| | | | | | | | | | |
|-------------------------------|----------------------------|----------|--------------------|--------------------------------|----------------------------------------|----------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS: @220V50Hz | | | ASHRAE32 Static | | (Condensing temperature 45°C (+113°F)) | | | | |
| Evaporating temperature | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 (-31) | 270 | 68 | 79 | 68 | 0.56 | 1.53 | 3.99 | 1.01 | 1.17 |
| -30 (-22) | 400 | 101 | 117 | 83 | 0.68 | 2.27 | 4.78 | 1.20 | 1.40 |
| -25 (-13) | 563 | 142 | 165 | 100 | 0.81 | 3.20 | 5.62 | 1.42 | 1.65 |
| -20 (- 4) | 756 | 190 | 221 | 116 | 0.96 | 4.30 | 6.50 | 1.64 | 1.90 |
| -15 (+ 5) | 972 | 245 | 285 | 132 | 1.09 | 5.55 | 7.42 | 1.87 | 2.17 |
| -10 (+14) | 1209 | 305 | 354 | 145 | 1.21 | 6.93 | 8.38 | 2.11 | 2.45 |

| | | | | | | | | | |
|-------------------------------|----------------------------|----------|--------------------|--------------------------------|----------------------------------------|----------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS: @220V50Hz | | | ASHRAE32 Static | | (Condensing temperature 55°C (+131°F)) | | | | |
| Evaporating temperature | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 (-31) | 230 | 58 | 67 | 60 | 0.51 | 1.30 | 3.86 | 0.97 | 1.13 |
| -30 (-22) | 343 | 86 | 101 | 78 | 0.64 | 1.94 | 4.44 | 1.12 | 1.30 |
| -25 (-13) | 496 | 125 | 145 | 98 | 0.80 | 2.81 | 5.07 | 1.28 | 1.48 |
| -20 (- 4) | 683 | 172 | 200 | 119 | 0.98 | 3.89 | 5.74 | 1.45 | 1.68 |
| -15 (+ 5) | 901 | 227 | 264 | 140 | 1.16 | 5.14 | 6.46 | 1.63 | 1.89 |
| -10 (+14) | 1146 | 289 | 336 | 159 | 1.33 | 6.56 | 7.20 | 1.82 | 2.11 |

E - PERFORMANCE - CURVES

| TEST CONDITIONS: @220V50Hz | | ASHRAE32 Static | | | (Condensing temperature 65°C (+149°F)) | | | | | |
|-------------------------------|----------------------------|--------------------|---------|-----------------------------|----------------------------------------|-------------------------|---------------------------|------|------|------|
| Evaporating temperature | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | | |
| | °C | (°F) | [Btu/h] | | | | [kcal/h] | [W] | [W] | [A] |
| -35 | (-31) | 181 | 46 | 53 | 54 | 0.46 | 1.02 | 3.36 | 0.85 | 0.98 |
| -30 | (-22) | 274 | 69 | 80 | 72 | 0.60 | 1.55 | 3.85 | 0.97 | 1.13 |
| -25 | (-13) | 412 | 104 | 121 | 94 | 0.78 | 2.34 | 4.40 | 1.11 | 1.29 |
| -20 | (- 4) | 592 | 149 | 173 | 118 | 0.98 | 3.37 | 4.99 | 1.26 | 1.46 |
| -15 | (+ 5) | 808 | 204 | 237 | 143 | 1.20 | 4.62 | 5.62 | 1.42 | 1.65 |
| -10 | (+14) | 1058 | 266 | 310 | 168 | 1.41 | 6.06 | 6.28 | 1.58 | 1.84 |

| TEST CONDITIONS: @220V60Hz | | ASHRAE32 Static | | | (Condensing temperature 45°C (+113°F)) | | | | | |
|-------------------------------|----------------------------|--------------------|---------|-----------------------------|----------------------------------------|-------------------------|---------------------------|------|------|------|
| Evaporating temperature | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | | |
| | °C | (°F) | [Btu/h] | | | | [kcal/h] | [W] | [W] | [A] |
| -35 | (-31) | 335 | 85 | 98 | 80 | 0.52 | 1.90 | 4.19 | 1.06 | 1.23 |
| -30 | (-22) | 497 | 125 | 146 | 99 | 0.64 | 2.82 | 5.01 | 1.26 | 1.47 |
| -25 | (-13) | 700 | 176 | 205 | 118 | 0.77 | 3.97 | 5.88 | 1.48 | 1.72 |
| -20 | (- 4) | 938 | 236 | 275 | 138 | 0.89 | 5.34 | 6.81 | 1.71 | 1.99 |
| -15 | (+ 5) | 1207 | 304 | 354 | 156 | 1.01 | 6.89 | 7.77 | 1.96 | 2.28 |
| -10 | (+14) | 1501 | 378 | 440 | 172 | 1.12 | 8.60 | 8.77 | 2.21 | 2.57 |

| TEST CONDITIONS: @220V60Hz | | ASHRAE32 Static | | | (Condensing temperature 55°C (+131°F)) | | | | | |
|-------------------------------|----------------------------|--------------------|---------|-----------------------------|----------------------------------------|-------------------------|---------------------------|------|------|------|
| Evaporating temperature | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | | |
| | °C | (°F) | [Btu/h] | | | | [kcal/h] | [W] | [W] | [A] |
| -35 | (-31) | 286 | 72 | 84 | 71 | 0.47 | 1.62 | 4.04 | 1.02 | 1.18 |
| -30 | (-22) | 426 | 107 | 125 | 92 | 0.60 | 2.42 | 4.65 | 1.17 | 1.36 |
| -25 | (-13) | 616 | 155 | 180 | 116 | 0.75 | 3.50 | 5.31 | 1.34 | 1.56 |
| -20 | (- 4) | 848 | 214 | 249 | 140 | 0.91 | 4.83 | 6.02 | 1.52 | 1.76 |
| -15 | (+ 5) | 1119 | 282 | 328 | 165 | 1.08 | 6.39 | 6.76 | 1.70 | 1.98 |
| -10 | (+14) | 1422 | 358 | 417 | 189 | 1.24 | 8.15 | 7.55 | 1.90 | 2.21 |

| TEST CONDITIONS: @220V60Hz | | ASHRAE32 Static | | | (Condensing temperature 65°C (+149°F)) | | | | | |
|-------------------------------|----------------------------|--------------------|---------|-----------------------------|----------------------------------------|-------------------------|---------------------------|------|------|------|
| Evaporating temperature | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | | |
| | °C | (°F) | [Btu/h] | | | | [kcal/h] | [W] | [W] | [A] |
| -35 | (-31) | 224 | 56 | 66 | 64 | 0.43 | 1.27 | 3.51 | 0.88 | 1.03 |
| -30 | (-22) | 340 | 86 | 100 | 86 | 0.57 | 1.93 | 4.03 | 1.02 | 1.18 |
| -25 | (-13) | 512 | 129 | 150 | 112 | 0.73 | 2.91 | 4.61 | 1.16 | 1.35 |
| -20 | (- 4) | 735 | 185 | 215 | 140 | 0.91 | 4.18 | 5.22 | 1.32 | 1.53 |
| -15 | (+ 5) | 1004 | 253 | 294 | 170 | 1.11 | 5.73 | 5.88 | 1.48 | 1.72 |
| -10 | (+14) | 1313 | 331 | 385 | 199 | 1.31 | 7.52 | 6.58 | 1.66 | 1.93 |

F - EXTERNAL CHARACTERISTICS

| | | | |
|-------------------------|-------------------|------|--------------------------|
| 1 Base plate | European Standard | | |
| 2 Tray holder | No | | |
| 3 Connectors | | | |
| 3.1 SUCTION | 6.1 +0.10/+0.00 | [mm] | (0.240" +0.004"/+0.000") |
| 3.1.1 Material | Copper | | |
| 3.1.2 Shape | Slanted | | |
| 3.2 DISCHARGE | 4.94 +0.08/-0.08 | [mm] | (0.194" +0.003"/-0.003") |
| 3.2.1 Material | Copper | | |
| 3.2.2 Shape | Slanted | | |
| 3.3 PROCESS | 6.1 +0.10/+0.00 | [mm] | (0.240" +0.004"/+0.000") |
| 3.3.1 Material | Copper | | |
| 3.3.2 Shape | Slanted | | |
| 3.4 Oil cooler (Copper) | No | [mm] | |
| 3.5 Connector sealing | Rubber Plugs | | |