

COMPRESSOR DEFINITION

| | |
|---------------------------|-----------------|
| Designation | EM Y26CLC |
| Nominal Voltage/Frequency | 220-240 V 50 Hz |
| Engineering Number | 897BA81 |

A - APPLICATION / LIMIT WORKING CONDITIONS

| | | | |
|------------------------------------|-----------------------------------|-----------------------------------|-----------|
| 1 Type | Hermetic reciprocating compressor | | |
| 2 Refrigerant | R-600a | | |
| 3 Nominal voltage and frequency | 220-240 / 50 | [V / Hz] | |
| 4 Application type | Low Back Pressure | | |
| 4.1 Evaporating temperature range | -35°C to -10°C | (-31°F to 14°F) | |
| 5 Motor type | RSIR | | |
| 6 Starting torque | LST - Low Starting Torque | | |
| 7 Expansion device | Capillary tube | | |
| 8 Compressor cooling | Operating voltage range | | |
| | | 50 Hz | 60 Hz |
| 8.1 LBP (32°C Ambient temperature) | Static | 198 to 254 V | - |
| 8.2 LBP (43°C Ambient temperature) | Static | 198 to 254 V | - |
| 8.3 HBP (32°C Ambient temperature) | - | - | - |
| 8.4 HBP (43°C Ambient temperature) | - | - | - |
| 9 Maximum condensing temperature | | | |
| 9.1 Operating | 6.9 | [kgf/cm ²] (98 psig) | / °C - °F |
| 9.2 Peak | 7.8 | [kgf/cm ²] (111 psig) | / °C - °F |
| 10 Maximum winding temperature | 130 | [°C] | |

B - MECHANICAL DATA

| | | |
|-------------------------------|----------------|----------------------------------|
| 1 Commercial designation | | [hp] |
| 2 Displacement | 5.19 | [cm ³] (0.317 cu.in) |
| 2.1 Bore [mm] | 21.000 | |
| 2.2 Stroke [mm] | 15.000 | |
| 3 Lubricant charge | 180 | [ml] (6.09 fl.oz.) |
| 3.1 Lubricants approved | | |
| 3.2 Lubricants type/viscosity | ALQUILB / ISO5 | |
| 4 Weight (with oil charge) | 7.7 | [kg] (16.98 lb.) |
| 5 Nitrogen charge | - | [kgf/cm ²] |

C - ELETRICAL DATA

| | | |
|--|------------------------------------|------------------------------------|
| 1 Nominal Voltage/Frequency/Number of Phases | 220-240 V 50 Hz 1 ~ (Single phase) | |
| 2 Starting device type | PTC | |
| 2.1 Starting device | V230 | |
| 3 Start capacitor | - | [μF(VAC minimum)] |
| 4 Run capacitor | - | [μF(VAC minimum)] |
| 5 Motor protection | T0882/07 | |
| 6 Start winding resistance | 27.30 | [Ω at 25°C (77°F)] +/- 8% |
| 7 Run winding resistance | 38.00 | [Ω at 25°C (77°F)] +/- 8% |
| 8 LRA - Locked rotor amperage (50 Hz) | 2.70 | [A] - Measured according to UL 984 |
| 9 FLA - Full load amperage L/MBP (50 Hz) | 0.35 | [A] |
| 10 FLA - Full Load Amperage HBP (50 Hz) | - | [A] |
| 11 Approval boards certification | VDE | |

D - PERFORMANCE - CHECK POINT DATA

| | | | | | | | | |
|-------------------------------|----------|-----|-----------------------------|-------------------------------|--|---------------------------|--|-------|
| TEST CONDITIONS: @220V50Hz | | | ASHRAELBP32 Static | | Evaporating temperature (Condensing temperature | | -23.3°C (-9.94°F) 54.4°C (129.92°F) | |
| Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| 280 | 71 | 82 | 55 | 0.36 | 0.88 | 5.10 | 1.29 | 1.49 |

E - PERFORMANCE - CURVES

| | | | | | | | | | |
|-------------------------------|----------------------------|----------|--------------------|-----------------------------|---------------------------------------|-------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS: @220V50Hz | | | ASHRAE32 Static | | (Condensing temperature 35°C (+95°F)) | | | | |
| Evaporating temperature | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 (-31) | 168 | 42 | 49 | 38 | 0.30 | 0.53 | 4.41 | 1.11 | 1.29 |
| -30 (-22) | 227 | 57 | 66 | 43 | 0.32 | 0.71 | 5.25 | 1.32 | 1.54 |
| -25 (-13) | 298 | 75 | 87 | 49 | 0.33 | 0.94 | 6.14 | 1.55 | 1.80 |
| -20 (- 4) | 385 | 97 | 113 | 54 | 0.35 | 1.21 | 7.12 | 1.79 | 2.09 |
| -15 (+ 5) | 488 | 123 | 143 | 59 | 0.37 | 1.54 | 8.23 | 2.07 | 2.41 |
| -10 (+14) | 611 | 154 | 179 | 64 | 0.38 | 1.93 | 9.50 | 2.40 | 2.79 |

| | | | | | | | | | |
|-------------------------------|----------------------------|----------|--------------------|-----------------------------|--|-------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS: @220V50Hz | | | ASHRAE32 Static | | (Condensing temperature 45°C (+113°F)) | | | | |
| Evaporating temperature | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 (-31) | 144 | 36 | 42 | 38 | 0.30 | 0.45 | 3.76 | 0.95 | 1.10 |
| -30 (-22) | 204 | 52 | 60 | 45 | 0.32 | 0.64 | 4.59 | 1.16 | 1.35 |
| -25 (-13) | 277 | 70 | 81 | 51 | 0.34 | 0.87 | 5.40 | 1.36 | 1.58 |
| -20 (- 4) | 362 | 91 | 106 | 58 | 0.36 | 1.14 | 6.24 | 1.57 | 1.83 |
| -15 (+ 5) | 464 | 117 | 136 | 65 | 0.39 | 1.46 | 7.13 | 1.80 | 2.09 |
| -10 (+14) | 583 | 147 | 171 | 72 | 0.41 | 1.84 | 8.13 | 2.05 | 2.38 |

| | | | | | | | | | |
|-------------------------------|----------------------------|----------|--------------------|-----------------------------|--|-------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS: @220V50Hz | | | ASHRAE32 Static | | (Condensing temperature 55°C (+131°F)) | | | | |
| Evaporating temperature | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 (-31) | 114 | 29 | 34 | 37 | 0.30 | 0.36 | 3.13 | 0.79 | 0.92 |
| -30 (-22) | 178 | 45 | 52 | 44 | 0.32 | 0.56 | 4.03 | 1.02 | 1.18 |
| -25 (-13) | 251 | 63 | 73 | 52 | 0.35 | 0.79 | 4.84 | 1.22 | 1.42 |
| -20 (- 4) | 336 | 85 | 98 | 60 | 0.37 | 1.06 | 5.59 | 1.41 | 1.64 |
| -15 (+ 5) | 436 | 110 | 128 | 69 | 0.40 | 1.37 | 6.34 | 1.60 | 1.86 |
| -10 (+14) | 552 | 139 | 162 | 77 | 0.44 | 1.74 | 7.12 | 1.80 | 2.09 |

E - PERFORMANCE - CURVES

| TEST CONDITIONS: @220V50Hz | | ASHRAE32 Static | | | (Condensing temperature 65°C (+149°F)) | | | | | |
|-------------------------------|-------|----------------------------|----------|-----|--|-------------------------------|-------------------------|---------------------------|-----------|-------|
| Evaporating temperature | | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C | (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 | (-31) | 78 | 20 | 23 | 34 | 0.29 | 0.24 | 2.27 | 0.57 | 0.66 |
| -30 | (-22) | 144 | 36 | 42 | 43 | 0.32 | 0.45 | 3.30 | 0.83 | 0.97 |
| -25 | (-13) | 218 | 55 | 64 | 52 | 0.35 | 0.69 | 4.17 | 1.05 | 1.22 |
| -20 | (- 4) | 304 | 77 | 89 | 62 | 0.38 | 0.96 | 4.92 | 1.24 | 1.44 |
| -15 | (+ 5) | 402 | 101 | 118 | 72 | 0.41 | 1.27 | 5.59 | 1.41 | 1.64 |
| -10 | (+14) | 516 | 130 | 151 | 83 | 0.45 | 1.63 | 6.23 | 1.57 | 1.83 |

F - EXTERNAL CHARACTERISTICS

| | | | |
|-------------------------|-------------------|------|--------------------------|
| 1 Base plate | European Standard | | |
| 2 Tray holder | Yes | | |
| 3 Connectors | | | |
| 3.1 SUCTION | 6.1 +0.10/+0.00 | [mm] | (0.240" +0.004"/+0.000") |
| 3.1.1 Material | Copper | | |
| 3.1.2 Shape | Slanted 42° | | |
| 3.2 DISCHARGE | 5.1 +0.10/+0.00 | [mm] | (0.201" +0.004"/+0.000") |
| 3.2.1 Material | Copper | | |
| 3.2.2 Shape | Straight | | |
| 3.3 PROCESS | 6 +0.08/-0.08 | [mm] | (0.236" +0.003"/-0.003") |
| 3.3.1 Material | Copper(OD) | | |
| 3.3.2 Shape | Slanted 42° | | |
| 3.4 Oil cooler (Copper) | No | [mm] | |
| 3.5 Connector sealing | Rubber Plugs | | |