

### COMPRESSOR DEFINITION

Designation	EM T6170Z
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	513300160

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	220-240 / 50	[ V / Hz ]	
4 Application type	High Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-15°C to 10°C	(5°F to 50°F)	
5 Motor type	CSIR		
6 Starting torque	HST - High starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	16.2	[kgf/cm <sup>2</sup> ] (230 psig)	/ °C - °F
9.2 Peak (gauge)	20.6	[kgf/cm <sup>2</sup> ] (293 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation	1/2	[hp]
2 Displacement	7.96	[cm <sup>3</sup> ] (0.486 cu.in)
2.1 Bore [mm]	24.000	
2.2 Stroke [mm]	17.600	
3 Lubricant charge	180	[ml] (6.09 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	8.1	[kg] (17.86 lb.)
5 Nitrogen charge	-	[kgf/cm <sup>2</sup> ]

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	Current Relay	
2.1 Starting device	213515005/MTRP-38	
3 Start capacitor	53-64(350)	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	MRA58169	
6 Start winding resistance	18.40	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	10.90	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	11.20	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	2.64	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	3.96	[A] - Measured according to UL 984
11 Approval boards certification	CCC - VDE	

### D - PERFORMANCE - CHECK POINT DATA

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		ASHRAE46 Fan			(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+ 5)	1217	307	357	214	1.50	7.11	5.69	1.43	1.67
-10	(+14)	1541	388	451	239	1.57	9.03	6.45	1.62	1.89
-5	(+23)	1910	481	560	267	1.65	11.24	7.16	1.81	2.10
0	(+32)	2332	588	683	297	1.76	13.80	7.85	1.98	2.30
+5	(+41)	2816	710	825	331	1.89	16.76	8.51	2.14	2.49
+10	(+50)	3370	849	988	368	2.04	20.20	9.15	2.31	2.68

TEST CONDITIONS: @220V50Hz		ASHRAE46 Fan			(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+ 5)	1075	271	315	228	1.54	6.85	4.71	1.19	1.38
-10	(+14)	1362	343	399	257	1.63	8.71	5.31	1.34	1.56
-5	(+23)	1691	426	496	288	1.73	10.86	5.88	1.48	1.72
0	(+32)	2069	521	606	323	1.86	13.36	6.41	1.62	1.88
+5	(+41)	2503	631	734	362	2.01	16.28	6.92	1.74	2.03
+10	(+50)	3003	757	880	406	2.19	19.66	7.41	1.87	2.17

### F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard EUEM		
2 Tray holder	Yes		
3 Connectors			
3.1 SUCTION	6.2 +0.05/+0.05	[mm]	(0.244" +0.002"/+0.002")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 40° up + 45° to Back		
3.2 DISCHARGE	4.9 +0.10/-0.05	[mm]	(0.193" +0.004"/-0.002")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted 0° up + 24° to Back		
3.3 PROCESS	6.2 +0.05/+0.05	[mm]	(0.244" +0.002"/+0.002")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 40° up + 45° to Back		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		