

COMPRESSOR DEFINITION

| | |
|---------------------------|---------------------------|
| Designation | F GS90HA |
| Nominal Voltage/Frequency | 220-240 V 50-60 Hz |
| Engineering Number | 513208391 |

A - APPLICATION / LIMIT WORKING CONDITIONS

| | | | |
|--|-----------------------------------|-----------------------------------|-----------|
| 1 Type | Hermetic reciprocating compressor | | |
| 2 Refrigerant | R-134a | | |
| 3 Nominal voltage and frequency | 220-240 / 50-60 | [V / Hz] | |
| 4 Application type | Low Back Pressure | | |
| 4.1 Evaporating temperature range | -35°C to -10°C | (-31°F to 14°F) | |
| 5 Motor type | RSIR | | |
| 6 Starting torque | LST - Low Starting Torque | | |
| 7 Expansion device | Capillary tube | | |
| 8 Compressor cooling | | Operating voltage range | |
| | | 50 Hz | 60 Hz |
| 8.1 LBP (32°C Ambient temperature) | Static | 198 to 255 V | - |
| 8.2 LBP (43°C Ambient temperature) | Static | 198 to 255 V | - |
| 8.3 HBP (32°C Ambient temperature) | - | - | - |
| 8.4 HBP (43°C Ambient temperature) | - | - | - |
| 9 Maximum condensing pressures/temperature | | | |
| 9.1 Operating (gauge) | 16.2 | [kgf/cm ²] (230 psig) | / °C - °F |
| 9.2 Peak (gauge) | 20.6 | [kgf/cm ²] (293 psig) | / °C - °F |
| 10 Maximum winding temperature | 130 | [°C] | |

B - MECHANICAL DATA

| | | |
|-------------------------------|---------------|--|
| 1 Commercial designation | 1/4+ | [hp] |
| 2 Displacement | 7.95 | [cm ³] (0.485 cu.in) |
| 2.1 Bore [mm] | 22.500 | |
| 2.2 Stroke [mm] | 20.000 | |
| 3 Lubricant charge | 280 | [ml] (9.47 fl.oz.) |
| 3.1 Lubricants approved | | |
| 3.2 Lubricants type/viscosity | ESTER / ISO22 | |
| 4 Weight (with oil charge) | 11.2 | [kg] (24.69 lb.) |
| 5 Nitrogen charge | 0.2 to 0.3 | [kgf/cm ²] (2.84 to 4.27 psig) |

C - ELETRICAL DATA

| | | |
|--|---------------------------------------|------------------------------------|
| 1 Nominal Voltage/Frequency/Number of Phases | 220-240 V 50-60 Hz 1 ~ (Single phase) | |
| 2 Starting device type | PTC | |
| 2.1 Starting device | 7M220MC1/8EA17C1/8EA5B1 | |
| 3 Start capacitor | - | [µF(VAC minimum)] |
| 4 Run capacitor | - | [µF(VAC minimum)] |
| 5 Motor protection | 4TM283KFBYY-53 | |
| 6 Start winding resistance | 14.60 | [Ω at 25°C (77°F)] +/- 8% |
| 7 Run winding resistance | 9.70 | [Ω at 25°C (77°F)] +/- 8% |
| 8 LRA - Locked rotor amperage (50 Hz) | - | [A] - Measured according to UL 984 |
| 9 FLA - Full load amperage L/MBP (50 Hz) | - | [A] - Measured according to UL 984 |
| 10 FLA - Full Load Amperage HBP (50 Hz) | - | [A] - Measured according to UL 984 |
| 11 Approval boards certification | CCC - IRAM - UL | |

D - PERFORMANCE - CHECK POINT DATA

| | | | | | | | | |
|-------------------------------|----------|-----|--------------------------------|----------------------------------|--|---------------------------|--|-------|
| TEST CONDITIONS: @220V50Hz | | | ASHRAELBP32 Static | | Evaporating temperature (Condensing temperature | | -23.3°C (-9.94°F) 54.4°C (129.92°F) | |
| Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| 800 | 202 | 234 | 165 | 1.08 | 4.55 | 4.85 | 1.22 | 1.42 |

E - PERFORMANCE - CURVES

| | | | | | | | | | |
|-------------------------------|----------------------------|----------|--------------------|--------------------------------|--|----------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS: @220V50Hz | | | ASHRAE32 Static | | (Condensing temperature 45°C (+113°F)) | | | | |
| Evaporating temperature | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 (-31) | 421 | 106 | 123 | 111 | 0.93 | 2.38 | 3.79 | 0.96 | 1.11 |
| -30 (-22) | 581 | 146 | 170 | 131 | 0.98 | 3.29 | 4.46 | 1.12 | 1.31 |
| -25 (-13) | 774 | 195 | 227 | 150 | 1.04 | 4.39 | 5.17 | 1.30 | 1.52 |
| -20 (- 4) | 1010 | 255 | 296 | 170 | 1.11 | 5.75 | 5.94 | 1.50 | 1.74 |
| -15 (+ 5) | 1297 | 327 | 380 | 191 | 1.18 | 7.40 | 6.78 | 1.71 | 1.99 |
| -10 (+14) | 1643 | 414 | 481 | 212 | 1.26 | 9.41 | 7.72 | 1.94 | 2.26 |

| | | | | | | | | | |
|-------------------------------|----------------------------|----------|--------------------|--------------------------------|--|----------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS: @220V50Hz | | | ASHRAE32 Static | | (Condensing temperature 55°C (+131°F)) | | | | |
| Evaporating temperature | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 (-31) | 369 | 93 | 108 | 108 | 0.92 | 2.09 | 3.42 | 0.86 | 1.00 |
| -30 (-22) | 531 | 134 | 156 | 131 | 0.98 | 3.01 | 4.06 | 1.02 | 1.19 |
| -25 (-13) | 721 | 182 | 211 | 154 | 1.05 | 4.10 | 4.69 | 1.18 | 1.37 |
| -20 (- 4) | 950 | 239 | 278 | 178 | 1.13 | 5.40 | 5.33 | 1.34 | 1.56 |
| -15 (+ 5) | 1224 | 308 | 359 | 204 | 1.22 | 6.98 | 6.00 | 1.51 | 1.76 |
| -10 (+14) | 1552 | 391 | 455 | 230 | 1.32 | 8.89 | 6.73 | 1.69 | 1.97 |

| | | | | | | | | | |
|-------------------------------|----------------------------|----------|--------------------|--------------------------------|--|----------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS: @220V50Hz | | | ASHRAE32 Static | | (Condensing temperature 65°C (+149°F)) | | | | |
| Evaporating temperature | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 (-31) | 305 | 77 | 89 | 105 | 0.91 | 1.73 | 2.91 | 0.73 | 0.85 |
| -30 (-22) | 472 | 119 | 138 | 130 | 0.98 | 2.67 | 3.59 | 0.91 | 1.05 |
| -25 (-13) | 662 | 167 | 194 | 157 | 1.06 | 3.76 | 4.22 | 1.06 | 1.24 |
| -20 (- 4) | 886 | 223 | 259 | 185 | 1.15 | 5.04 | 4.80 | 1.21 | 1.41 |
| -15 (+ 5) | 1150 | 290 | 337 | 214 | 1.26 | 6.56 | 5.38 | 1.35 | 1.58 |
| -10 (+14) | 1463 | 369 | 429 | 246 | 1.38 | 8.38 | 5.95 | 1.50 | 1.74 |

F - EXTERNAL CHARACTERISTICS

| | | | |
|-------------------------|-----------------|------|--------------------------|
| 1 Base plate | Universal | | |
| 2 Tray holder | No | | |
| 3 Connectors | | | |
| 3.1 SUCTION | 6.5 +0.12/-0.08 | [mm] | (0.256" +0.005"/-0.003") |
| 3.1.1 Material | Copper | | |
| 3.1.2 Shape | Straight | | |
| 3.2 DISCHARGE | 6.5 +0.12/-0.08 | [mm] | (0.256" +0.005"/-0.003") |
| 3.2.1 Material | Copper | | |
| 3.2.2 Shape | Straight | | |
| 3.3 PROCESS | 6.5 +0.12/-0.08 | [mm] | (0.256" +0.005"/-0.003") |
| 3.3.1 Material | Copper | | |
| 3.3.2 Shape | Straight | | |
| 3.4 Oil cooler (Copper) | No | [mm] | |
| 3.5 Connector sealing | Rubber Plugs | | |