

### COMPRESSOR DEFINITION

Designation	<b>F GS90HA</b>
Nominal Voltage/Frequency	<b>220-240 V 50-60 Hz</b>
Engineering Number	<b>513200208</b>

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	220-240 / 50-60	[ V / Hz ]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSIR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	198 to 255 V	-
8.2 LBP (43°C Ambient temperature)	Static	198 to 255 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	16.2	[kgf/cm <sup>2</sup> ] (230 psig)	/ °C - °F
9.2 Peak (gauge)	20.6	[kgf/cm <sup>2</sup> ] (293 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation	1/4+	[hp]
2 Displacement	7.95	[cm <sup>3</sup> ] (0.485 cu.in)
2.1 Bore [mm]	22.500	
2.2 Stroke [mm]	20.000	
3 Lubricant charge	350	[ml] (11.84 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	11.2	[kg] (24.69 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm <sup>2</sup> ] (2.84 to 4.27 psig)

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50-60 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	7M220MC1/8EA17C1/8EA5B1	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	4TM283NFBYY-53	
6 Start winding resistance	14.60	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	9.70	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	-	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	CCC	

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
800	202	234	165	1.08	4.55	4.85	1.22	1.42

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 45°C (+113°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	421	106	123	111	0.93	2.38	3.79	0.96	1.11
-30 (-22)	581	146	170	131	0.98	3.29	4.46	1.12	1.31
-25 (-13)	774	195	227	150	1.04	4.39	5.17	1.30	1.52
-20 (- 4)	1010	255	296	170	1.11	5.75	5.94	1.50	1.74
-15 (+ 5)	1297	327	380	191	1.18	7.40	6.78	1.71	1.99
-10 (+14)	1643	414	481	212	1.26	9.41	7.72	1.94	2.26

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 55°C (+131°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	369	93	108	108	0.92	2.09	3.42	0.86	1.00
-30 (-22)	531	134	156	131	0.98	3.01	4.06	1.02	1.19
-25 (-13)	721	182	211	154	1.05	4.10	4.69	1.18	1.37
-20 (- 4)	950	239	278	178	1.13	5.40	5.33	1.34	1.56
-15 (+ 5)	1224	308	359	204	1.22	6.98	6.00	1.51	1.76
-10 (+14)	1552	391	455	230	1.32	8.89	6.73	1.69	1.97

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 65°C (+149°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	305	77	89	105	0.91	1.73	2.91	0.73	0.85
-30 (-22)	472	119	138	130	0.98	2.67	3.59	0.91	1.05
-25 (-13)	662	167	194	157	1.06	3.76	4.22	1.06	1.24
-20 (- 4)	886	223	259	185	1.15	5.04	4.80	1.21	1.41
-15 (+ 5)	1150	290	337	214	1.26	6.56	5.38	1.35	1.58
-10 (+14)	1463	369	429	246	1.38	8.38	5.95	1.50	1.74

### F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal EG/F		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.1.1 Material	Copper		
3.1.2 Shape	Straight		
3.2 DISCHARGE	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.3.1 Material	Copper		
3.3.2 Shape	Straight		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		