

### COMPRESSOR DEFINITION

Designation	<b>F G65HAKW</b>
Nominal Voltage/Frequency	<b>220-240 V 50 Hz</b>
Engineering Number	<b>513200187</b>

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	220-240 / 50	[ V / Hz ]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSIR		
6 Starting torque	LST/HST - Low/High starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	198 to 255 V	-
8.2 LBP (43°C Ambient temperature)	Static	198 to 255 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	16.2	[kgf/cm <sup>2</sup> ] (230 psig)	/ °C - °F
9.2 Peak (gauge)	20.6	[kgf/cm <sup>2</sup> ] (293 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation	1/5	[hp]
2 Displacement	6.76	[cm <sup>3</sup> ] (0.413 cu.in)
2.1 Bore [mm]	22.500	
2.2 Stroke [mm]	17.000	
3 Lubricant charge	335	[ml] (11.33 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	10.5	[kg] (23.15 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm <sup>2</sup> ] (2.84 to 4.27 psig)

### C - ELECTRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	7M220MC1/8EA17C1/8EA5B1	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	4TM276RFBYY-53	
6 Start winding resistance	37.10	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	12.90	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	6.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	1.35	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	CCC - IRAM - VDE	

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)		
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
560	141	164	140	0.88	3.18	4.00	1.01	1.17	

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Fan		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)		
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
560	141	164	140	0.88	3.18	4.00	1.01	1.17	

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 45°C (+113°F))					
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
-35 (-31)	299	75	88	100	0.78	1.69	3.00	0.76	0.88	
-30 (-22)	418	105	123	115	0.81	2.37	3.64	0.92	1.07	
-25 (-13)	558	141	164	132	0.86	3.17	4.24	1.07	1.24	
-20 (- 4)	725	183	213	150	0.91	4.13	4.85	1.22	1.42	
-15 (+ 5)	927	234	272	168	0.98	5.29	5.50	1.39	1.61	
-10 (+14)	1170	295	343	187	1.06	6.70	6.22	1.57	1.82	

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 55°C (+131°F))					
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
-35 (-31)	250	63	73	96	0.76	1.41	2.61	0.66	0.76	
-30 (-22)	368	93	108	114	0.80	2.09	3.23	0.81	0.95	
-25 (-13)	505	127	148	133	0.86	2.87	3.79	0.96	1.11	
-20 (- 4)	667	168	195	154	0.92	3.79	4.32	1.09	1.27	
-15 (+ 5)	860	217	252	177	1.00	4.91	4.86	1.23	1.42	
-10 (+14)	1092	275	320	200	1.09	6.26	5.44	1.37	1.59	

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		ASHRAE32 Static			(Condensing temperature 65°C (+149°F) )					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	201	51	59	89	0.72	1.14	2.25	0.57	0.66
-30	(-22)	319	80	93	110	0.78	1.81	2.88	0.73	0.84
-25	(-13)	452	114	132	132	0.85	2.57	3.41	0.86	1.00
-20	(- 4)	608	153	178	157	0.94	3.46	3.88	0.98	1.14
-15	(+ 5)	793	200	232	184	1.04	4.53	4.33	1.09	1.27
-10	(+14)	1014	256	297	212	1.15	5.81	4.78	1.21	1.40

### F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal EG/F		
2 Tray holder	Yes		
3 Connectors			
3.1 SUCTION	8.2 +0.12/-0.08	[mm]	(0.323" +0.005"/-0.003")
3.1.1 Material	Copper plated steel		
3.1.2 Shape	Slanted		
3.2 DISCHARGE	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.2.1 Material	Copper plated steel		
3.2.2 Shape	Slanted		
3.3 PROCESS	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.3.1 Material	Copper plated steel		
3.3.2 Shape	Slanted		
3.4 Oil cooler (Copper)	6.5 +0.09/-0.09	[mm]	(0.256" +0.004"/-0.004")
3.5 Connector sealing	Rubber Plugs		