

COMPRESSOR DEFINITION

Designation	F G95HAKW
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	513200081

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	CSIR		
6 Starting torque	LST/HST - Low/High starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static/Fan	198 to 255 V	-
8.2 LBP (43°C Ambient temperature)	Static/Fan	198 to 255 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	14.2	[kgf/cm ²] (202 psig)	/ °C - °F
9.2 Peak	15.9	[kgf/cm ²] (226 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/3	[hp]
2 Displacement	10.61	[cm ³] (0.647 cu.in)
2.1 Bore [mm]	26.000	
2.2 Stroke [mm]	20.000	
3 Lubricant charge	280	[ml] (9.47 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	10.6	[kg] (23.37 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	Current Relay	
2.1 Starting device	213516256	
3 Start capacitor	64-77(250)	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	MRA58152-5590	
6 Start winding resistance	21.90	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	7.70	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	13.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	2.00	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	CE - IRAM - UKCA	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)		
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
880	222	258	215	1.54	5.00	4.09	1.03	1.20	

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Fan		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)		
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
880	222	258	215	1.54	5.00	4.09	1.03	1.20	

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 45°C (+113°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	471	119	138	155	1.38	2.66	3.03	0.76	0.89
-30 (-22)	638	161	187	176	1.43	3.62	3.65	0.92	1.07
-25 (-13)	853	215	250	200	1.49	4.84	4.30	1.08	1.26
-20 (- 4)	1123	283	329	225	1.56	6.39	4.99	1.26	1.46
-15 (+ 5)	1454	366	426	253	1.65	8.30	5.72	1.44	1.68
-10 (+14)	1853	467	543	284	1.75	10.62	6.51	1.64	1.91

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 55°C (+131°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	403	102	118	150	1.37	2.28	2.71	0.68	0.79
-30 (-22)	583	147	171	177	1.43	3.31	3.32	0.84	0.97
-25 (-13)	800	202	235	205	1.50	4.54	3.91	0.99	1.15
-20 (- 4)	1061	267	311	236	1.59	6.04	4.51	1.14	1.32
-15 (+ 5)	1372	346	402	269	1.70	7.83	5.10	1.29	1.50
-10 (+14)	1739	438	510	304	1.83	9.96	5.71	1.44	1.67

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		ASHRAE32 Static			(Condensing temperature 65°C (+149°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	302	76	88	137	1.35	1.71	2.21	0.56	0.65
-30	(-22)	492	124	144	169	1.41	2.79	2.87	0.72	0.84
-25	(-13)	708	178	207	202	1.49	4.02	3.47	0.87	1.02
-20	(- 4)	955	241	280	238	1.59	5.44	4.02	1.01	1.18
-15	(+ 5)	1242	313	364	275	1.72	7.09	4.53	1.14	1.33
-10	(+14)	1575	397	462	315	1.86	9.02	5.02	1.26	1.47

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal EG/F		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.1.1 Material	Copper plated steel		
3.1.2 Shape	Slanted		
3.2 DISCHARGE	5 +0.18/-0.06	[mm]	(0.197" +0.007"/-0.002")
3.2.1 Material	Copper plated steel		
3.2.2 Shape	Slanted		
3.3 PROCESS	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.3.1 Material	Copper plated steel		
3.3.2 Shape	Slanted		
3.4 Oil cooler (Copper)	5.1 +0.10/+0.00	[mm]	(0.201" +0.004"/+0.000")
3.5 Connector sealing	Rubber Plugs		