

COMPRESSOR DEFINITION

Designation	NB T1112Y
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	810BA47

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSIR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	198 to 254 V	-
8.2 LBP (43°C Ambient temperature)	Static	198 to 254 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	6.9	[kgf/cm ²] (98 psig)	/ °C - °F
9.2 Peak	7.8	[kgf/cm ²] (111 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation		[hp]
2 Displacement	8.77	[cm ³] (0.535 cu.in)
2.1 Bore [mm]	26.497	
2.2 Stroke [mm]	15.920	
3 Lubricant charge	350	[ml] (11.84 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	MINERAL / ISO10	
4 Weight (with oil charge)	10.17	[kg] (22.42 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	2019	
3 Start capacitor	-	[μF(VAC minimum)]
4 Run capacitor	-	[μF(VAC minimum)]
5 Motor protection	AD25FQ10	
6 Start winding resistance	24.50	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	15.50	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	4.50	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	0.59	[A]
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A]
11 Approval boards certification	VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
466	117	137	97	0.60	1.46	4.80	1.21	1.41

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 35°C (+95°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	282	71	83	68	0.57	0.88	4.16	1.05	1.22
-30 (-22)	372	94	109	76	0.55	1.17	4.90	1.23	1.44
-25 (-13)	487	123	143	86	0.55	1.53	5.69	1.43	1.67
-20 (- 4)	629	159	184	96	0.58	1.98	6.54	1.65	1.92
-15 (+ 5)	799	201	234	107	0.62	2.52	7.47	1.88	2.19
-10 (+14)	999	252	293	117	0.67	3.15	8.50	2.14	2.49

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 45°C (+113°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	251	63	74	69	0.70	0.79	3.64	0.92	1.07
-30 (-22)	344	87	101	79	0.67	1.08	4.35	1.10	1.27
-25 (-13)	460	116	135	91	0.66	1.44	5.06	1.27	1.48
-20 (- 4)	601	151	176	104	0.68	1.89	5.80	1.46	1.70
-15 (+ 5)	767	193	225	117	0.72	2.41	6.57	1.66	1.93
-10 (+14)	962	242	282	130	0.76	3.03	7.40	1.87	2.17

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 55°C (+131°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	207	52	61	67	0.61	0.65	3.14	0.79	0.92
-30 (-22)	303	76	89	79	0.59	0.95	3.85	0.97	1.13
-25 (-13)	419	106	123	92	0.60	1.31	4.53	1.14	1.33
-20 (- 4)	558	141	163	107	0.64	1.75	5.19	1.31	1.52
-15 (+ 5)	721	182	211	123	0.68	2.27	5.84	1.47	1.71
-10 (+14)	909	229	266	139	0.74	2.87	6.51	1.64	1.91

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		ASHRAE32 Static			(Condensing temperature 65°C (+149°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	169	43	50	64	0.52	0.53	2.64	0.66	0.77
-30	(-22)	267	67	78	78	0.54	0.84	3.39	0.85	0.99
-25	(-13)	383	97	112	94	0.58	1.20	4.06	1.02	1.19
-20	(- 4)	520	131	152	111	0.65	1.64	4.68	1.18	1.37
-15	(+ 5)	679	171	199	130	0.73	2.14	5.25	1.32	1.54
-10	(+14)	862	217	253	149	0.82	2.72	5.79	1.46	1.70

F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted parallel to Base Plate		
3.3 PROCESS	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		