

### COMPRESSOR DEFINITION

Designation	<b>NB T1116Y</b>
Nominal Voltage/Frequency	<b>220-240 V 50 Hz</b>
Engineering Number	<b>811EA68</b>

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	220-240 / 50	[ V / Hz ]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSIR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	198 to 254 V	-
8.2 LBP (43°C Ambient temperature)	Static	198 to 254 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	7.7	[kgf/cm <sup>2</sup> ] (109 psig)	/ °C - °F
9.2 Peak (gauge)	9.8	[kgf/cm <sup>2</sup> ] (139 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation		[hp]
2 Displacement	12.11	[cm <sup>3</sup> ] (0.739 cu.in)
2.1 Bore [mm]	27.775	
2.2 Stroke [mm]	20.000	
3 Lubricant charge	350	[ml] (11.84 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	MINERAL / ISO7	
4 Weight (with oil charge)	10.73	[kg] (23.66 lb.)
5 Nitrogen charge	-	[kgf/cm <sup>2</sup> ]

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	2019	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	AD55BU10	
6 Start winding resistance	21.30	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	12.10	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	6.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	0.88	[A]
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A]
11 Approval boards certification	VDE	

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			CECOMAFLBP Static		Evaporating temperature (Condensing temperature		-25°C (-13°F) 55°C (131°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
539	136	158	129	0.87	2.06	4.19	1.06	1.23

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		CECOMAF Static				(Condensing temperature 35°C (+95°F) )				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	415	105	122	93	0.77	1.33	4.48	1.13	1.31
-30	(-22)	543	137	159	105	0.80	1.74	5.21	1.31	1.53
-25	(-13)	698	176	205	117	0.84	2.24	5.98	1.51	1.75
-20	(- 4)	885	223	259	130	0.88	2.84	6.81	1.71	1.99
-15	(+ 5)	1109	280	325	144	0.92	3.57	7.69	1.94	2.25
-10	(+14)	1377	347	403	159	0.97	4.44	8.66	2.18	2.54

TEST CONDITIONS: @220V50Hz		CECOMAF Static				(Condensing temperature 45°C (+113°F) )				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	353	89	104	93	0.77	1.23	3.79	0.95	1.11
-30	(-22)	475	120	139	108	0.81	1.65	4.39	1.11	1.29
-25	(-13)	617	156	181	123	0.85	2.15	5.01	1.26	1.47
-20	(- 4)	787	198	231	139	0.90	2.75	5.65	1.42	1.66
-15	(+ 5)	989	249	290	156	0.96	3.45	6.33	1.60	1.85
-10	(+14)	1228	309	360	174	1.02	4.30	7.06	1.78	2.07

TEST CONDITIONS: @220V50Hz		CECOMAF Static				(Condensing temperature 55°C (+131°F) )				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	293	74	86	93	0.78	1.11	3.16	0.80	0.93
-30	(-22)	408	103	120	110	0.82	1.55	3.68	0.93	1.08
-25	(-13)	540	136	158	129	0.87	2.06	4.18	1.05	1.23
-20	(- 4)	693	175	203	148	0.93	2.65	4.69	1.18	1.37
-15	(+ 5)	872	220	256	168	1.00	3.34	5.20	1.31	1.52
-10	(+14)	1084	273	317	189	1.08	4.16	5.74	1.45	1.68

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		CECOMAF Static			(Condensing temperature 65°C (+149°F) )					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	226	57	66	91	0.78	0.95	2.50	0.63	0.73
-30	(-22)	336	85	98	112	0.82	1.41	2.97	0.75	0.87
-25	(-13)	457	115	134	134	0.88	1.93	3.40	0.86	1.00
-20	(- 4)	594	150	174	156	0.95	2.51	3.81	0.96	1.12
-15	(+ 5)	752	189	220	180	1.04	3.20	4.20	1.06	1.23
-10	(+14)	937	236	275	205	1.13	4.00	4.59	1.16	1.35

### F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted parallel B.Plate 30°		
3.3 PROCESS	6 +0.08/-0.08	[mm]	(0.236" +0.003"/-0.003")
3.3.1 Material	Copper(OD)		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		