

COMPRESSOR DEFINITION

| | |
|---------------------------|-----------------|
| Designation | NB T1116Y |
| Nominal Voltage/Frequency | 220-240 V 50 Hz |
| Engineering Number | 815EA68 |

A - APPLICATION / LIMIT WORKING CONDITIONS

| | | | |
|--|-----------------------------------|-----------------------------------|-----------|
| 1 Type | Hermetic reciprocating compressor | | |
| 2 Refrigerant | R-600a | | |
| 3 Nominal voltage and frequency | 220-240 / 50 | [V / Hz] | |
| 4 Application type | Low Back Pressure | | |
| 4.1 Evaporating temperature range | -35°C to -10°C | (-31°F to 14°F) | |
| 5 Motor type | RSIR | | |
| 6 Starting torque | LST - Low Starting Torque | | |
| 7 Expansion device | Capillary tube | | |
| 8 Compressor cooling | Operating voltage range | | |
| | | 50 Hz | 60 Hz |
| 8.1 LBP (32°C Ambient temperature) | Static | 198 to 254 V | - |
| 8.2 LBP (43°C Ambient temperature) | Static | 198 to 254 V | - |
| 8.3 HBP (32°C Ambient temperature) | - | - | - |
| 8.4 HBP (43°C Ambient temperature) | - | - | - |
| 9 Maximum condensing pressures/temperature | | | |
| 9.1 Operating (gauge) | 7.7 | [kgf/cm ²] (109 psig) | / °C - °F |
| 9.2 Peak (gauge) | 9.8 | [kgf/cm ²] (139 psig) | / °C - °F |
| 10 Maximum winding temperature | 130 | [°C] | |

B - MECHANICAL DATA

| | | |
|-------------------------------|----------------|----------------------------------|
| 1 Commercial designation | | [hp] |
| 2 Displacement | 12.11 | [cm ³] (0.739 cu.in) |
| 2.1 Bore [mm] | 27.775 | |
| 2.2 Stroke [mm] | 20.000 | |
| 3 Lubricant charge | 280 | [ml] (9.47 fl.oz.) |
| 3.1 Lubricants approved | | |
| 3.2 Lubricants type/viscosity | ALQUILB / ISO5 | |
| 4 Weight (with oil charge) | 10.73 | [kg] (23.66 lb.) |
| 5 Nitrogen charge | - | [kgf/cm ²] |

C - ELETRICAL DATA

| | | |
|--|------------------------------------|------------------------------------|
| 1 Nominal Voltage/Frequency/Number of Phases | 220-240 V 50 Hz 1 ~ (Single phase) | |
| 2 Starting device type | PTC | |
| 2.1 Starting device | MSDA3 | |
| 3 Start capacitor | - | [µF(VAC minimum)] |
| 4 Run capacitor | - | [µF(VAC minimum)] |
| 5 Motor protection | T0521/07 | |
| 6 Start winding resistance | 20.90 | [Ω at 25°C (77°F)] +/- 8% |
| 7 Run winding resistance | 17.80 | [Ω at 25°C (77°F)] +/- 8% |
| 8 LRA - Locked rotor amperage (50 Hz) | - | [A] - Measured according to UL 984 |
| 9 FLA - Full load amperage L/MBP (50 Hz) | - | [A] - Measured according to UL 984 |
| 10 FLA - Full Load Amperage HBP (50 Hz) | - | [A] - Measured according to UL 984 |
| 11 Approval boards certification | VDE | |

D - PERFORMANCE - CHECK POINT DATA

| TEST CONDITIONS: @220V50Hz | | | CECOMAFLBP Static | | Evaporating temperature (Condensing temperature | | -25°C (-13°F) 55°C (131°F) | |
|-------------------------------|----------|-----|--------------------------------|----------------------------------|--|---------------------------|-------------------------------|-------|
| Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| 522 | 132 | 153 | 125 | 0.78 | 1.99 | 4.18 | 1.05 | 1.22 |

E - PERFORMANCE - CURVES

| TEST CONDITIONS: @220V50Hz | | CECOMAF Static | | | | (Condensing temperature 35°C (+95°F)) | | | | |
|-------------------------------|-------|----------------------------|----------|-----|--------------------------------|--|----------------------------|---------------------------|-----------|-------|
| Evaporating temperature | | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C | (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 | (-31) | 405 | 102 | 119 | 84 | 0.66 | 1.30 | 4.77 | 1.20 | 1.40 |
| -30 | (-22) | 525 | 132 | 154 | 99 | 0.70 | 1.68 | 5.32 | 1.34 | 1.56 |
| -25 | (-13) | 682 | 172 | 200 | 114 | 0.74 | 2.19 | 6.03 | 1.52 | 1.77 |
| -20 | (- 4) | 878 | 221 | 257 | 128 | 0.79 | 2.82 | 6.90 | 1.74 | 2.02 |
| -15 | (+ 5) | 1113 | 281 | 326 | 141 | 0.83 | 3.58 | 7.90 | 1.99 | 2.31 |
| -10 | (+14) | 1389 | 350 | 407 | 154 | 0.88 | 4.48 | 9.03 | 2.28 | 2.65 |

| TEST CONDITIONS: @220V50Hz | | CECOMAF Static | | | | (Condensing temperature 45°C (+113°F)) | | | | |
|-------------------------------|-------|----------------------------|----------|-----|--------------------------------|---|----------------------------|---------------------------|-----------|-------|
| Evaporating temperature | | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C | (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 | (-31) | 358 | 90 | 105 | 88 | 0.67 | 1.24 | 4.06 | 1.02 | 1.19 |
| -30 | (-22) | 464 | 117 | 136 | 104 | 0.71 | 1.62 | 4.47 | 1.13 | 1.31 |
| -25 | (-13) | 603 | 152 | 177 | 121 | 0.76 | 2.10 | 4.99 | 1.26 | 1.46 |
| -20 | (- 4) | 775 | 195 | 227 | 137 | 0.82 | 2.70 | 5.61 | 1.41 | 1.64 |
| -15 | (+ 5) | 983 | 248 | 288 | 155 | 0.88 | 3.43 | 6.33 | 1.60 | 1.85 |
| -10 | (+14) | 1226 | 309 | 359 | 172 | 0.95 | 4.29 | 7.13 | 1.80 | 2.09 |

| TEST CONDITIONS: @220V50Hz | | CECOMAF Static | | | | (Condensing temperature 55°C (+131°F)) | | | | |
|-------------------------------|-------|----------------------------|----------|-----|--------------------------------|---|----------------------------|---------------------------|-----------|-------|
| Evaporating temperature | | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C | (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 | (-31) | 303 | 76 | 89 | 91 | 0.68 | 1.15 | 3.35 | 0.84 | 0.98 |
| -30 | (-22) | 397 | 100 | 116 | 108 | 0.72 | 1.51 | 3.69 | 0.93 | 1.08 |
| -25 | (-13) | 519 | 131 | 152 | 127 | 0.78 | 1.98 | 4.09 | 1.03 | 1.20 |
| -20 | (- 4) | 671 | 169 | 197 | 147 | 0.85 | 2.56 | 4.56 | 1.15 | 1.34 |
| -15 | (+ 5) | 853 | 215 | 250 | 168 | 0.93 | 3.26 | 5.07 | 1.28 | 1.49 |
| -10 | (+14) | 1066 | 269 | 312 | 189 | 1.02 | 4.09 | 5.63 | 1.42 | 1.65 |

E - PERFORMANCE - CURVES

| TEST CONDITIONS: @220V50Hz | | CECOMAF Static | | | (Condensing temperature 65°C (+149°F)) | | | | | |
|-------------------------------|-------|----------------------------|----------|-----|---|-------------------------------|-------------------------|---------------------------|-----------|-------|
| Evaporating temperature | | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C | (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 | (-31) | 238 | 60 | 70 | 93 | 0.68 | 1.00 | 2.54 | 0.64 | 0.74 |
| -30 | (-22) | 322 | 81 | 94 | 111 | 0.73 | 1.36 | 2.89 | 0.73 | 0.85 |
| -25 | (-13) | 430 | 108 | 126 | 132 | 0.80 | 1.82 | 3.26 | 0.82 | 0.95 |
| -20 | (- 4) | 562 | 142 | 165 | 155 | 0.89 | 2.38 | 3.64 | 0.92 | 1.07 |
| -15 | (+ 5) | 721 | 182 | 211 | 180 | 0.98 | 3.06 | 4.03 | 1.02 | 1.18 |
| -10 | (+14) | 906 | 228 | 265 | 206 | 1.09 | 3.86 | 4.41 | 1.11 | 1.29 |

F - EXTERNAL CHARACTERISTICS

| | | | |
|-------------------------|------------------------------|------|--------------------------|
| 1 Base plate | European Standard | | |
| 2 Tray holder | Yes | | |
| 3 Connectors | | | |
| 3.1 SUCTION | 6.1 +0.10/+0.00 | [mm] | (0.240" +0.004"/+0.000") |
| 3.1.1 Material | Copper | | |
| 3.1.2 Shape | Slanted 42° | | |
| 3.2 DISCHARGE | 4.95 +0.05/+0.05 | [mm] | (0.195" +0.002"/+0.002") |
| 3.2.1 Material | Copper | | |
| 3.2.2 Shape | Slanted parallel B.Plate 30° | | |
| 3.3 PROCESS | 6 +0.08/-0.08 | [mm] | (0.236" +0.003"/-0.003") |
| 3.3.1 Material | Copper(OD) | | |
| 3.3.2 Shape | Slanted 42° | | |
| 3.4 Oil cooler (Copper) | No | [mm] | |
| 3.5 Connector sealing | Rubber Plugs | | |