

### COMPRESSOR DEFINITION

Designation	<b>VEM B11C</b>
Nominal Voltage/Frequency	<b>230 V 53-150 Hz</b>
Engineering Number	<b>513906009</b>

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	230 / 53-150	[ V / Hz ]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	BPM		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	6.9	[kgf/cm <sup>2</sup> ] (98 psig)	/ °C - °F
9.2 Peak (gauge)	7.8	[kgf/cm <sup>2</sup> ] (111 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation		[hp]
2 Displacement	11.14	[cm <sup>3</sup> ] (0.680 cu.in)
2.1 Bore [mm]	26.000	
2.2 Stroke [mm]	21.000	
3 Lubricant charge	210	[ml] (7.10 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO5	
4 Weight (with oil charge)	7.8	[kg] (17.20 lb.)
5 Nitrogen charge	-	[kgf/cm <sup>2</sup> ]

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	230 V 53-150 Hz 3 ~ (Three phase)	
2 Starting device type	Inverter	
2.1 Starting device	CF02D01 M 0.0 X/VCC32456XXXX	
3 Start capacitor	-	[μF(VAC minimum)]
4 Run capacitor	-	[μF(VAC minimum)]
5 Motor protection	VCC32456XXXXX	
6 Start winding resistance	8.10	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	8.10	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (40/150 Hz)	2.10	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (40/150 Hz)	2.10	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (40/150 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification		

### D - PERFORMANCE - CHECK POINT DATA

### E - PERFORMANCE - CURVES

TEST CONDITIONS:		ASHRAE32			(Condensing temperature 35°C (+95°F))					
@220V1600RPM		Static								
Evaporating temperature	Cooling capacity			Power consumption	Current consumption	Gas flow rate	EFFICIENCY RATE			
	+/- 5%			+/- 5%	+/- 5%	+/- 5%	+/- 7%			
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
-35 (-31)	223	56	65	37	0.29	0.70	0.00	0.00	0.00	
-30 (-22)	229	58	67	35	0.28	0.72	0.00	0.00	0.00	
-25 (-13)	372	94	109	46	0.36	1.17	0.00	0.00	0.00	
-20 (- 4)	537	135	157	59	0.45	1.69	0.00	0.00	0.00	
-15 (+ 5)	607	153	178	63	0.47	1.91	0.00	0.00	0.00	
-10 (+14)	466	117	137	47	0.35	1.47	0.00	0.00	0.00	

TEST CONDITIONS:		ASHRAE32			(Condensing temperature 45°C (+113°F))					
@220V1600RPM		Static								
Evaporating temperature	Cooling capacity			Power consumption	Current consumption	Gas flow rate	EFFICIENCY RATE			
	+/- 5%			+/- 5%	+/- 5%	+/- 5%	+/- 7%			
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
-35 (-31)	207	52	61	38	0.31	0.65	0.00	0.00	0.00	
-30 (-22)	215	54	63	41	0.32	0.67	0.00	0.00	0.00	
-25 (-13)	361	91	106	55	0.42	1.13	0.00	0.00	0.00	
-20 (- 4)	528	133	155	68	0.52	1.66	0.00	0.00	0.00	
-15 (+ 5)	601	152	176	70	0.53	1.89	0.00	0.00	0.00	
-10 (+14)	464	117	136	52	0.39	1.46	0.00	0.00	0.00	

TEST CONDITIONS:		ASHRAE32			(Condensing temperature 35°C (+95°F))					
@220V2000RPM		Static								
Evaporating temperature	Cooling capacity			Power consumption	Current consumption	Gas flow rate	EFFICIENCY RATE			
	+/- 5%			+/- 5%	+/- 5%	+/- 5%	+/- 7%			
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
-35 (-31)	278	70	81	45	0.36	0.87	0.00	0.00	0.00	
-30 (-22)	299	75	88	46	0.36	0.93	0.00	0.00	0.00	
-25 (-13)	480	121	141	60	0.46	1.51	0.00	0.00	0.00	
-20 (- 4)	681	172	199	75	0.57	2.14	0.00	0.00	0.00	
-15 (+ 5)	761	192	223	78	0.59	2.40	0.00	0.00	0.00	
-10 (+14)	582	147	170	57	0.43	1.83	0.00	0.00	0.00	

TEST CONDITIONS:		ASHRAE32			(Condensing temperature 45°C (+113°F))					
@220V2000RPM		Static								
Evaporating temperature	Cooling capacity			Power consumption	Current consumption	Gas flow rate	EFFICIENCY RATE			
	+/- 5%			+/- 5%	+/- 5%	+/- 5%	+/- 7%			
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
-35 (-31)	265	67	78	49	0.39	0.83	0.00	0.00	0.00	
-30 (-22)	276	69	81	52	0.41	0.86	0.00	0.00	0.00	
-25 (-13)	451	114	132	68	0.53	1.42	0.00	0.00	0.00	
-20 (- 4)	651	164	191	83	0.63	2.05	0.00	0.00	0.00	
-15 (+ 5)	736	185	216	85	0.64	2.32	0.00	0.00	0.00	
-10 (+14)	565	142	165	62	0.46	1.78	0.00	0.00	0.00	

### E - PERFORMANCE - CURVES

TEST CONDITIONS:		ASHRAE32			(Condensing temperature 35°C (+95°F))					
@220V3000RPM		Static								
Evaporating temperature	Cooling capacity			Power consumption	Current consumption	Gas flow rate	EFFICIENCY RATE			
	+/- 5%			+/- 5%	+/- 5%	+/- 5%	+/- 7%			
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
-35 (-31)	413	104	121	70	0.55	1.29	5.95	1.50	1.74	
-30 (-22)	455	115	133	69	0.52	1.42	6.33	1.60	1.85	
-25 (-13)	730	184	214	92	0.68	2.29	7.84	1.98	2.30	
-20 (- 4)	1031	260	302	117	0.87	3.24	9.22	2.32	2.70	
-15 (+ 5)	1148	289	336	125	0.94	3.61	9.23	2.33	2.70	
-10 (+14)	875	221	257	93	0.70	2.76	6.61	1.66	1.94	

TEST CONDITIONS:		ASHRAE32			(Condensing temperature 45°C (+113°F))					
@220V3000RPM		Static								
Evaporating temperature	Cooling capacity			Power consumption	Current consumption	Gas flow rate	EFFICIENCY RATE			
	+/- 5%			+/- 5%	+/- 5%	+/- 5%	+/- 7%			
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
-35 (-31)	399	100	117	73	0.56	1.25	5.44	1.37	1.60	
-30 (-22)	423	107	124	76	0.56	1.32	5.50	1.39	1.61	
-25 (-13)	688	173	202	101	0.75	2.16	6.84	1.72	2.00	
-20 (- 4)	986	248	289	127	0.95	3.10	8.21	2.07	2.41	
-15 (+ 5)	1108	279	325	133	1.00	3.49	8.36	2.11	2.45	
-10 (+14)	849	214	249	98	0.74	2.67	6.04	1.52	1.77	

TEST CONDITIONS:		ASHRAE32			(Condensing temperature 55°C (+131°F))					
@220V3000RPM		Static								
Evaporating temperature	Cooling capacity			Power consumption	Current consumption	Gas flow rate	EFFICIENCY RATE			
	+/- 5%			+/- 5%	+/- 5%	+/- 5%	+/- 7%			
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
-35 (-31)	342	86	100	71	0.53	1.07	4.78	1.20	1.40	
-30 (-22)	356	90	104	79	0.58	1.11	4.54	1.14	1.33	
-25 (-13)	619	156	181	108	0.80	1.94	5.75	1.45	1.68	
-20 (- 4)	922	232	270	136	1.02	2.90	7.14	1.80	2.09	
-15 (+ 5)	1058	267	310	142	1.07	3.33	7.47	1.88	2.19	
-10 (+14)	819	206	240	104	0.79	2.58	5.48	1.38	1.60	

TEST CONDITIONS:		ASHRAE32			(Condensing temperature 35°C (+95°F))					
@220V4500RPM		Static								
Evaporating temperature	Cooling capacity			Power consumption	Current consumption	Gas flow rate	EFFICIENCY RATE			
	+/- 5%			+/- 5%	+/- 5%	+/- 5%	+/- 7%			
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
-35 (-31)	570	144	167	104	0.80	1.78	5.53	1.39	1.62	
-30 (-22)	661	167	194	109	0.79	2.07	5.78	1.46	1.69	
-25 (-13)	989	249	290	139	1.01	3.10	7.07	1.78	2.07	
-20 (- 4)	1320	333	387	169	1.25	4.15	8.27	2.08	2.42	
-15 (+ 5)	1422	358	417	172	1.30	4.48	8.25	2.08	2.42	
-10 (+14)	1063	268	312	125	0.95	3.35	5.89	1.48	1.73	

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V4500RPM		ASHRAE32 Static			(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	554	140	162	110	0.83	1.73	4.99	1.26	1.46
-30	(-22)	614	155	180	116	0.84	1.92	5.08	1.28	1.49
-25	(-13)	925	233	271	147	1.07	2.90	6.31	1.59	1.85
-20	(- 4)	1252	316	367	176	1.31	3.94	7.53	1.90	2.21
-15	(+ 5)	1364	344	400	179	1.36	4.29	7.64	1.93	2.24
-10	(+14)	1028	259	301	129	0.99	3.24	5.50	1.39	1.61

TEST CONDITIONS: @220V4500RPM		ASHRAE32 Static			(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	518	130	152	110	0.80	1.62	4.67	1.18	1.37
-30	(-22)	545	137	160	117	0.85	1.70	4.57	1.15	1.34
-25	(-13)	835	211	245	148	1.11	2.62	5.70	1.44	1.67
-20	(- 4)	1156	291	339	177	1.36	3.64	6.92	1.74	2.03
-15	(+ 5)	1275	321	374	179	1.40	4.02	7.13	1.80	2.09
-10	(+14)	960	242	281	128	1.02	3.02	5.17	1.30	1.52

### F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal EUEM		
2 Tray holder	Yes		
3 Connectors			
3.1 SUCTION	6.2 +0.05/+0.05	[mm]	(0.244" +0.002"/+0.002")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 40° up + 0° to Back		
3.2 DISCHARGE	4.9 +0.10/-0.05	[mm]	(0.193" +0.004"/-0.002")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted 0° up + 24° to Back		
3.3 PROCESS	6.2 +0.05/+0.05	[mm]	(0.244" +0.002"/+0.002")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 40° up + 45° to Back		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		