

COMPRESSOR DEFINITION

Designation	EG U90HLC
Nominal Voltage/Frequency	115 V 60 Hz
Engineering Number	513700047

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	115 / 60	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static/Fan	-	94 to 140 V
8.2 LBP (43°C Ambient temperature)	Static/Fan	-	94 to 140 V
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	16.2	[kgf/cm ²] (230 psig)	/ °C - °F
9.2 Peak (gauge)	20.6	[kgf/cm ²] (293 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/4+	[hp]
2 Displacement	7.95	[cm ³] (0.485 cu.in)
2.1 Bore [mm]	22.500	
2.2 Stroke [mm]	20.000	
3 Lubricant charge	280	[ml] (9.47 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO10	
4 Weight (with oil charge)	11.14	[kg] (24.56 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	115 V 60 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	7M4R7MD3/8EA14C3/8EA1B3/8EA21C3/8EA3B3/8EA4B3	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	20(180)	[µF(VAC minimum)]
5 Motor protection	4TM762MFBYY-53	
6 Start winding resistance	4.35	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	2.40	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	17.70	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	2.90	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	UL	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @115V60Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)		
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
950	239	278	171	1.66	5.40	5.56	1.40	1.63	

TEST CONDITIONS: @115V60Hz			ASHRAELBP32 Fan		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)		
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
950	239	278	171	1.66	5.40	5.56	1.40	1.63	

E - PERFORMANCE - CURVES

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 45°C (+113°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	507	128	149	114	1.21	2.87	4.44	1.12	1.30
-30 (-22)	700	176	205	136	1.38	3.97	5.13	1.29	1.50
-25 (-13)	934	235	274	159	1.55	5.30	5.88	1.48	1.72
-20 (- 4)	1221	308	358	183	1.74	6.95	6.68	1.68	1.96
-15 (+ 5)	1572	396	461	208	1.95	8.97	7.56	1.91	2.22
-10 (+14)	1999	504	586	234	2.18	11.46	8.53	2.15	2.50

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 55°C (+131°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	439	111	129	112	1.18	2.48	3.94	0.99	1.15
-30 (-22)	626	158	184	136	1.36	3.55	4.60	1.16	1.35
-25 (-13)	854	215	250	162	1.57	4.85	5.28	1.33	1.55
-20 (- 4)	1134	286	332	189	1.79	6.45	5.99	1.51	1.76
-15 (+ 5)	1477	372	433	219	2.04	8.43	6.75	1.70	1.98
-10 (+14)	1896	478	556	251	2.32	10.86	7.56	1.90	2.21

E - PERFORMANCE - CURVES

TEST CONDITIONS: @115V60Hz		ASHRAE32 Static			(Condensing temperature 65°C (+149°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	368	93	108	107	1.15	2.08	3.42	0.86	1.00
-30	(-22)	543	137	159	132	1.34	3.08	4.09	1.03	1.20
-25	(-13)	758	191	222	160	1.56	4.30	4.74	1.19	1.39
-20	(- 4)	1024	258	300	190	1.80	5.83	5.39	1.36	1.58
-15	(+ 5)	1354	341	397	224	2.08	7.73	6.06	1.53	1.78
-10	(+14)	1759	443	515	260	2.39	10.07	6.75	1.70	1.98

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal EG/F/AMEM version 2		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.1.1 Material	Copper		
3.1.2 Shape	Straight		
3.2 DISCHARGE	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.3.1 Material	Copper		
3.3.2 Shape	Straight		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		