

COMPRESSOR DEFINITION

| | |
|---------------------------|-----------------|
| Designation | EG X80HLC |
| Nominal Voltage/Frequency | 115-127 V 60 Hz |
| Engineering Number | 513703015 |

A - APPLICATION / LIMIT WORKING CONDITIONS

| | | | |
|------------------------------------|-----------------------------------|-----------------------------------|-------------|
| 1 Type | Hermetic reciprocating compressor | | |
| 2 Refrigerant | R-134a | | |
| 3 Nominal voltage and frequency | 115-127 / 60 | [V / Hz] | |
| 4 Application type | Low Back Pressure | | |
| 4.1 Evaporating temperature range | -35°C to -10°C | (-31°F to 14°F) | |
| 5 Motor type | RSCR | | |
| 6 Starting torque | LST - Low Starting Torque | | |
| 7 Expansion device | Capillary tube | | |
| 8 Compressor cooling | | Operating voltage range | |
| | | 50 Hz | 60 Hz |
| 8.1 LBP (32°C Ambient temperature) | Static | - | 98 to 140 V |
| 8.2 LBP (43°C Ambient temperature) | Static | - | 98 to 140 V |
| 8.3 HBP (32°C Ambient temperature) | - | - | - |
| 8.4 HBP (43°C Ambient temperature) | - | - | - |
| 9 Maximum condensing temperature | | | |
| 9.1 Operating | 14.2 | [kgf/cm ²] (202 psig) | / °C - °F |
| 9.2 Peak | 15.9 | [kgf/cm ²] (226 psig) | / °C - °F |
| 10 Maximum winding temperature | 130 | [°C] | |

B - MECHANICAL DATA

| | | |
|-------------------------------|---------------|--|
| 1 Commercial designation | 1/4 | [hp] |
| 2 Displacement | 6.36 | [cm ³] (0.388 cu.in) |
| 2.1 Bore [mm] | 22.500 | |
| 2.2 Stroke [mm] | 16.000 | |
| 3 Lubricant charge | 280 | [ml] (9.47 fl.oz.) |
| 3.1 Lubricants approved | | |
| 3.2 Lubricants type/viscosity | ESTER / ISO10 | |
| 4 Weight (with oil charge) | 11.01 | [kg] (24.27 lb.) |
| 5 Nitrogen charge | 0.2 to 0.3 | [kgf/cm ²] (2.84 to 4.27 psig) |

C - ELETRICAL DATA

| | | |
|--|------------------------------------|------------------------------------|
| 1 Nominal Voltage/Frequency/Number of Phases | 115-127 V 60 Hz 1 ~ (Single phase) | |
| 2 Starting device type | TSD | |
| 2.1 Starting device | TSD- 115V/TSD2-115V | |
| 3 Start capacitor | - | [µF(VAC minimum)] |
| 4 Run capacitor | 12(180) | [µF(VAC minimum)] |
| 5 Motor protection | BT110-120 | |
| 6 Start winding resistance | 5.60 | [Ω at 25°C (77°F)] +/- 8% |
| 7 Run winding resistance | 3.50 | [Ω at 25°C (77°F)] +/- 8% |
| 8 LRA - Locked rotor amperage (60 Hz) | 13.00 | [A] - Measured according to UL 984 |
| 9 FLA - Full load amperage L/MBP (60 Hz) | 1.70 | [A] - Measured according to UL 984 |
| 10 FLA - Full Load Amperage HBP (60 Hz) | - | [A] - Measured according to UL 984 |
| 11 Approval boards certification | CE - NOM - UKCA - UL | |

D - PERFORMANCE - CHECK POINT DATA

| | | | | | | | | |
|-------------------------------|----------|-----|--------------------------------|----------------------------------|--|---------------------------|--|-------|
| TEST CONDITIONS: @115V60Hz | | | ASHRAELBP32 Static | | Evaporating temperature (Condensing temperature | | -23.3°C (-9.94°F) 54.4°C (129.92°F) | |
| Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| 815 | 205 | 239 | 133 | 1.18 | 4.63 | 6.15 | 1.55 | 1.80 |

E - PERFORMANCE - CURVES

| | | | | | | | | | |
|-------------------------------|----------------------------|----------|--------------------|--------------------------------|--|----------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS: @115V60Hz | | | ASHRAE32 Static | | (Condensing temperature 45°C (+113°F)) | | | | |
| Evaporating temperature | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 (-31) | 401 | 101 | 117 | 86 | 0.78 | 2.27 | 4.64 | 1.17 | 1.36 |
| -30 (-22) | 602 | 152 | 176 | 106 | 0.95 | 3.41 | 5.66 | 1.43 | 1.66 |
| -25 (-13) | 823 | 207 | 241 | 125 | 1.11 | 4.67 | 6.60 | 1.66 | 1.93 |
| -20 (- 4) | 1074 | 271 | 315 | 143 | 1.27 | 6.11 | 7.52 | 1.90 | 2.20 |
| -15 (+ 5) | 1366 | 344 | 400 | 161 | 1.43 | 7.80 | 8.49 | 2.14 | 2.49 |
| -10 (+14) | 1710 | 431 | 501 | 178 | 1.58 | 9.80 | 9.58 | 2.42 | 2.81 |

| | | | | | | | | | |
|-------------------------------|----------------------------|----------|--------------------|--------------------------------|--|----------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS: @115V60Hz | | | ASHRAE32 Static | | (Condensing temperature 55°C (+131°F)) | | | | |
| Evaporating temperature | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 (-31) | 324 | 82 | 95 | 77 | 0.70 | 1.83 | 4.19 | 1.06 | 1.23 |
| -30 (-22) | 517 | 130 | 151 | 100 | 0.90 | 2.93 | 5.12 | 1.29 | 1.50 |
| -25 (-13) | 734 | 185 | 215 | 123 | 1.11 | 4.17 | 5.94 | 1.50 | 1.74 |
| -20 (- 4) | 988 | 249 | 289 | 147 | 1.32 | 5.62 | 6.72 | 1.69 | 1.97 |
| -15 (+ 5) | 1287 | 324 | 377 | 171 | 1.53 | 7.35 | 7.51 | 1.89 | 2.20 |
| -10 (+14) | 1644 | 414 | 482 | 195 | 1.75 | 9.42 | 8.40 | 2.12 | 2.46 |

| | | | | | | | | | |
|-------------------------------|----------------------------|----------|--------------------|--------------------------------|--|----------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS: @115V60Hz | | | ASHRAE32 Static | | (Condensing temperature 65°C (+149°F)) | | | | |
| Evaporating temperature | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 (-31) | 248 | 63 | 73 | 71 | 0.65 | 1.41 | 3.53 | 0.89 | 1.03 |
| -30 (-22) | 426 | 107 | 125 | 95 | 0.86 | 2.41 | 4.45 | 1.12 | 1.30 |
| -25 (-13) | 633 | 159 | 185 | 121 | 1.09 | 3.59 | 5.24 | 1.32 | 1.53 |
| -20 (- 4) | 881 | 222 | 258 | 148 | 1.32 | 5.01 | 5.95 | 1.50 | 1.74 |
| -15 (+ 5) | 1181 | 298 | 346 | 177 | 1.57 | 6.74 | 6.66 | 1.68 | 1.95 |
| -10 (+14) | 1542 | 389 | 452 | 206 | 1.83 | 8.84 | 7.44 | 1.88 | 2.18 |

F - EXTERNAL CHARACTERISTICS

| | | | |
|-------------------------|-----------------|------|--------------------------|
| 1 Base plate | Universal | | |
| 2 Tray holder | No | | |
| 3 Connectors | | | |
| 3.1 SUCTION | 6.5 +0.12/-0.08 | [mm] | (0.256" +0.005"/-0.003") |
| 3.1.1 Material | Copper | | |
| 3.1.2 Shape | Straight | | |
| 3.2 DISCHARGE | 6.5 +0.12/-0.08 | [mm] | (0.256" +0.005"/-0.003") |
| 3.2.1 Material | Copper | | |
| 3.2.2 Shape | Straight | | |
| 3.3 PROCESS | 6.5 +0.12/-0.08 | [mm] | (0.256" +0.005"/-0.003") |
| 3.3.1 Material | Copper | | |
| 3.3.2 Shape | Straight | | |
| 3.4 Oil cooler (Copper) | No | [mm] | |
| 3.5 Connector sealing | Rubber Plugs | | |