

COMPRESSOR DEFINITION

Designation	NE K6160Z
Nominal Voltage/Frequency	115 V 60 Hz
Engineering Number	267BG92

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	115 / 60	[V / Hz]	
4 Application type	High Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-15°C to 10°C	(5°F to 50°F)	
5 Motor type	CSIR		
6 Starting torque	HST - Hight starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	14.2	[kgf/cm ²] (202 psig)	/ °C - °F
9.2 Peak	15.9	[kgf/cm ²] (226 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/4	[hp]
2 Displacement	7.28	[cm ³] (0.444 cu.in)
2.1 Bore [mm]	26.497	
2.2 Stroke [mm]	13.200	
3 Lubricant charge	350	[ml] (11.84 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	10.4	[kg] (22.93 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	115 V 60 Hz 1~ (Single phase)	
2 Starting device type	Current Relay	
2.1 Starting device	MTRPH-0019	
3 Start capacitor	145-175(165)	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	T0590/G9	
6 Start winding resistance	6.14	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	1.24	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	-	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	IMQ - UL	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @115V60Hz			ASHRAEHBP46 Fan		Evaporating temperature (Condensing temperature		7.2°C (44.96°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
2884	727	845	360	4.66	18.70	8.01	2.02	2.35

E - PERFORMANCE - CURVES

TEST CONDITIONS: @115V60Hz		ASHRAE46 Fan				(Condensing temperature 35°C (+95°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+5)	1396	352	409	217	3.89	7.55	6.42	1.62	1.88
-10	(+14)	1754	442	514	235	3.93	9.52	7.46	1.88	2.18
-5	(+23)	2178	549	638	252	4.01	11.87	8.65	2.18	2.53
0	(+32)	2668	672	782	268	4.13	14.60	9.96	2.51	2.92
+5	(+41)	3224	813	945	284	4.31	17.74	11.35	2.86	3.33
+10	(+50)	3846	969	1127	300	4.53	21.30	12.80	3.22	3.75

TEST CONDITIONS: @115V60Hz		ASHRAE46 Fan				(Condensing temperature 45°C (+113°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+5)	1214	306	356	227	3.94	7.10	5.37	1.35	1.57
-10	(+14)	1556	392	456	251	4.02	9.12	6.19	1.56	1.81
-5	(+23)	1968	496	577	274	4.13	11.58	7.16	1.80	2.10
0	(+32)	2451	618	718	297	4.27	14.50	8.24	2.08	2.42
+5	(+41)	3004	757	880	319	4.44	17.88	9.41	2.37	2.76
+10	(+50)	3627	914	1063	341	4.65	21.74	10.63	2.68	3.12

TEST CONDITIONS: @115V60Hz		ASHRAE46 Fan				(Condensing temperature 55°C (+131°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+5)	1051	265	308	238	4.02	6.69	4.40	1.11	1.29
-10	(+14)	1335	336	391	267	4.13	8.54	5.00	1.26	1.47
-5	(+23)	1695	427	497	295	4.26	10.89	5.75	1.45	1.69
0	(+32)	2129	536	624	322	4.41	13.75	6.62	1.67	1.94
+5	(+41)	2638	665	773	348	4.58	17.15	7.57	1.91	2.22
+10	(+50)	3222	812	944	376	4.77	21.09	8.57	2.16	2.51

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.1 +0.10/+0.00	[mm]	(0.319" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		