

### COMPRESSOR DEFINITION

Designation	EM 2U60HLP
Nominal Voltage/Frequency	220 V 60 Hz
Engineering Number	513305505

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	220 / 60	[ V / Hz ]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	-	198 to 242 V
8.2 LBP (43°C Ambient temperature)	Static	-	198 to 242 V
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	14.2	[kgf/cm <sup>2</sup> ] (202 psig)	/ °C - °F
9.2 Peak	15.9	[kgf/cm <sup>2</sup> ] (226 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation	1/5	[hp]
2 Displacement	5.54	[cm <sup>3</sup> ] (0.338 cu.in)
2.1 Bore [mm]	21.000	
2.2 Stroke [mm]	16.000	
3 Lubricant charge	150	[ml] (5.07 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO10	
4 Weight (with oil charge)	7.23	[kg] (15.94 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm <sup>2</sup> ] (2.84 to 4.27 psig)

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220 V 60 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	7M220MD3/8EA17C3/8EA17E61/8EA17E62/8EA17E63/8M220I	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	3(350)/4(350)/5(350)	[µF(VAC minimum)]
5 Motor protection	CP4TMC291K61	
6 Start winding resistance	26.16	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	19.35	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50/60 Hz)	7.00/6.65	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50/60 Hz)	1.33/1.02	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50/60 Hz)	1.52/1.23	[A] - Measured according to UL 984
11 Approval boards certification	IMTRO - TUV	

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V60Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
614	155	180	116	0.55	3.49	5.29	1.33	1.55

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V60Hz		ASHRAE32 Static				(Condensing temperature 35°C (+95°F) )				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	381	96	112	78	0.47	2.16	4.85	1.22	1.42
-30	(-22)	520	131	152	91	0.49	2.95	5.71	1.44	1.67
-25	(-13)	687	173	201	105	0.52	3.90	6.58	1.66	1.93
-20	(- 4)	890	224	261	119	0.56	5.06	7.49	1.89	2.20
-15	(+ 5)	1137	287	333	134	0.61	6.49	8.47	2.13	2.48
-10	(+14)	1437	362	421	150	0.66	8.23	9.54	2.40	2.80

TEST CONDITIONS: @220V60Hz		ASHRAE32 Static				(Condensing temperature 45°C (+113°F) )				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	338	85	99	79	0.50	1.91	4.31	1.08	1.26
-30	(-22)	470	118	138	92	0.51	2.67	5.08	1.28	1.49
-25	(-13)	629	159	184	108	0.54	3.57	5.84	1.47	1.71
-20	(- 4)	823	207	241	125	0.58	4.68	6.60	1.66	1.93
-15	(+ 5)	1060	267	311	143	0.63	6.05	7.39	1.86	2.17
-10	(+14)	1348	340	395	163	0.69	7.72	8.25	2.08	2.42

TEST CONDITIONS: @220V60Hz		ASHRAE32 Static				(Condensing temperature 55°C (+131°F) )				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	294	74	86	78	0.50	1.66	3.79	0.96	1.11
-30	(-22)	419	106	123	93	0.51	2.38	4.51	1.14	1.32
-25	(-13)	570	144	167	110	0.54	3.24	5.18	1.31	1.52
-20	(- 4)	755	190	221	130	0.59	4.30	5.82	1.47	1.71
-15	(+ 5)	981	247	287	151	0.65	5.60	6.47	1.63	1.89
-10	(+14)	1257	317	368	176	0.72	7.20	7.15	1.80	2.10

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V60Hz		ASHRAE32 Static			(Condensing temperature 65°C (+149°F) )					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	247	62	72	75	0.48	1.40	3.27	0.82	0.96
-30	(-22)	366	92	107	92	0.49	2.07	3.97	1.00	1.16
-25	(-13)	509	128	149	111	0.53	2.89	4.57	1.15	1.34
-20	(- 4)	684	172	200	134	0.59	3.89	5.13	1.29	1.50
-15	(+ 5)	900	227	264	160	0.67	5.14	5.66	1.43	1.66
-10	(+14)	1165	293	341	188	0.76	6.67	6.19	1.56	1.81

### F - EXTERNAL CHARACTERISTICS

1 Base plate	New Base Plate EUEM		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42° up + 45° to Back		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted 30° up + 24° to Back		
3.3 PROCESS	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 45° up + 45° to Back		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		