

COMPRESSOR DEFINITION

Designation	EM T65HLR
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	513300104

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSIR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	187 to 255 V	-
8.2 LBP (43°C Ambient temperature)	Static	187 to 255 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	14.2	[kgf/cm ²] (202 psig)	/ °C - °F
9.2 Peak	15.9	[kgf/cm ²] (226 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/4	[hp]
2 Displacement	5.96	[cm ³] (0.364 cu.in)
2.1 Bore [mm]	22.500	
2.2 Stroke [mm]	15.000	
3 Lubricant charge	180	[ml] (6.09 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	7.8	[kg] (17.20 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	Current Relay	
2.1 Starting device	213514130	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	MSP63AHJ-5590	
6 Start winding resistance		[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance		[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	-	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	CCC - VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
614	155	180	132	0.91	3.49	4.64	1.17	1.36

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		ASHRAE32 Static				(Condensing temperature 35°C (+95°F))			
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	407	103	119	92	0.81	2.30	4.42	1.11	1.30
-30 (-22)	546	138	160	104	0.83	3.09	5.29	1.33	1.55
-25 (-13)	720	181	211	116	0.86	4.09	6.21	1.57	1.82
-20 (- 4)	932	235	273	129	0.90	5.30	7.19	1.81	2.11
-15 (+ 5)	1185	299	347	144	0.94	6.76	8.23	2.07	2.41
-10 (+14)	1481	373	434	159	0.99	8.48	9.32	2.35	2.73

TEST CONDITIONS: @220V50Hz		ASHRAE32 Static				(Condensing temperature 45°C (+113°F))			
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	344	87	101	94	0.81	1.95	3.69	0.93	1.08
-30 (-22)	472	119	138	107	0.84	2.68	4.41	1.11	1.29
-25 (-13)	630	159	185	122	0.87	3.58	5.15	1.30	1.51
-20 (- 4)	820	207	240	138	0.92	4.67	5.92	1.49	1.73
-15 (+ 5)	1045	263	306	155	0.98	5.96	6.71	1.69	1.97
-10 (+14)	1307	329	383	173	1.04	7.49	7.53	1.90	2.21

TEST CONDITIONS: @220V50Hz		ASHRAE32 Static				(Condensing temperature 55°C (+131°F))			
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	290	73	85	92	0.81	1.64	3.15	0.79	0.92
-30 (-22)	412	104	121	109	0.84	2.34	3.76	0.95	1.10
-25 (-13)	558	141	163	127	0.89	3.17	4.37	1.10	1.28
-20 (- 4)	730	184	214	147	0.94	4.15	4.96	1.25	1.45
-15 (+ 5)	931	235	273	168	1.01	5.31	5.55	1.40	1.63
-10 (+14)	1164	293	341	190	1.09	6.67	6.14	1.55	1.80

F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard EUEM		
2 Tray holder	Yes		
3 Connectors			
3.1 SUCTION	6.2 +0.05/+0.05	[mm]	(0.244" +0.002"/+0.002")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 40° up + 45° to Back		
3.2 DISCHARGE	4.9 +0.10/-0.05	[mm]	(0.193" +0.004"/-0.002")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted 0° up + 24° to Back		
3.3 PROCESS	6.2 +0.05/+0.05	[mm]	(0.244" +0.002"/+0.002")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 40° up + 45° to Back		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		