

### COMPRESSOR DEFINITION

Designation	EM TE2134U
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	513300296

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-290		
3 Nominal voltage and frequency	220-240 / 50	[ V / Hz ]	
4 Application type	Very Low Back Pressure		
4.1 Evaporating temperature range	-45°C to -10°C	(-49°F to 14°F)	
5 Motor type	CSIR		
6 Starting torque	HST - High starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	19.1	[kgf/cm <sup>2</sup> ] (272 psig)	/ °C - °F
9.2 Peak (gauge)	21.2	[kgf/cm <sup>2</sup> ] (301 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation	1/3	[hp]
2 Displacement	9.50	[cm <sup>3</sup> ] (0.580 cu.in)
2.1 Bore [mm]	24.000	
2.2 Stroke [mm]	21.000	
3 Lubricant charge	210	[ml] (7.10 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	8.6	[kg] (18.96 lb.)
5 Nitrogen charge	-	[kgf/cm <sup>2</sup> ]

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	Current Relay	
2.1 Starting device	QL2-6.4	
3 Start capacitor	88-108(250)	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	MST304AMZ-3259	
6 Start winding resistance	22.33	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	7.89	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	14.90	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	2.69	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	3.04	[A] - Measured according to UL 984
11 Approval boards certification	VDE	

**D - PERFORMANCE - CHECK POINT DATA**

---

**E - PERFORMANCE - CURVES**

---

### F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard EUEM		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.2 +0.12/-0.08	[mm]	(0.323" +0.005"/-0.003")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 40° up + 45° to Back		
3.2 DISCHARGE	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted 0° up + 24° to Back		
3.3 PROCESS	6.2 +0.05/+0.05	[mm]	(0.244" +0.002"/+0.002")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 40° up + 45° to Back		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		