

COMPRESSOR DEFINITION

Designation	EG YS110CLC
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	513701337

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	187 to 255 V	-
8.2 LBP (43°C Ambient temperature)	Static	187 to 255 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	6.9	[kgf/cm ²] (98 psig)	/ °C - °F
9.2 Peak	7.8	[kgf/cm ²] (111 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/3	[hp]
2 Displacement	14.77	[cm ³] (0.901 cu.in)
2.1 Bore [mm]	28.000	
2.2 Stroke [mm]	24.000	
3 Lubricant charge	280	[ml] (9.47 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO5	
4 Weight (with oil charge)	10.98	[kg] (24.21 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	8EA17C3/8EA17E61/QPS2-A22MD3	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	5(330)	[µF(VAC minimum)]
5 Motor protection	4TM283KFBYY-53	
6 Start winding resistance	18.60	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	13.27	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	-	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification		

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAE LBP-NOFAN Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
848	214	248	148		2.66	5.73	1.44	1.68

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		ASHRAE32-NOFAN Static				(Condensing temperature 35°C (+95°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
-35 (-31)	580	146	170	95	0.48	1.82	6.03	1.52	1.77	
-30 (-22)	686	173	201	108	0.53	2.15	6.44	1.62	1.89	
-25 (-13)	844	213	247	120	0.58	2.65	7.11	1.79	2.08	
-20 (- 4)	1060	267	311	134	0.64	3.33	8.00	2.02	2.34	
-15 (+ 5)	1340	338	393	149	0.71	4.22	9.01	2.27	2.64	
-10 (+14)	1690	426	495	167	0.79	5.33	10.09	2.54	2.96	

TEST CONDITIONS: @220V50Hz		ASHRAE32-NOFAN Static				(Condensing temperature 45°C (+113°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
-35 (-31)	460	116	135	100	0.49	1.44	4.73	1.19	1.39	
-30 (-22)	618	156	181	115	0.56	1.94	5.36	1.35	1.57	
-25 (-13)	823	207	241	131	0.63	2.58	6.23	1.57	1.82	
-20 (- 4)	1082	273	317	147	0.70	3.40	7.27	1.83	2.13	
-15 (+ 5)	1400	353	410	165	0.78	4.41	8.42	2.12	2.47	
-10 (+14)	1783	449	523	185	0.88	5.63	9.59	2.42	2.81	

TEST CONDITIONS: @220V50Hz		ASHRAE32-NOFAN Static				(Condensing temperature 55°C (+131°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
-35 (-31)	414	104	121	103	0.51	1.30	4.07	1.03	1.19	
-30 (-22)	581	146	170	122	0.59	1.82	4.69	1.18	1.37	
-25 (-13)	791	199	232	141	0.67	2.48	5.52	1.39	1.62	
-20 (- 4)	1049	264	308	160	0.76	3.30	6.49	1.64	1.90	
-15 (+ 5)	1363	344	399	181	0.85	4.29	7.53	1.90	2.21	
-10 (+14)	1738	438	509	203	0.96	5.48	8.58	2.16	2.51	

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		ASHRAE32-NOFAN Static			(Condensing temperature 65°C (+149°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	421	106	123	106	0.52	1.32	3.92	0.99	1.15
-30	(-22)	554	140	162	129	0.62	1.74	4.29	1.08	1.26
-25	(-13)	726	183	213	151	0.72	2.28	4.85	1.22	1.42
-20	(- 4)	943	238	276	173	0.82	2.96	5.52	1.39	1.62
-15	(+ 5)	1209	305	354	197	0.93	3.81	6.23	1.57	1.83
-10	(+14)	1532	386	449	223	1.05	4.83	6.92	1.74	2.03

F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	Yes		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted		
3.3 PROCESS	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		