

COMPRESSOR DEFINITION

Designation	EM D26CLT
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	700PA98

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	187 to 255 V	-
8.2 LBP (43°C Ambient temperature)	Static	187 to 255 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	6.9	[kgf/cm ²] (98 psig)	/ °C - °F
9.2 Peak	7.8	[kgf/cm ²] (111 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/10	[hp]
2 Displacement	5.19	[cm ³] (0.317 cu.in)
2.1 Bore [mm]	21.000	
2.2 Stroke [mm]	15.000	
3 Lubricant charge	150	[ml] (5.07 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO5	
4 Weight (with oil charge)	7.9	[kg] (17.42 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	TSD	
2.1 Starting device	MI.E-START 2021	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	2.5(350)/2(350)	[µF(VAC minimum)]
5 Motor protection	AX24BNXX	
6 Start winding resistance	22.40	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	40.44	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	2.77	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	0.40	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	0.48	[A] - Measured according to UL 984
11 Approval boards certification	VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAE LBP-NOFAN Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
274	69	80	43	0.20	0.86	6.42	1.62	1.88

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		ASHRAE32-NOFAN Static				(Condensing temperature 35°C (+95°F))			
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	155	39	46	27	0.13	0.49	5.66	1.43	1.66
-30 (-22)	223	56	65	33	0.16	0.70	6.74	1.70	1.98
-25 (-13)	299	75	88	38	0.18	0.94	7.85	1.98	2.30
-20 (- 4)	387	97	113	43	0.20	1.21	9.02	2.27	2.64
-15 (+ 5)	489	123	143	48	0.22	1.54	10.30	2.60	3.02
-10 (+14)	610	154	179	52	0.25	1.93	11.74	2.96	3.44

TEST CONDITIONS: @220V50Hz		ASHRAE32-NOFAN Static				(Condensing temperature 45°C (+113°F))			
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	140	35	41	29	0.14	0.44	4.93	1.24	1.45
-30 (-22)	204	51	60	34	0.17	0.64	5.94	1.50	1.74
-25 (-13)	277	70	81	40	0.19	0.87	6.91	1.74	2.02
-20 (- 4)	361	91	106	46	0.21	1.14	7.89	1.99	2.31
-15 (+ 5)	461	116	135	51	0.24	1.45	8.93	2.25	2.62
-10 (+14)	579	146	170	57	0.27	1.83	10.07	2.54	2.95

TEST CONDITIONS: @220V50Hz		ASHRAE32-NOFAN Static				(Condensing temperature 55°C (+131°F))			
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	120	30	35	29	0.14	0.37	4.22	1.06	1.24
-30 (-22)	180	45	53	35	0.17	0.57	5.18	1.30	1.52
-25 (-13)	249	63	73	41	0.19	0.78	6.05	1.52	1.77
-20 (- 4)	331	83	97	48	0.22	1.04	6.87	1.73	2.01
-15 (+ 5)	427	108	125	55	0.25	1.35	7.70	1.94	2.26
-10 (+14)	543	137	159	63	0.29	1.71	8.57	2.16	2.51

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		ASHRAE32-NOFAN Static			(Condensing temperature 65°C (+149°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	96	24	28	26	0.13	0.30	3.64	0.92	1.07
-30	(-22)	153	38	45	33	0.16	0.48	4.59	1.16	1.34
-25	(-13)	219	55	64	41	0.19	0.69	5.39	1.36	1.58
-20	(- 4)	297	75	87	49	0.23	0.93	6.09	1.54	1.79
-15	(+ 5)	390	98	114	58	0.27	1.23	6.74	1.70	1.97
-10	(+14)	503	127	147	68	0.31	1.59	7.37	1.86	2.16

F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	Yes		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42° up + 45° to Back		
3.2 DISCHARGE	5.1 +0.10/+0.00	[mm]	(0.201" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted 42° up + 45° to Back		
3.3 PROCESS	6 +0.08/-0.08	[mm]	(0.236" +0.003"/-0.003")
3.3.1 Material	Copper(OD)		
3.3.2 Shape	Slanted 43° up + 45° to Back		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		