

COMPRESSOR DEFINITION

Designation	EM 2X1125U
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	513300412

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-290		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Very Low Back Pressure		
4.1 Evaporating temperature range	-45°C to -10°C	(-49°F to 14°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	19.1	[kgf/cm ²] (272 psig)	/ °C - °F
9.2 Peak (gauge)	21.2	[kgf/cm ²] (301 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/2.5	[hp]
2 Displacement	6.09	[cm ³] (0.372 cu.in)
2.1 Bore [mm]	21.000	
2.2 Stroke [mm]	17.600	
3 Lubricant charge	150	[ml] (5.07 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO10	
4 Weight (with oil charge)	8.23	[kg] (18.14 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	TSD	
2.1 Starting device	TSD2-220V/TSD2-D-220V	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	5(350)	[µF(VAC minimum)]
5 Motor protection	4TM283KFBYY-73	
6 Start winding resistance	12.60	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	12.10	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	8.40	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	2.45	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	3.00	[A] - Measured according to UL 984
11 Approval boards certification		

D - PERFORMANCE - CHECK POINT DATA

E - PERFORMANCE - CURVES

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal EUEM		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.2 +0.05/+0.05	[mm]	(0.244" +0.002"/+0.002")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 40° up + 45° to Back		
3.2 DISCHARGE	4.9 +0.10/-0.05	[mm]	(0.193" +0.004"/-0.002")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted 0° up + 24° to Back		
3.3 PROCESS	6.2 +0.05/+0.05	[mm]	(0.244" +0.002"/+0.002")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 40° up + 45° to Back		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		