

COMPRESSOR DEFINITION

Designation	NE K2134GK
Nominal Voltage/Frequency	208-230 V 60 Hz
Engineering Number	959DD71

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-404A		
3 Nominal voltage and frequency	208-230 / 60	[V / Hz]	
4 Application type	Low Back Pressure R404A		
4.1 Evaporating temperature range	-40°C to -10°C	(-40°F to 14°F)	
5 Motor type	CSIR		
6 Starting torque	HST - High starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	25.2	[kgf/cm ²] (358 psig)	/ °C - °F
9.2 Peak	28.3	[kgf/cm ²] (402 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/2	[hp]
2 Displacement	8.77	[cm ³] (0.535 cu.in)
2.1 Bore [mm]	26.497	
2.2 Stroke [mm]	15.920	
3 Lubricant charge	350	[ml] (11.84 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	11.6	[kg] (25.57 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	208-230 V 60 Hz 1~ (Single phase)	
2 Starting device type	Current Relay	
2.1 Starting device	MTRP-49	
3 Start capacitor	64-77(330)	[μF(VAC minimum)]
4 Run capacitor	-	[μF(VAC minimum)]
5 Motor protection	T0660/J5	
6 Start winding resistance	15.30	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	3.60	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	-	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	UL	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @208V60Hz			ASHRAELBP32 Fan		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
1858	468	544	420	2.80	12.60	4.42	1.11	1.30

E - PERFORMANCE - CURVES

TEST CONDITIONS: @208V60Hz			ASHRAE32 Fan		(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	877	221	257	245	2.21	5.89	3.57	0.90	1.05
-35	(-31)	1160	292	340	285	2.33	7.82	4.08	1.03	1.20
-30	(-22)	1515	382	444	325	2.46	10.25	4.66	1.18	1.37
-25	(-13)	1943	490	569	365	2.60	13.20	5.32	1.34	1.56
-20	(- 4)	2443	616	716	406	2.75	16.68	6.01	1.52	1.76
-15	(+ 5)	3016	760	884	448	2.92	20.72	6.74	1.70	1.98
-10	(+14)	3662	923	1073	489	3.10	25.33	7.48	1.89	2.19

TEST CONDITIONS: @208V60Hz			ASHRAE32 Fan		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	790	199	231	244	2.21	5.30	3.24	0.82	0.95
-35	(-31)	1062	268	311	290	2.34	7.15	3.66	0.92	1.07
-30	(-22)	1406	354	412	338	2.50	9.49	4.15	1.05	1.22
-25	(-13)	1821	459	534	387	2.67	12.35	4.70	1.18	1.38
-20	(- 4)	2308	582	676	437	2.86	15.73	5.28	1.33	1.55
-15	(+ 5)	2867	722	840	488	3.07	19.66	5.88	1.48	1.72
-10	(+14)	3497	881	1025	540	3.30	24.14	6.48	1.63	1.90

TEST CONDITIONS: @208V60Hz			ASHRAE32 Fan		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	707	178	207	233	2.17	4.73	3.03	0.76	0.89
-35	(-31)	966	243	283	286	2.33	6.49	3.39	0.85	0.99
-30	(-22)	1296	327	380	341	2.51	8.73	3.80	0.96	1.11
-25	(-13)	1696	427	497	399	2.72	11.48	4.25	1.07	1.25
-20	(- 4)	2167	546	635	459	2.95	14.74	4.72	1.19	1.38
-15	(+ 5)	2709	683	794	521	3.21	18.54	5.20	1.31	1.52
-10	(+14)	3322	837	973	585	3.49	22.89	5.67	1.43	1.66

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.1 +0.10/+0.00	[mm]	(0.319" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		